



## RECOMMENDED CARE

**CARE FOR THE SCREEN** Caring for your Fresh Air Screen is a breeze. It can be left up all year long, or it can be removed for storage. Please do not use sharp objects on your screen, as this can damage your screen and void any return/warranty policies. To add roofing nails for extra hold; please apply this to the adhesive loop only. Your screen can be easily removed and stored until you are ready to use again. Remove any nails from the adhesive loop (if applied). Gently wash your screen with soap and water. Allow the screen to dry thoroughly before storing.

**CARE FOR THE ADHESIVE LOOP** Make sure the surface of the frame is clean and dry before applying the adhesive loop strip. You can use isopropyl alcohol and water, but avoid harsh chemicals, silicone sprays or cleaners that leave a sticky or oily residue, as this can affect your application. Make sure the area has dried fully before applying the adhesive loop strip. Allow the tape to fully cure prior to installing your screen. To do this, apply the adhesive loop strip and let it sit for 24 hours, then fasten your screen to it, using the instructions provided. This will allow the adhesion to work at its full strength before adding the weight of the screen. It is common for adhesive loop strips to be lifted first at the corners. If you find this to be the case with your screen, try rounding off the corners with a pair of scissors. This will reduce the likelihood of the corners catching and lifting. Some areas that are exposed to extreme temperatures or weather conditions may experience some difficulty with maintaining proper adhesion. It is okay to apply roofing nails, marine screws, or similar binding to the adhesive loop strip. If you choose this option, be sure to avoid puncturing the screen itself with sharp points or edges.

**CARE FOR ZIPPERS** Fresh Air Screens feature heavy-duty zippers that do not require special attention for everyday use. The following are tips to troubleshoot zipper issues that may occur. **Is your zipper not zipping?** Nothing is more frustrating than sliding the zipper pull and finding out that nothing happened. This could simply be a slider issue that can be solved with a plier. Narrow both side gaps, then the vertical (up and down) gap to tighten it. Adjustments should be very slight, as it may not take much to restore it to full use. Check the slider, then adjust it again if necessary. **Is your zipper stuck?** Usually, this is not a difficult problem to solve as it is usually stuck on a thread or hair. The solution is as simple as finding the blockage and removing it. If you do not see a blockage, check the alignment of the teeth. Fixing an alignment issue in the teeth might be a bit more complicated, so check with a representative to see what options fit your scenario best! **Is the pull tab broken?** It's not too common for a pull tab to break on the heavy-duty zippers used on Fresh Air Screens, but anything is possible! Simply insert a metal ring, thin wire or even a paperclip into the slider to replace the pull.

**CARE FOR ROD POCKETS** Use caution when inserting the rods. If they are cut sharp or jagged, they may catch on the stitching or fibers and tear the material. Sand down the edges or put rubber caps on the ends to prevent damage. Inserting too much weight on the screen can cause pulling on the adhesive loop or stitching. If you find signs of stretching or tearing, replace your rod with a light weight. When inserting the rod - do not force the rod through. Work slowly and adjust the material if you feel any tension to prevent forceful damage.

## USAGE AGREEMENT

***Fresh Air Screens® are specifically designed to act as a door screen for garages, porches, patios, and similar structures. The use of a Fresh Air Screen® can improve ventilation in these structures. They are specifically designed to not interfere with associated mechanisms such as garage doors. Fresh Air Screens, Inc. does not condone the use of the Fresh Air Screen®, for any other purpose or structure listed above. Any usage outside of this agreement voids the Manufacturing Warranty, and Fresh Air Screens, Inc. will not be held liable for any damage to the structure, person, or any other property incurred from misuse. Please follow the instructions provided with the product or online at [www.freshairscreens.com](http://www.freshairscreens.com) for appropriate usage and care.***

## SAFETY DISCLAIMER

***FRESH AIR SCREENS ARE NOT DESIGNED TO BE A SECURITY WALL AND WILL NOT PREVENT CHILDREN, ADULTS, OR AGGRESSIVE ANIMALS FROM GETTING IN OR OUT OF THE ENCLOSED AREA.***

***ROPES INCLUDED IN CERTAIN ACCESSORIES MAY POSE A STRANGULATION HAZARD. FRESH AIR SCREENS OFFERS SCREEN MODELS WITHOUT ROPE ACCESSORIES, AS A SAFER CHOICE FOR SMALL CHILDREN AND ANIMALS. MAY CONTAIN SMALL PARTS. \*NEVER LEAVE CHILDREN UNATTENDED.***