

SAFETY DATA SHEET

Issuing Date 04-Aug-2016

Revision Date 02-Aug-2016

Revision Number 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name NI-MH AA1800mAh 4.8V

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Nickel Metal Hydride (NiMH) Battery

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Guangdong TianQiu Electronics Technology Co.,Ltd.

Supplier Address 9/F TianQiu Building No.16-30, He Yi Rd., San Yuan Li Ave., GuangZhou China
GUANGZHOU
GUANDONG
510410
CN

Supplier Phone Number Phone:8620-36322277
Fax:8620-36322277

Supplier Email tq.cosong@163.com

Emergency telephone number

Company Emergency Phone Number 8620-13825131170

2. HAZARDS IDENTIFICATION

Classification


This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4



Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Germ cell mutagenicity	Category 2
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements**Emergency Overview**

Signal word	Danger
Hazard Statements Harmful if swallowed Harmful if inhaled Causes skin irritation Causes serious eye damage May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction Suspected of causing genetic defects May cause cancer May damage fertility or the unborn child Causes damage to organs through prolonged or repeated exposure	
	
This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.	
Appearance No information available	Physical state Solid
Odor No information available	

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
In case of inadequate ventilation wear respiratory protection
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water
Take off contaminated clothing and wash before reuse
If skin irritation or rash occurs: Get medical advice/attention

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

22.2594 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

Very toxic to aquatic life with long lasting effects
Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Nickel hydroxide	12054-48-7	10 - 30	*
Nickel	7440-02-0	10 - 30	*
Iron	7439-89-6	5 - 10	*
Cobalt	7440-48-4	3 - 7	*
PVC (Chloroethylene, polymer)	9002-86-2	3 - 7	*
Cobalt(II) oxide	1307-96-6	1 - 5	*
Manganese	7439-96-5	1 - 5	*
Potassium hydroxide	1310-58-3	1 - 5	*
Sodium hydroxide	1310-73-2	1 - 5	*
Copper	7440-50-8	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice	First aid is upon rupture of sealed battery.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Seek immediate medical attention/advice.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Remove to fresh air. May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get medical attention immediately if symptoms occur.
Ingestion	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. May produce an allergic reaction. If an allergic reaction occurs, stop use and seek medical help right away. Call a physician or poison control center immediately.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects	Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Itching. Rashes. Hives. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
--	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Product is or contains a sensitizer. May cause sensitization by skin contact. May cause sensitization by inhalation and skin contact.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Nickel hydroxide 12054-48-7	TWA: 0.2 mg/m ³ Ni inhalable fraction	TWA: 1 mg/m ³ Ni (vacated) TWA: 1 mg/m ³ Ni	IDLH: 10 mg/m ³ Ni TWA: 0.015 mg/m ³ except Nickel carbonyl Ni
Nickel 7440-02-0	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³	IDLH: 10 mg/m ³ TWA: 0.015 mg/m ³
Cobalt 7440-48-4	TWA: 0.02 mg/m ³	TWA: 0.1 mg/m ³ dust and fume (vacated) TWA: 0.05 mg/m ³ dust and fume	IDLH: 20 mg/m ³ dust and fume TWA: 0.05 mg/m ³ dust and fume
PVC (Chloroethylene, polymer)	TWA: 1 mg/m ³ respirable fraction	-	

9002-86-2			
Cobalt(II) oxide 1307-96-6	TWA: 0.02 mg/m ³ Co	-	
Manganese 7439-96-5	TWA: 0.02 mg/m ³ respirable fraction TWA: 0.1 mg/m ³ inhalable fraction TWA: 0.02 mg/m ³ Mn respirable fraction TWA: 0.1 mg/m ³ Mn inhalable fraction	(vacated) TWA: 1 mg/m ³ fume (vacated) STEL: 3 mg/m ³ fume (vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ fume Ceiling: 5 mg/m ³ Mn	IDLH: 500 mg/m ³ TWA: 1 mg/m ³ fume STEL: 3 mg/m ³
Potassium hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³ (vacated) Ceiling: 2 mg/m ³	IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Hexavalent Chrome may be formed during welding Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state

Solid

Appearance

No information available

Color

No information available

Odor

No information available

Odor Threshold

No information available

Property

Values

Remarks Method

pH

No data available

None known

Melting / freezing point

No data available

None known

Boiling point / boiling range

No data available

None known

Flash Point

No data available

None known

Evaporation Rate

No data available

None known



Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing properties	No data available	

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:.

Inhalation

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components). May cause allergy or

asthma symptoms or breathing difficulties if inhaled. May cause sensitization in susceptible persons.

Eye contact

Specific test data for the substance or mixture is not available. Causes serious eye damage. (based on components). Severely irritating to eyes. May cause irreversible damage to eyes.

Skin contact

Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Prolonged contact may cause redness and irritation. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful if swallowed. (based on components). May cause additional affects as listed under "Inhalation".

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Nickel hydroxide 12054-48-7	= 1515 mg/kg (Rat)	> 2 g/kg (Rat)	= 1200 mg/m ³ (Rat) 4 h
Nickel 7440-02-0	> 9000 mg/kg (Rat)	-	-
Iron 7439-89-6	= 984 mg/kg (Rat)	-	-
Cobalt 7440-48-4	= 6171 mg/kg (Rat)	-	> 10 mg/L (Rat) 1 h
Cobalt(II) oxide 1307-96-6	= 159 mg/kg (Rat) = 202 mg/kg (Rat)	-	-
Manganese 7439-96-5	= 9 g/kg (Rat)	-	-
Potassium hydroxide 1310-58-3	= 284 mg/kg (Rat)	-	-
Sodium hydroxide 1310-73-2	-	= 1350 mg/kg (Rabbit)	-

Information on toxicological effects**Symptoms**

Erythema (skin redness). May cause redness and tearing of the eyes. May cause blindness. Burning. Coughing and/ or wheezing. Itching. Rashes. Hives. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

May cause sensitization by skin contact. May cause sensitization by inhalation.

Mutagenic Effects

Contains a known or suspected mutagen.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Nickel hydroxide 12054-48-7	A1	Group 1	Known	X
Nickel 7440-02-0		Group 2B	Reasonably Anticipated	X
Cobalt 7440-48-4	A3	Group 2B	Reasonably Anticipated	X
PVC (Chloroethylene, polymer)		Group 3		

9002-86-2				
Cobalt(II) oxide 1307-96-6	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity Contains a known or suspected reproductive toxin.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity Prolonged exposure may cause chronic effects. Repeated contact may cause allergic reactions in very susceptible persons. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.

Target Organ Effects Respiratory system. Eyes. Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI). Reproductive System. Blood. Central Nervous System (CNS). Kidney. Lungs. Nasal cavities. Heart. Liver.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

1,771.00 mg/kg

ATEmix (dermal)

53,519.00 mg/kg

ATEmix (inhalation-gas)

12,306.00 ppm

ATEmix (inhalation-dust/mist)

4.10 mg/l

ATEmix (inhalation-vapor)

30.08 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Nickel 7440-02-0	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)		48h EC50: > 100 mg/L 48h EC50: = 1 mg/L
Iron 7439-89-6		96h LC50: = 13.6 mg/L (Morone saxatilis)		
Cobalt 7440-48-4		96h LC50: > 100 mg/L (Brachydanio rerio)		
Potassium hydroxide 1310-58-3		96h LC50: = 80 mg/L (Gambusia affinis)		
Sodium hydroxide 1310-73-2		96h LC50: = 45.4 mg/L (Oncorhynchus mykiss)		
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio)		48h EC50: = 0.03 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Log Pow
Potassium hydroxide 1310-58-3	0.65 0.83

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.
US EPA Waste Number	D007

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Nickel 7440-02-0	Toxic powder Ignitable powder
Cobalt 7440-48-4	Toxic powder Ignitable powder Toxic
Cobalt(II) oxide 1307-96-6	Toxic
Manganese 7439-96-5	Ignitable powder
Potassium hydroxide 1310-58-3	Toxic Corrosive
Sodium hydroxide 1310-73-2	Toxic Corrosive
Copper 7440-50-8	Toxic

14. TRANSPORT INFORMATION

DOT	NOT REGULATED
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
TDG	Not regulated
MEX	Not regulated
ICAO	Not regulated
IATA	Not regulated
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
IMDG/IMO	Not regulated
Hazard Class	N/A
Marine Pollutant	Product is a marine pollutant according to the criteria set by IMDG/IMO
RID	Not regulated
ADR	Not regulated
ADN	Not regulated



15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Nickel hydroxide - 12054-48-7	12054-48-7	10 - 30	0.1
Nickel - 7440-02-0	7440-02-0	10 - 30	0.1
Cobalt - 7440-48-4	7440-48-4	3 - 7	0.1
Cobalt(II) oxide - 1307-96-6	1307-96-6	1 - 5	0.1
Manganese - 7439-96-5	7439-96-5	1 - 5	1.0
Copper - 7440-50-8	7440-50-8	0.1 - 1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Nickel hydroxide 12054-48-7		X		X
Nickel 7440-02-0		X	X	
Potassium hydroxide 1310-58-3	1000 lb			X
Sodium hydroxide 1310-73-2	1000 lb			X
Copper 7440-50-8		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Nickel hydroxide 12054-48-7	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Potassium hydroxide 1310-58-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Sodium hydroxide	1000 lb		RQ 1000 lb final RQ



1310-73-2		RQ 454 kg final RQ
Copper	5000 lb	RQ 5000 lb final RQ
7440-50-8		RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Nickel hydroxide - 12054-48-7	Carcinogen
Nickel - 7440-02-0	Carcinogen
Cobalt - 7440-48-4	Carcinogen
Cobalt(II) oxide - 1307-96-6	Carcinogen
Antimony trioxide - 1309-64-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Nickel hydroxide 12054-48-7	X	X	X	X	X
Nickel 7440-02-0	X	X	X	X	X
Cerium 7440-45-1	X				
Cobalt 7440-48-4	X	X	X	X	X
PVC (Chloroethylene, polymer) 9002-86-2	X				
Cobalt(II) oxide 1307-96-6	X		X	X	X
Manganese 7439-96-5	X	X	X	X	X
Potassium hydroxide 1310-58-3	X	X	X	X	
Sodium hydroxide 1310-73-2	X	X	X	X	
Aluminum 7429-90-5	X	X	X	X	

International Regulations**Mexico****National occupational exposure limits**

Chemical name	Carcinogen Status	Exposure Limits
Nickel hydroxide		Mexico: TWA= 0.1 mg/m ³ Mexico: STEL= 0.3 mg/m ³
Nickel		Mexico: TWA 1 mg/m ³
Cobalt	A3	Mexico: TWA= 0.1 mg/m ³
Manganese		Mexico: TWA 0.2 mg/m ³ Mexico: TWA 1 mg/m ³ Mexico: STEL 3 mg/m ³
Sodium hydroxide		Mexico: Ceiling 2 mg/m ³
Copper		Mexico: TWA= 1 mg/m ³ Mexico: TWA= 0.2 mg/m ³ Mexico: STEL= 2 mg/m ³

A3 - Confirmed Animal Carcinogen

Mexico - Occupational Exposure Limits - Carcinogens

Canada**WHMIS Hazard Class**

Non-controlled



16. OTHER INFORMATION

NFPA	Health Hazards 1	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 0	Flammability 0	Physical Hazard 0	Personal Protection
				X

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Issuing Date	04-Aug-2016
Revision Date	02-Aug-2016
Revision Note	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet