



Prepared according to Global Harmonized System (GHS) standards

## SECTION 1

## CHEMICAL PRODUCT IDENTIFICATION

Toro, Inc  
8111 Lyndale Ave S  
Bloomington, MN 55420-1196  
Tel: 1-888-384-9939

**Product Trade Name:** **Toro Full Synthetic 10W30 Engine Oil**

**CAS Number:** Mixture  
**Synonyms/Other:** N/A  
**Recommended Use:** Engine Oil  
**Restrictions on Use:** Not Determined  
**Created Date:** 10/16/2018  
**Preparation/Revision Date:** 8/22/2019  
**Emergency Phone Number:** 1-800-424-9300 (CHEMTREC)  
**SDS CODE:** 14732

## SECTION 2

## HAZARD IDENTIFICATION

**Appearance:** Blue  
**Odor:** Mild Petroleum  
**Classification:** Skin corrosion / irritation category 3  
**Target Organs:** Skin  
**Pictogram(s):** None required.

**Signal Word:** WARNING  
**Hazard Statement:** H316 - Causes mild skin irritation  
**Other Hazards:** Not determined.  
**Prevention:** None required.  
**Response:** P332+P313 - If skin irritation occurs: Get medical advice/attention  
**Storage Procedures:** None required.  
**Disposal:** None required.  
**Other:** See section 11 for complete health hazard information.

## SECTION 3

## COMPOSITION OF INGREDIENTS

Component	CAS Number	Percentage (by weight)
Zinc alkyl dithiophosphate	113706-15-3	< 2%

The balance of components do not contribute to the overall classification of the fluid, according to the GHS Standard.

## SECTION 4

## FIRST AID MEASURES

**Eye Contact:** If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

**Skin Contact:** Avoid direct contact. Wear chemical protective clothing, if necessary. Wash skin with lukewarm, gently flowing water and mild soap until product is removed. Call a doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention.



**Inhalation:** Get medical advice or attention if you feel unwell or are concerned.  
**Ingestion:** If you feel unwell or concerned: Get medical advice/attention. Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.  
**Other:** No additional information

## SECTION 5

## FIRE FIGHTING MEASURES

**Flash Point:** 241°C by Cleveland Open Cup Tester.  
**Flammable limits:** Not determined.  
**Extinguishing media:** Use dry chemical, alcohol foam, all purpose AFFF or carbon dioxide to extinguish fire.  
**Special firefighting procedures:** DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).  
**Unusual fire & explosion hazards:** Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. High temperatures may create heavy flammable vapors that may settle along ground level and low spots to create an invisible fire hazard.  
**Byproducts of combustion:** Fires involving this product may release oxides of carbon, phosphorus, nitrogen and sulfur; reactive hydrocarbons and irritating vapors.  
**Autoignition temperature:** Not determined.  
**Explosion data:** Not determined. Care should always be exercised in dust/mist areas.  
**Other:** Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

## SECTION 6

## ACCIDENTAL RELEASE MEASURES

**Spill control procedures (land):** Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. Clean up residue with an appropriate solvent. If a large spill occurs notify appropriate authorities. In case of road spill or accident contact Chem-Trec (800-424-9300).  
**Spill control procedures (water):** Try to contain large spills with floating booms to prevent spill from spreading. Remove from surface by skimming or with suitable adsorbents. If a large spill occurs notify appropriate authorities (normally the National Response Center or Coast Guard at 800-424-8802).  
**Waste disposal method:** Do not empty into drains. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.  
**Other:** CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.



**SECTION 7 HANDLING AND STORAGE**

**Handling procedures:** Keep containers closed when not in use. Do not transfer to unmarked containers. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.  
 Handling temperatures should not exceed 60°C (140°F) to minimize danger of burns. Open containers carefully in a well ventilated area or use appropriate respiratory protection. Wash thoroughly after handling.

**Storage procedures:** Store containers away from heat, sparks, open flame, or oxidizing materials. Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition.

**Additional information:** No additional information.

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure limits/standards for materials that can be formed when handling this product:**

	<b>OSHA TWA</b>	<b>OSHA STEL</b>	<b>ACGIH TWA</b>
Contains highly refined petroleum oil	*5 mg/m <sup>3</sup> (PEL)	*10 mg/m <sup>3</sup>	*5 mg/m <sup>3</sup> (TLV)

\* Exposure limits not defined. Limits used are for, "oil mist".

TWA – Time Weighted Average is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.

STEL – Short Term Exposure Limit is the employee's 15-minute time weighted average exposure which shall not be exceeded at any time during a work day unless another time limit is specified.

All base oils, including additive carriers, contain <3.0% DMSO extractable material.

**Personal protection:** Applicable mainly to persons in repeated contact situations such as packaging of product, service/maintenance, and cleanup/spill control personnel.

**Respiratory protection:** None required if ventilation is adequate. Otherwise a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-mask form dust/mist air purifying respirator.

**Eye protection:** Eye protection is strongly recommended. Wear safety glasses with side shields or vented/splash proof goggles (ANSI Z87.1 or approved equivalent).

**Hand protection:** Impervious, chemically resistant gloves such as neoprene or nitrile rubber to avoid skin sensitization and absorption.

**Other protection:** Use of an apron and overboots of chemically impervious materials such as neoprene or nitrile rubber is recommended based on level of activity and exposure. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other materials which cannot be decontaminated.

**Local control measures:** Use adequate ventilation when working with material in an enclosed area. Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in areas where this material is used and stored.



**Other:** Consumption of food and drink should be avoided in work areas where product is present. Always wash hands and face with soap and water before eating, drinking or smoking.

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Blue  
**Odor:** Mild Petroleum  
**Odor threshold:** Not determined.  
**pH:** Not applicable.  
**Melting/Freezing point:** Not determined.  
**Initial boiling point:** Not determined.  
**Boiling range:** Not determined.  
**Flash point:** 241°C.  
**Evaporation rate:** Not determined.  
**Flammability:** Not determined.  
**Upper flammable limit:** Not determined.  
**Lower flammable limit:** Not determined.  
**Vapor pressure:** Not determined.  
**Vapor density:** Not determined.  
**Relative density:** 0.86  
**Solubility:** Negligible in water, miscible in most petroleum solvents.  
**Partition Coefficient:** Not determined.  
**Auto-ignition temperature:** Not determined.  
**Decomposition temperature:** Not determined.  
**Viscosity:** 64.9 cSt at 40°C.  
**Other:** Not applicable.

**SECTION 10 STABILITY AND REACTIVITY**

**Reactivity**  
**Chemical stability:** Material is chemically stable at room temperatures and pressure.  
**Hazardous polymerization:** Will not occur.  
**Conditions to avoid:** Avoid high temperatures and product contamination.  
**Incompatibility with other materials:** Avoid contact with acids and strong oxidizing materials.  
**Decomposition products:** Smoke, carbon monoxide, carbon dioxide, and other aldehydes of incomplete combustion. Oxides of carbon, nitrogen, and sulfur; reactive hydrocarbons and irritating  
**Other:** Not applicable.

**SECTION 11 TOXICOLOGICAL INFORMATION**

**Acute toxicity (LD50) \*See note at the bottom of the section**  
**Oral:** >5000 mg/kg  
**Dermal:** >5000 mg/kg  
**Inhalation:** >20.0 mg/l  
**Skin irritation:** Causes mild skin irritation  
**Eye irritation:** Non-irritant  
**Dermal sensitization:** Not expected to have a sensitizing effect.  
**Respiratory sensitization:** Not expected to have a sensitizing effect.  
**Aspiration Hazard:** Not applicable



**Chronic Toxicity**

**Mutagenicity:** Not suspected of causing genetic defects  
**Carcinogenicity:** Not suspected of causing cancer.  
**Reproductive toxicity:** Not expected to have adverse effects on reproduction.  
**STOT-single exposure:** Not expected to have adverse effects.  
**STOT-repeated exposure:** Not expected to have long term adverse effects.  
**Other:** \*All data in this section is based off calculations from Part 3 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

**SECTION 12 ECOLOGICAL INFORMATION**

**Environmental toxicity**

**Fish:** > 100 mg/l.  
**Invertebrates:** > 100 mg/l.  
**Aquatic plants:** > 100 mg/l.  
**Microorganism:** > 100 mg/l.  
**Persistence/Degradability:** This product is not expected to be readily biodegradable.  
**Bioaccumulation:** Not determined.  
**Mobility in soil:** Not determined.  
**Other:** All classifications are based on calculations in Part 4 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

**SECTION 13 DISPOSAL CONSIDERATIONS**

**Waste disposal:** This product unadulterated by other materials can be classified as a non-hazardous waste. Depending on use, used product may be regulated. Dispose of in a licensed facility. Do not discharge product in to sewer system. Dispose of containers by crushing or puncturing, so as to prevent unauthorized use of used containers. Waste management should be in full compliance with federal, state, and local laws.  
**Other:** The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

**SECTION 14 TRANSPORT INFORMATION**

**Land Transport (DOT):** Not regulated for land transport.  
**Proper Shipping Name:** Not applicable.  
**Land Transport (TDG):** Not regulated for land transport.  
**Proper Shipping Name:** Not applicable.  
**Sea Transport (IMDG):** Not regulated for sea transport.  
**Proper Shipping Name:** Not applicable.  
**Air Transport (IATA):** Not regulated for air transport.  
**Proper Shipping Name:** Not applicable.  
**Other:** Not applicable.



**SECTION 15 REGULATORY INFORMATION**

**Federal Regulation**

**Clean water act/oil:** Under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Control Act of 1990, this material is considered an oil. Any spill or discharges that produce a visible sheen or film on surface of water, or in waterways, ditches, or sewers leading to surface water must be reported. Contact the National Response Center at 800-424-8802.

**TSCA:** All components of this material are listed in the U.S. TSCA Inventory.

**Other TSCA:** Not applicable.

**SARA title III:** Section 302/304 extremely hazardous substances:

None.

Section 311, 312 hazard categorization:

Acute (immediate health effects):	YES
Chronic (delayed health effects):	NO
Fire (hazard):	NO
Reactivity (hazard):	NO
Pressure ( sudden release hazard):	NO

Section 313 toxic chemicals:

No components present are at or greater than the de minimis (minimum reportable) concentration requirements for reporting.

**CERCLA:** For stationary/moving sources – reportable quantity (due to): Not hazardous due to the petroleum exclusion.

**State Regulations**

**Right-to-know** Not determined.

**Other:** A release of this product, as supplied, is exempt from reporting under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA). However, releases may be reportable to the Nation Response Center under the Clean Water Act, 33 U.S.C. 1321(b)(3) and (5) - see head of Section 15. Failure to report may result in substantial civil and criminal penalties.

Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.

**SECTION 16 OTHER INFORMATION**

	<b>NFPA 704</b>	<b>NPCA-HMIS</b>	<b>KEY</b>
<b>HEALTH:</b>	1	1	0 = Minimal
<b>FIRE:</b>	1	1	1 = Slight
<b>REACTIVITY:</b>	0	0	2 = Moderate
<b>SPECIFIC HAZARD:</b>	None	N/A	3 = Serious
<b>PROTECTION INDEX:</b>	N/A	B	4 = Severe

Version: II

INFORMATION PROVIDED IN THIS SDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF THE AUTHORS' KNOWLEDGE. HOWEVER, THE AUTHOR'S MAKE NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. THE AUTHORS ASSUME NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions / Comments: None. 10/16/2018  
 Update to Section 3. 08/22/19

Internal use only: OB19-KJ

# SAFETY DATA SHEET

Issuing Date 16-Mar-2015

Revision Date 30-Jan-2014

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name Fuel Treatment

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Fuel additive

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name The Toro Company

Supplier Address 8111 Lyndale Avenue South  
Bloomington  
MN  
8515  
US

Supplier Phone Number Phone:952-887-8515  
Contact Phone951-785-3482

Supplier Email eden.allen@toro.com

### Emergency telephone number

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).


Germ cell mutagenicity	Category 1B
Aspiration toxicity	Category 1



Flammable liquids

Category 4

**GHS Label elements, including precautionary statements****Emergency Overview**

<b>Signal word</b>	<b>Danger</b>		
<b>Hazard Statements</b>			
May cause genetic defects			
May be fatal if swallowed and enters airways			
Combustible liquid			
			
<b>Appearance</b>	Liquid	<b>Physical state</b>	Liquid
		<b>Odor</b>	Gasoline oil

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

**Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

**Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**

0 % of the mixture consists of ingredient(s) of unknown toxicity

**Other information**



Causes mild skin irritation  
 Toxic to aquatic life  
 PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

#### **Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Chemical name</b>	<b>CAS No</b>	<b>Weight-%</b>	<b>Trade Secret</b>
Petroleum naphtha, light aromatic	64742-95-6	60 - 100	*
Petroleum distillates, hydrotreated light	64742-47-8	60 - 100	*
Xylene	1330-20-7	3 - 7	*
1,2,3-Trimethylbenzene	526-73-8	3 - 7	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### **4. FIRST AID MEASURES**

#### **First aid measures**

<b><u>General Advice</u></b>	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
<b><u>Eye contact</u></b>	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.
<b><u>Skin contact</u></b>	Wash with soap and water.
<b><u>Inhalation</u></b>	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Seek immediate medical attention/advice. Delayed pulmonary edema may occur.
<b><u>Ingestion</u></b>	Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
<b><u>Self-protection of the first aider</u></b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Remove all sources of ignition.

#### **Most important symptoms and effects, both acute and delayed**

<b><u>Most Important Symptoms and Effects</u></b>	Difficulty in breathing. Coughing and/ or wheezing. Dizziness.
---	--

#### **Indication of any immediate medical attention and special treatment needed**



**Notes to Physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

### **Unsuitable extinguishing media**

CAUTION: Use of water spray when fighting fire may be inefficient.

### **Specific hazards arising from the chemical**

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

**Uniform Fire Code** Combustible Liquid: III-A

### **Hazardous Combustion Products**

Carbon oxides.

### **Explosion Data**

**Sensitivity to Mechanical Impact** No.

**Sensitivity to Static Discharge** Yes.

### **Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### **Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

### **Environmental precautions**

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

### **Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal.

**Methods for cleaning up** Dam up. Take precautionary measures against static discharges. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.



## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Do not breathe dust/fume/gas/mist/vapors/spray.

### Conditions for safe storage, including any incompatibilities

**Storage** Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Keep out of the reach of children. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

**Incompatible Products** None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light 64742-47-8	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> (as oil mist)	TWA: 5 mg/m <sup>3</sup> (as oil mist)	
Xylene 1330-20-7	STEL = 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	
1,2,3-Trimethylbenzene 526-73-8	-	-	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

### Appropriate engineering controls

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** Wear protective gloves and protective clothing.

<b>Respiratory protection</b>	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
<b>Hygiene Measures</b>	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

<b>Physical state</b>	Liquid	<b>Odor</b>	Gasoline oil
<b>Appearance</b>	Liquid	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
<b>pH</b>	UNKNOWN	None known	
<b>Melting / freezing point</b>	No data available	None known	
<b>Boiling point / boiling range</b>	No data available	None known	
<b>Flash Point</b>	79 C / 174 F	None known	
<b>Evaporation Rate</b>	No data available	None known	
<b>Flammability (solid, gas)</b>	No data available	None known	
<b>Flammability Limit in Air</b>			
<b>Upper flammability limit</b>	No data available		
<b>Lower flammability limit</b>	No data available		
<b>Vapor pressure</b>	No data available	None known	
<b>Vapor density</b>	No data available	None known	
<b>Specific Gravity</b>	.8146	None known	
<b>Water Solubility</b>	Liquid	None known	
<b>Solubility in other solvents</b>	No data available	None known	
<b>Partition coefficient: n-octanol/water</b>	No data available	None known	
<b>Autoignition temperature</b>	No data available	None known	
<b>Decomposition temperature</b>	No data available	None known	
<b>Kinematic viscosity</b>	No data available	None known	
<b>Dynamic viscosity</b>	No data available	None known	
<b>Explosive properties</b>	No data available		
<b>Oxidizing properties</b>	No data available		

### Other Information

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	No data available
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available.

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Hazardous Polymerization

Hazardous polymerization does not occur.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

None known based on information supplied.

### Hazardous Decomposition Products

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

##### Inhalation

Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

##### Eye contact

Specific test data for the substance or mixture is not available. May cause irritation.

##### Skin contact

Repeated exposure may cause skin dryness or cracking.

##### Ingestion

Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum naphtha, light aromatic 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Xylene 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit ) > 1700 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h

### Information on toxicological effects

#### Symptoms

Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure



**Sensitization** No information available.

**Mutagenic Effects** There is no data for this product. Contains a known or suspected mutagen.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		

*IARC (International Agency for Research on Cancer)  
Group 3 - Not Classifiable as to Carcinogenicity in Humans*

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic Toxicity** Contains a known or suspected mutagen. Possible risk of irreversible effects. Aspiration may cause pulmonary edema and pneumonitis. May cause adverse effects on the bone marrow and blood-forming system.

**Target Organ Effects** May affect the genetic material in germ cells (sperm and eggs). Respiratory system. Blood. Central Nervous System (CNS). Eyes. Skin. Kidney. Liver.

**Aspiration Hazard** No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

- ATEmix (oral)**  
86,000.00 mg/kg
- ATEmix (dermal)**  
22,000.00 mg/kg (ATE)
- ATEmix (inhalation-gas)**  
90,000.00 ppm (4 hr)
- ATEmix (inhalation-dust/mist)**  
30.00 mg/l
- ATEmix (inhalation-vapor)**  
220.00 ATEmix



**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Toxic to aquatic organisms.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum naphtha, light aromatic 64742-95-6		96h LC50: = 9.22 mg/L (Oncorhynchus mykiss)		48h EC50: = 6.14 mg/L
Petroleum distillates, hydrotreated light 64742-47-8		96h LC50: = 2.2 mg/L (Lepomis macrochirus) 96h LC50: = 2.4 mg/L (Oncorhynchus mykiss) 96h LC50: = 45 mg/L (Pimephales promelas)		96h LC50: = 4720 mg/L
Xylene 1330-20-7		96h LC50: = 13.4 mg/L (Pimephales promelas) 96h LC50: = 19 mg/L (Lepomis macrochirus) 96h LC50: 13.1 - 16.5 mg/L (Lepomis macrochirus) 96h LC50: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) 96h LC50: 2.661 - 4.093 mg/L (Oncorhynchus mykiss) 96h LC50: = 780 mg/L (Cyprinus carpio) 96h LC50: > 780 mg/L (Cyprinus carpio) 96h LC50: 30.26 - 40.75 mg/L (Poecilia reticulata) 96h LC50: 23.53 - 29.97 mg/L (Pimephales promelas) 96h LC50: 7.711 - 9.591 mg/L (Lepomis macrochirus)	EC50 = 0.0084 mg/L 24 h	48h EC50: = 3.82 mg/L 48h LC50: = 0.6 mg/L

**Persistence and Degradability**

No information available.

**Bioaccumulation**

Chemical name	Log Pow
Xylene 1330-20-7	3.15

**Other adverse effects**

No information available.



**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal methods** This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

**Contaminated Packaging** Dispose of contents/containers in accordance with local regulations.

**California Hazardous Waste Codes** 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Xylene 1330-20-7	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**  
**Proper Shipping Name** NOT REGULATED  
**Hazard Class** NON REGULATED  
 N/A

**TDG** Not regulated

**MEX** Not regulated

**ICAO** Not regulated

**IATA**  
**Proper Shipping Name** Not regulated  
**Hazard Class** NON REGULATED  
 N/A

**IMDG/IMO**  
**Hazard Class** Not regulated  
 N/A

**RID** Not regulated

**ADR** Not regulated

**ADN** Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL** All components are listed either on the DSL or NDSL.





TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	3 - 7	1.0

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb			X

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Xylene 1330-20-7	100 lb		RQ= 100 lb final RQ RQ= 45.4 kg final RQ

### US State Regulations

#### California Proposition 65

This product does not contain any Proposition 65 chemicals.

#### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Xylene 1330-20-7	X	X	X	X	X
1,2,3-Trimethylbenzene 526-73-8	X	X			X

### International Regulations

#### Mexico

##### National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Xylene 1330-20-7 ( 3 - 7 )		Mexico: TWA= 100 ppm Mexico: TWA= 435 mg/m <sup>3</sup> Mexico: STEL= 150 ppm



<p>1,2,3-Trimethylbenzene 526-73-8 ( 3 - 7 )</p>		<p>Mexico: STEL= 655 mg/m<sup>3</sup> Mexico: TWA 25 ppm Mexico: TWA 125 mg/m<sup>3</sup> Mexico: STEL 35 ppm Mexico: STEL 170 mg/m<sup>3</sup></p>
--	--	---

Mexico - Occupational Exposure Limits - Carcinogens

**Canada**

**WHMIS Hazard Class**

Not determined

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b> 1	<b>Flammability</b> 2	<b>Instability</b> 0	<b>Physical and Chemical Hazards - Personal Protection</b> X
<b>HMIS</b>	<b>Health Hazards</b> * 2	<b>Flammability</b> 2	<b>Physical Hazard</b> 0	

**Chronic Hazard Star Legend** \* = Chronic Health Hazard

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 16-Mar-2015  
**Revision Date** 30-Jan-2014  
**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

