



MECHANICAL CONTROLLED **MINI**  
**WINDOW AIR CONDITIONER**



Eco-Friendly  
Refrigerant



2 Way  
Air Direction



Auto Restart



Chassis Type:  
Fixed



2 Cooling Speeds  
2 Fan-Only Speeds

## QUALITY PERFORMANCE

Save money and stay cool with the Impecca Preferred Mini Air Conditioning unit. Guide the air flow as you like with two-way air direction. Its 5,000/6,000 Cooling BTU/h, operating using eco-friendly refrigerant, will easily cool a room with up to 150/250 square feet.

## SPECS

Model		IWA05-KM	IWA06-KM
<b>Performance</b>	Cooling Capacity (BTU/hr)	5000	6000
	Application area (Sq. Feet)	100-150	250
	EER	11.1	11.1
	Air Flow (m3/h) (High/Low)	234/188	250/173
<b>Electrical Ratings</b>	Voltage	115	115
	Watts	446	536
	Amps	4.0	5
	Cord Length (Ft.)	6.2	6.5
	Plug Type	5-15P	5-15P
<b>Features</b>	Control Type	Mechanical	Mechanical
	Cool / Fan Speeds	2 / 2	2 / 2
	Air Direction	2 Way	2 Way
	Indoor noise level dB(A) (Low)	55.1/53/50.5	56.4/54.1/51.9
	Refrigerant type	R410A	R410A
	Chassis type	Fixed	Fixed
<b>Dimensions</b>	Unit Width	16.5	18.5
	Unit Depth	15.4	15.7
	Unit Height	12	13.4
	Carton Width	17.9	21.7
	Carton Depth	17.2	17.8
	Carton Height	14.6	14.4
	Window Opening Width Required (Inch)	23-36	23-36
	Window Opening Height Required (Inch)	13	14
<b>Weight</b>	Net / Gross (Lbs.)	39.6 / 45.1	43.6 / 50.6
<b>Loading Q'ty</b>	Pallet	36	24
	Container (40'HQ)	944	762



**INSTALLATION KIT INCLUDED!**  
 (tools not included)