

T7400 Series Fiberglass Twin Step Ladders



Werner T7400 Twin Step Ladders feature a duty rating of 375 pounds per side of the ladder. Designed for one or two-person jobs, the T7400 ladders have heavy gauge aluminum tops and feature heavy duty internal spreaders to resist damage around the worksite or in transit. The GLAS*MARK® Violater stripes on the rails make the ladder more visible and the EDGE® bracing system and external rail shields add to the long lasting durability of these ladders. Fiberglass rails are non-conductive for working near electricity.

Features

- 4 rivets attach top to each front rail
- Aluminum top
- Back-up plates to reinforce top connectors
- Designed for one or two person jobs
- Designed for one person jobs
- Designed for two person jobs
- Every rivet backed up by metal plate or washer to protect fiberglass
- Internal Spreaders
- Molded braces
- Rail Shields
- Shoulder bolt and nut on top hinge
- Slip-resistant foot pad
- Slip-resistant Traction-Tred steps
- Slip-resistant Traction-Tred steps all knee braced

Specifications

| Model No. | Size | Reach Height | Max. Standing Height | Load Capacity | Type | Approx. Width |
|-----------|-------|--------------|----------------------|---------------|----------------------|---------------|
| T7404 | 4 ft | 8 ft | 1 ft 11 in | 375 lbs | Type IAA Duty Rating | 21-1/2 in |
| T7405 | 5 ft | 9 ft | 2 ft 10 in | 375 lbs | Type IAA Duty Rating | 23-1/2 in |
| T7406 | 6 ft | 10 ft | 3 ft 10 in | 375 lbs | Type IAA Duty Rating | 25 in |
| T7408 | 8 ft | 12 ft | 5 ft 9 in | 375 lbs | Type IAA Duty Rating | 28-1/2 in |
| T7410 | 10 ft | 14 ft | 7 ft 8 in | 375 lbs | Type IAA Duty Rating | 32 in |
| T7412 | 12 ft | 16 ft | 9 ft 7 in | 375 lbs | Type IAA Duty Rating | 35-1/2 in |
| T7414 | 14 ft | 18 ft | 11 ft 6 in | 300 lbs | Type IA Duty Rating | 39 in |
| T7416 | 16 ft | 20 ft | 13 ft 5 in | 300 lbs | Type IA Duty Rating | 42-1/2 in |
| T7418 | 18 ft | 22 ft | 15 ft 4 in | 300 lbs | Type IA Duty Rating | 46 in |
| T7420 | 20 ft | 24 ft | 17 ft 3 in | 300 lbs | Type IA Duty Rating | 49-1/2 in |