Dry Coat:	Recoat:	<u>Coverage:</u>	<u>Clean Up:</u>
1 HOUR	4 HOURS	LIP TO 400 SO ET PER GAL	SOAP & WATER

Paint confidently with Rust-Oleum HOME Advanced Paint + Primer Interior Wall Paint. A ready-to-use formula in designer colors provides great results, the first time, every time. Our advanced paint and primer offers excellent hide & coverage, with superior washability, and a mold and mildew resistant coating.

Spanish Translation

Pinte con confianza con Rust-Oleum HOME Advanced Paint + Primer Interior Wall Paint. Una fórmula lista para usar en colores de diseñador que proporciona resultados excelentes, la primera vez, cada vez. Nuestra pintura e imprimador avanzada ofrece excelente cobertura, con lavabilidad superior y un revestimiento resistente al moho.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

Coverage/Where to Use: One gallon will cover up to 400 sq. ft., depending on surface texture, porosity, and application method. Dark colors may require multiple coats. Ideal for interior walls, trim, windows, and doors.

Surfaces - Drywall, masonry and wood. (Note, do not use on floors.)

Surface Preparation: Surface must be free of any dust, grease, oil, stains, rust or any other contaminants. Sand glossy surfaces before painting and wash walls if necessary. Fill in any cracks or holes to ensure a smooth surface. Drywall joint compound must dry for two days. New drywall and bare wood should be primed before painting. Allow new plaster to cure for 30 days before painting. We recommend the use of Zinsser Bulls Eye 1-2-3® Primer to protect new drywall, painting over contrasting colors, bare woods and metals or where paint adhesion could propose a problem.

* WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to HYPERLINK "http://www.epa.gov/lead" www.epa.gov/lead.

Application: Stir well before use. Inter mix cans of the same color and product to ensure color consistency. Apply using a high quality 3/8"-1/2" nap roller or a high quality brush. If using an airless sprayer, follow manufacturer's instructions for use, and use a .013"-.017" tip at 1800-2300 psi, adjusting as needed. Apply using even strokes, moving from dry to wet areas, keeping a wet edge. Two coats are required for new or uncoated surfaces. Some colors may require additional coats. Thinning is not recommended.

Drying: Based on $77^{\circ}F$ ($25^{\circ}C$) < 50% humidity, dries to the touch in one hour. May be recoated after four hours. Allow more time to dry at cooler temperatures or in high humidity.

Clean Up: Clean hands, tools, spills and splatters with soap and warm water.

Disposal: To dispose of empty containers and unused product, contact your local environmental regulatory agency.

Care: Do not place objects on painted surfaces until thoroughly dry. Freshly painted surfaces may be washed after 30 days. Clean with mild, non-oily soap and water.

Refer to Safety Data Sheet for additional health and safety information.

NO TINTING REQUIRED (Spanish: No se requiere el tintado.) PROTECT FROM FREEZING.

PRECAUTIONS: Do not take internally. Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. Close container after each use. Avoid contact with skin and eyes. Wash thoroughly after handling. First Aid: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of contact, immediately flush skin with soap and water and eyes with plenty of water. If swallowed, get medical attention immediately. KEEP OUT OF REACH OF CHILDREN. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800)481-4785.

VOC: <50g/L