PRESSURE BALANCE UNIT FOR KOHLER® INSTALLATION INSTRUCTIONS

1007102975

Tools Required:

Screwdriver
Pliers
Adjustable Wrench

Installation Instructions:

1. Turn off water supply to the shower faucet. Once the water supply is shut off, turn the faucet on to release water pressure, then turn the faucet off.
2. Remove the shower valve trim: Handle, Escutcheon and Sleeve.
3. Remove Collar and old Cap (Cartridge): Before removing, note the position of the tab or the word “UP’ on the on the Cap. Remove the Screws to remove the Collar (if present), and Cap (with Adapter, if present).
4. Remove old Pressure Balance Unit (Regulator): Using pliers, pull the old Unit from the valve body. Remove any debris from the inside of the valve body.
5. Install new Pressure Balance Unit (Regulator): insert Unit into the valve body.
6. Install new Cap (Cartridge): Position the Adapter (if present), and Cap/Cartridge with ”UP” oriented as noted. Secure the Collar (if present) with Screws, and secure the Cap with Screws.
7. Turn on water supply and check for leaks.
8. Reinstall the following components:
   Install Handle, by positioning the Handle on the Stem to check the proper orientation.
   Reinstall the shower valve trim: Sleeve, Escutcheon, and Handle.

