



PROFESSIONAL MARKING & STRIPING SPRAYS

DESCRIPTION AND USES – MARKING PAINT

An aerosol coating specifically packaged for use in an inverted position as a marking paint. Use for marking construction and excavation sites, underground utilities and for traffic safety. They can also be used with the #2393000 Marking Wand to make large jobs less tedious. They feature fast dry and adhesion to concrete, blacktop, gravel, soil and grass.

APPEARANCE

Flat to semi-gloss finish (dependent on surface porosity).

PRODUCTS

| SKU | Description |
|---------|------------------------|
| 2524838 | Caution Blue |
| 2544838 | High Visibility Yellow |
| 2545838 | Caution Yellow |
| 2558838 | Fluorescent Red-Orange |
| 2592838 | White |
| 207464 | Fluorescent Green |
| 255641 | Fluorescent Pink |
| 2554838 | Fluorescent Orange |
| 2564838 | Safety Red |
| 2596838 | Clear |

PACKAGING

15-ounce containers, 6 containers per carton

PRODUCT APPLICATION

SURFACE PREPARATION

Remove excessive loose debris from the surface before application of the coating.

APPLICATION

Apply when temperature is above 40°F (4°C) and humidity is below 85% to ensure proper drying. Protect surrounding surfaces from overspray. Overspray can carry a significant distance. Shake can vigorously for one minute after mixing ball is heard. Invert can and point at ground or floor. Hold can 4 to 10 inches above surface to be marked. Press in sideways to spray or use Rust-Oleum Marking Wand (#2393000) or Rust-Oleum Marking Pistol (#210188). Follow directions for proper use of this equipment. Keep can moving to prevent build-up. Clean valve by spraying upright for 2-3 seconds after each use. If valve clogs, carefully remove spray tip and clean in thinner. DO NOT insert any object into can valve opening.

DESCRIPTION AND USES - STRIPING PAINT

A lead-free aerosol striping paint designed for use in an inverted position. Features weather and abrasion resistance for durability. When used with the Rust-Oleum Striping Machine #2395000, these coatings are ideal for striping parking lots, aisles and athletic fields. They feature fast dry and adhesion to concrete, blacktop, gravel and grass.

APPEARANCE

Flat finish.

PRODUCTS

| SKU | Description |
|---------|-------------|
| 2526838 | Blue |
| 2548838 | Yellow |
| 211777 | Red |
| 2593838 | White |
| 2578838 | Black |

PACKAGING

18-ounce containers, 6 containers per carton

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt and contaminants by sweeping the concrete or blacktop before application of the coating. Grease, oil and chemical contaminants are best removed by washing the surface with a commercial detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry.

APPLICATION

Apply when temperature is above 32°F (0°C) and humidity is below 85% to ensure proper drying. Protect surrounding surfaces from overspray. Overspray can carry a significant distance.

The Inverted Striping sprays are designed for use with the Rust-Oleum Striping Machine item #2395000. Follow machine directions for proper use. The width of the stripe can be varied from 2 to 4 inches wide by adjusting the position of the can holder on the Striping Machine. For best results be sure the Striping Machine is in motion before squeezing the trigger and release the trigger before stopping.

The inverted striping aerosols can also be used with the #2388000 Striping Wand.



TECHNICAL DATA

PROFESSIONAL MARKING & STRIPING SPRAYS

PHYSICAL PROPERTIES

| | | MARKING | STRIPING |
|--|------------------|---|--|
| Resin Type | | Vinyl Toluene Modified Alkyd | Vinyl Toluene Modified Alkyd |
| Pigment Type | | Varies with color | Varies with color |
| Solvents | | Acetone, N-Butyl Acetate, Toluene, VM&P Naphtha, Xylene | Acetone, Mineral Spirits, Toluene, VM&P Naphtha, Xylene |
| MIR | | 1.1 Max | 1.1 Max |
| Fill Weight | | 15 oz. (426 g) | 18 oz. (510 g) |
| Practical Coverage at Recommended DFT (assumes 15% material loss) | | 300-350 linear feet (91-106 meters) at 1.5 inch wide (3.8 cm) (coverage is dependent on surface porosity) | 2 inch stripe: 400 feet 2 inch stripe: 300-400 feet (2593838) 4 inch stripe: 200 feet 4 inch stripe: 150-200 feet (2593838) (coverage is dependent on surface porosity) |
| Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity | Tack-free | <5 minutes | <10 minutes |
| | Recoat | — | Anytime |
| Shelf Life | | 5 years | |
| Flash Point | | -156°F (-104°C) | |
| Safety Information | | For additional information, see SDS | |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877-385-8155
www.rustoleum.com/industrial

Form: GDH-447
Rev.: 070816