

xterior

3 mL)

DAP® Painter's Putty '53'® is ideal for filling nail holes, dents & cracks in interior or exter wood surfaces. It may also be used to glaze wooden window sashes. TIPS: Do not apply if ten is below 40°F. Product must be painted to maintain durability for interior & exterior application Paintable w/oil & latex-based paints. Prime with an oil-based primer before painting w latex-based paints. NOTE: Prior to use, & particularly where product is used as a glazing, it important for user to read & understand the additional important information on suggested us surface preparation, product application, painting & other items found in the Technical Bulletin this product (available at dap.com or by calling 1-888-DAP-TIPS). APPLICATION: 1. Surfa must be clean & dry. 2. Roll amount of putty needed with hand into the shape of a point & pre firmly into place with finger. 3. Finish with clean putty knife. Avoid contact with surrounding ar Sanding of product is not recommended. Allow skin to form before painting (approx. 24-48 hour 4. When used for glazing, remove all old glazing, prime wood sash with oil-based primer before applying putty. Allow to skin over (approx. 7-14 days) & prime with an oil-based primer & paint match sash. CLEAN-UP & STORAGE: Clean tools immediately after use with mineral spirits. not use mineral spirit to clean skin. Dry material must be cut or scraped away. Be sure contain is tightly sealed for storage. Store in a cool dry place.

WARNING: CONTAINS CRYSTALLINE SILICA. Sanding of this product may result in the generation dust. Exposure to excessive amounts of dust may cause a buildup of material in eyes, ears, no mouth & respiratory system causing irritation or injury. If sanding, use of a NIOSH-approved distribution mask is recommended. Do not ingest. FIRST AID: INHALATION: Remove to fresh air. SKIN: Walkington water. EYE: Flood with large quantities of water for at least 15 minutes. INGESTIC Get medical attention immediately. DO NOT INDUCE VOMITING. For emergencies, call pois control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For SDS, contact your supplier or visit dap.com. KEEP OUT OF REACH OF CHILDREN.

Lancer and Reproductive Harm – www.P65warnings.ca.gov

© DAP Products Inc., Baltimore, MD 21224 Made in the USA with U.S. & globally sourced materials.