

# Natural Look Penetrating Sealer

FILAMP90 **eco** PLUS

 **SEALER**  
WATER BASED

**FILA**<sup>®</sup>  
surface care solutions

FOR ALL NATURAL STONE, POLISHED PORCELAIN AND GROUT



## WHAT IT'S FOR

- Natural look anti-stain sealing.
- The best environmentally friendly stain protection for porcelain tiles, natural stone, marble and granite with polished, brushed and honed finishes.
- Reduces absorption without affecting the material's natural look.
- Impregnates, protects, and makes cleaning easier.
- Ideal for grout joints, ceramic and crackle effect surfaces, resin-marble, and stone slabs.
- Suitable for treating decorated cement tiles and reconstructed stones.

## ADVANTAGES

- Solvent free, withstands residual humidity and can therefore be applied 24-48 hours after the initial cleaning.
- Non film-forming and non yellowing.
- It is ideally suited for protecting kitchen and bathroom countertops.
- Certified food-safe.
- The surface can be walked on after just 4 hours.
- Very low VOC emissions product: certified by GEV and marked EC1 PLUS \* and helps towards achieving credits for LEED \*\*.

○ **FAST SETUP: THE INSTALLATION IS READY AFTER ONLY 4 HOURS**

○ **IDEAL FOR KITCHEN COUNTERTOPS**

## HOW TO USE IT

The product should be applied to a clean, dry surface. **For matte finish natural stones and agglomerates, decorated concrete tiles, manufactured stones:** Apply FILAMP90 ECO PLUS with a paintbrush, or lambswool applicator pad, making sure to fully saturate the surface. Wipe off excess product after 10 minutes with a dry cloth, lambswool pad, or sponge. **For polished finish natural stones, agglomerates, porcelains, marble and granite:** Apply an even coat of FILAMP90 ECO PLUS, with a paintbrush, or lambswool applicator pad. Wipe off excess product after 10 minutes on honed finish stones. Wipe off after 4 hours on polished marbles, making sure to rub the product to help penetrate. **Warning:** Before using the product, we recommend doing a spot test to check for any changes in color. Use fans to circulate the air in the room during use to speed up the drying process. Do not apply this product outdoors if rain is in the forecast. It does not protect marble, travertine and limestone from acid stains. **Storage temperature:** 41° F to 86° F, (5° C to 30° C). Must be applied to material at temperatures between 50° F to 86° F, (10° C and 30° C).



### Coverage:

(1 QT - 0.95 L)

Polished porcelain tiles 305-405 sq ft (28-38 m<sup>2</sup>)

Polished Stones and agglomerates 205-305 sq ft (19-28 m<sup>2</sup>)

Natural finish stones 100-205 sq ft (9-19 m<sup>2</sup>)

*Coverage rates are indicative and per coat.*



### Packaging:

0.5 GAL (1.89 L) 4 plastic bottles per box

1 QT (946 ml) 5 plastic bottles per box

1 PT (473 ml) 8 plastic bottles per box

Fila Chemicals USA, Corp.  
Miami, FL 33172  
tel +1-305-513-0708  
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over

**200 INTERNATIONAL TOP BRANDS**

manufacturers of materials for floors and wall coverings

filasolutions.com