Issuing Date 16-Mar-2015 Revision Date 30-Jan-2014 Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Fuel Treatment

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Fuel additive

Uses advised against No information available

Details of the supplier of the safety data sheet

**Supplier Name** The Toro Company

Supplier Address 8111 Lyndale Avenue South

Bloomington

MN 8515 US

Supplier Phone Number Phone:952-887-8515

Contact Phone951-785-3482

Supplier Email eden.allen@toro.com

Emergency telephone number

### 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Germ cell mutagenicity	Category 1B
Aspiration toxicity	Category 1



Flammable liquids Category 4

#### GHS Label elements, including precautionary statements

**Emergency Overview** 

Signal word

**Danger** 

#### **Hazard Statements**

May cause genetic defects May be fatal if swallowed and enters airways Combustible liquid



Appearance Liquid

Physical state Liquid

Odor Gasoline oil

#### **Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Keep away from heat/sparks/open flames/hot surfaces. - No smoking

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

### **Unknown Toxicity**

0 % of the mixture consists of ingredient(s) of unknown toxicity

#### **Other information**



Causes mild skin irritation
Toxic to aquatic life
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

#### **Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical name	CAS No	Weight-%	Trade Secret
Petroleum naphtha, light aromatic	64742-95-6	60 - 100	*
Petroleum distillates, hydrotreated light	64742-47-8	60 - 100	*
Xylene	1330-20-7	3 - 7	*
1,2,3-Trimethylbenzene	526-73-8	3 - 7	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

#### First aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a

physician.

**Skin contact** Wash with soap and water.

**Inhalation** Aspiration into lungs can produce severe lung damage. If breathing has stopped, give

artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Seek immediate medical attention/advice. Delayed

pulmonary edema may occur.

**Ingestion** Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce

vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an

unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Remove all sources of ignition.

#### Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

**Effects** 

Indication of any immediate medical attention and special treatment needed



Page 3 / 12

Notes to Physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

#### **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

#### Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Uniform Fire Code Combustible Liquid: III-A

#### **Hazardous Combustion Products**

Carbon oxides.

**Explosion Data** 

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes. Ensure adequate ventilation. Use personal protective equipment

as required. Evacuate personnel to safe areas. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled

material.

Other Information Refer to protective measures listed in Sections 7 and 8.

**Environmental precautions** 

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so.

#### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled

material. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up Dam up. Take precautionary measures against static discharges. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.



### 7. HANDLING AND STORAGE

#### **Precautions for safe handling**

**Handling** Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

**Storage** Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place.

Protect from moisture. Keep out of the reach of children. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with

the particular national regulations. Store in accordance with local regulations.

**Incompatible Products**None known based on information supplied.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

#### **Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	
64742-47-8	STEL: 10 mg/m <sup>3</sup>	(as oil mist)	
	(as oil mist)		
Xylene	STEL = 150 ppm	TWA: 100 ppm	
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m <sup>3</sup>	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m <sup>3</sup>	
1,2,3-Trimethylbenzene	<del>-</del>	-	TWA: 25 ppm
526-73-8			TWA: 125 mg/m <sup>3</sup>

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992) See section 15 for national exposure control parameters

#### **Appropriate engineering controls**

Engineering Measures Showers

Eyewash stations Ventilation systems

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** Wear protective gloves and protective clothing.

Revision Date 30-Jan-2014 1141363 - Fuel Treatment

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or **Hygiene Measures** 

smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

None known

Regular cleaning of equipment, work area and clothing is recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### **Physical and Chemical Properties**

Physical state Liquid **Appearance** Liquid

Odor Gasoline oil Color No information available **Odor Threshold** No information available

Property **Values** Remarks Method

**UNKNOWN** Hq None known Melting / freezing point No data available None known Boiling point / boiling range No data available None known Flash Point 79 C / 174 F None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known

Flammability Limit in Air **Upper flammability limit** No data available Lower flammability limit No data available

Vapor pressure No data available Vapor density No data available **Specific Gravity** .8146

Water Solubility Liquid Solubility in other solvents No data available Partition coefficient: n-octanol/waterNo data available No data available **Autoignition temperature** No data available **Decomposition temperature** Kinematic viscosity No data available **Dynamic viscosity** No data available No data available

**Explosive properties Oxidizing properties** No data available

#### **Other Information**

**Softening Point** No data available No data available **VOC Content (%) Particle Size** No data available

**Particle Size Distribution** 

Page 6 / 12

### 10. STABILITY AND REACTIVITY

#### Reactivity

No data available.

#### **Chemical stability**

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### **Conditions to avoid**

Heat, flames and sparks.

### **Incompatible materials**

None known based on information supplied.

### **Hazardous Decomposition Products**

Carbon oxides.

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Product Information

**Inhalation** Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be

fatal. May cause irritation of respiratory tract.

**Eye contact** Specific test data for the substance or mixture is not available. May cause irritation.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Ingestion** Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema

and pneumonitis. May be fatal if swallowed and enters airways.

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Petroleum naphtha, light aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg ( Rabbit )	= 3400 ppm (Rat) 4 h	
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h	
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h	

### Information on toxicological effects

**Symptoms** Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like

symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure



**Sensitization** No information available.

Mutagenic Effects There is no data for this product. Contains a known or suspected mutagen.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene		Group 3		
1330-20-7		·		

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure**No information available.

**Chronic Toxicity**Contains a known or suspected mutagen. Possible risk of irreversible effects. Aspiration

may cause pulmonary edema and pneumonitis. May cause adverse effects on the bone

marrow and blood-forming system.

Target Organ Effects May affect the genetic material in germ cells (sperm and eggs). Respiratory system. Blood.

Central Nervous System (CNS). Eyes. Skin. Kidney. Liver.

**Aspiration Hazard** No information available.

#### Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
86,000.00 mg/kg
ATEmix (dermal)
22,000.00 mg/kg (ATE)
ATEmix (inhalation-gas)
90,000.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
30.00 mg/l
ATEmix (inhalation-vapor)
220.00 ATEmix

Revision Date 30-Jan-2014 1141363 - Fuel Treatment

## 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

Toxic to aquatic organisms.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum naphtha, light		96h LC50: = 9.22 mg/L		48h EC50: = 6.14 mg/L
aromatic		(Oncorhynchus mykiss)		
64742-95-6				
Petroleum distillates,		96h LC50: = 2.2 mg/L		96h LC50: = 4720 mg/L
hydrotreated light		(Lepomis macrochirus) 96h		
64742-47-8		LC50: = 2.4 mg/L		
		(Oncorhynchus mykiss) 96h		
		LC50: = 45 mg/L		
		(Pimephales promelas)		
Xylene		96h LC50: = 13.4 mg/L	EC50 = 0.0084 mg/L 24 h	48h EC50: = 3.82 mg/L 48h
1330-20-7		(Pimephales promelas) 96h	_	LC50: = 0.6 mg/L
		LC50: = 19 mg/L (Lepomis		
		macrochirus) 96h LC50:		
		13.1 - 16.5 mg/L (Lepomis		
		macrochirus) 96h LC50:		
		13.5 - 17.3 mg/L		
		(Oncorhynchus mykiss) 96h		
		LC50: 2.661 - 4.093 mg/L		
		(Oncorhynchus mykiss) 96h		
		LC50: = 780 mg/L (Cyprinus		
		carpio) 96h LC50: > 780		
		mg/L (Cyprinus carpio) 96h		
		LC50: 30.26 - 40.75 mg/L		
		(Poecilia reticulata) 96h		
		LC50: 23.53 - 29.97 mg/L		
		(Pimephales promelas) 96h		
		LC50: 7.711 - 9.591 mg/L		
		(Lepomis macrochirus)		

### **Persistence and Degradability**

No information available.

### **Bioaccumulation**

Chemical name	Log Pow
Xylene	3.15
1330-20-7	

Other adverse effects
No information available.

Page 9 / 12

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

**Contaminated Packaging** Dispose of contents/containers in accordance with local regulations.

#### California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Xylene	Toxic
1330-20-7	Ignitable

### 14. TRANSPORT INFORMATION

NOT REGULATED

Proper Shipping Name NON REGULATED

Hazard Class N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated
Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A

RID Not regulated

ADR Not regulated

ADN Not regulated

### 15. REGULATORY INFORMATION

### **International Inventories**

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	3 - 7	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb			Х

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Xylene	100 lb		RQ= 100 lb final RQ
1330-20-7			RQ= 45.4 kg final RQ

#### US State Regulations

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

#### **U.S. State Right-to-Know Regulations**

.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Xylene	X	X	X	X	X
1330-20-7					
1,2,3-Trimethylbenzene	Х	X			X
526-73-8					

### International Regulations

#### **Mexico**

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Xylene		Mexico: TWA= 100 ppm
1330-20-7 ( 3 - 7 )		Mexico: TWA= 435 mg/m <sup>3</sup>
		Mexico: STEL= 150 ppm



	Mexico: STEL= 655 mg/m <sup>3</sup>
1,2,3-Trimethylbenzene	Mexico: TWA 25 ppm
526-73-8 ( 3 - 7 )	Mexico: TWA 125 mg/m <sup>3</sup>
	Mexico: STEL 35 ppm
	Mexico: STEL 170 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

Canada

**WHMIS Hazard Class** 

Not determined

### **16. OTHER INFORMATION**

NFPA Health Hazards 1 Flammability 2 Instability 0 Physical and

Chemical Hazards - HMIS Health Hazards \* 2 Flammability 2 Physical Hazard 0 Personal Protection

Χ

Chronic Hazard Star Legend \* = Chronic Health Hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

**Issuing Date** 16-Mar-2015 **Revision Date** 30-Jan-2014

Revision Note No information available

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet** 

