


AIRGUARD®



Premium Underlayment

The **ONLY** underlayment that includes **MICROBAN®** antimicrobial protection.



MOISTURE PROTECTION

- Built-in vapor barrier for moisture protection
- Patented AirFlow Technology provides consistent air movement under the flooring to safely release vapor emissions through the perimeter of the room and away from flooring
- Provides a barrier between subfloor and finished floor
- 4" film overlap with adhesive strip seals seams



ANTIMICROBIAL PROTECTION

- MICROBAN® antimicrobial protection prevents the growth of stain and odor-causing bacteria, as well as mold and mildew growth
- Safeguards the health of your floors, and ultimately promotes a healthier indoor air quality



PREMIUM CUSHIONING

- Helps provide a comfortable walking surface
- Helps eliminate minor subfloor imperfections



SUPERIOR SOUND CONTROL

- Absorbs impact sounds for quiet footfalls
- Provides deep, rich sound
- Exceeds building code requirements



RADIANT HEAT

- Adds R-value to chilly floors to reduce cold transfer from subfloor to flooring.
- Suitable for use with radiant heat flooring

SUPERIOR MOISTURE & SOUND PROTECTION

ROBERTS® AirGuard® Premium Underlayment is a comprehensive protection system for use under laminate and engineered wood flooring. Compatible with most radiant heat systems, AirGuard features innovative AirFlow Technology, and is the only underlayment to include MICROBAN® antimicrobial protection to safeguard your floors against mold, mildew and odor-causing bacteria.

PRODUCT RATINGS*

IIC
68

STC
67

R-Value
0.432

Δ Delta
20

PROUDLY
MADE IN USA



* IIC measures sound such as moving furniture and walking, STC measures sound such as voices and television. Minimum IIC and STC sound rating requirement is 50 according to the International Building Code. R-Value is the rating used to measure resistance to heat flow. Δ Delta Rating is the only true measurement of sound reduction from a product (not a floor assembly) in the industry.

AIRGUARD®



Premium Underlayment

The **ONLY** underlayment that includes **MICROBAN®** antimicrobial protection.



PRODUCT RATINGS*

IIC
68

STC
67

R-Value
0.432

Δ Delta
20

SPECIFICATIONS (+/-10%):

Material Composition	Clear Film Bottom, Polyshim Center, Blue Moisture Barrier Top
Thickness	2 mm
Compression Set	ASTM D3574 - 6.3%
Compression Strength	ASTM D3574 - 4.7 PSI
Indentation	ASTM F1914 - 0.046" at 50lbs
Smoke Density	ASTM E662 - PASS
Flammability Test	ASTM D2859 (CPSC FF1-70) - PASS
Thermal Resistance (R-Value)	0.432
Water Vapor Permeance	ASTM E96 - 0.286 lbs/1000 ft ² /24 hrs
Antimicrobial Protection	Fortified with MICROBAN® Antimicrobial Protection
Installation Methods	Floating
Warranty	Limited Lifetime Warranty

AVAILABILITY (ROLL SIZES):

Item #	70-105	70-105-1
Roll Size	100 ft ² (9.3 m ²)	630 ft ² (58.5 m ²)
Roll Width	40" (1.02 m)	40" (1.02 m)
Roll Length	30' (9.14 m)	189' (57.61 m)

PROUDLY
MADE IN USA



AirGuard®, ROBERTS® and logos are registered trademarks of Roberts Consolidated Industries, Inc., a wholly owned subsidiary of Q.E.P. Co., Inc. MICROBAN® trademark is owned by the Microban International, Ltd. and is used with permission.

Applications:

Residential & commercial

Approved Substrates:


Cured concrete, interior plywood, & properly prepared OSB (skim coat may be required)

Approved for Use Under:

Laminate flooring & engineered wood flooring

Locations:

Below-grade, on-grade, & above-grade



- 1 Moisture penetrates bottom layer
- 2 Moisture blocked by top layer
- 3 Moisture released out the sides as vapor