

STEEL CORE

5 GALLON AIR TIRE BEAD SEATER

40100



⚠ WARNING

This product contains or, when used, produces a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.
(California Health & Safety Code § 25249.5, et seq.)

**Actual product may vary slightly*

Please carefully read and save these instructions before attempting to assemble, maintain, install, or operate this product. Observe all safety information to protect yourself and others. Failure to observe the instructions may result in property damage and/or personal injury. Please keep instructions for future reference.

For warranty purchases, please keep your dated proof of purchase. File or attach to the manual for safe keeping.

Applications:

Used in various vacuum tire

Advantages:

- To provide a short high-pressure blast of air inside the tire cavity. The sudden force of air pushes the tire bead onto the wheel rim creating an air tight seal. Once this air tight seal is established, the tire is inflated.
- Safety, ease-of-use, and ultimate quality

Features:

- Valve for faster and easier air release
- Durable, rubber coated nozzle tip to prevent damaging rims.
- Visible, easy to read air gauge to accurately monitor take volume.
- Quick-slip inlet/outlet valve designed to allow take inlet/outlet in a single quick motion.

Specifications:

Capacity	5 Gallon
Inlet Valve	1/4" NPT with Plug
Outlet Valve	1-1/2" NPT
Pressure Gauge	Range 0-200 PSI
Working Pressure	125 PSI
Safety Pressure	130 PSI to 150 PSI

Pressure Reference Chart

Brand	ATV	LAWN Tractor	Car	4 x 4	Truck		Tractor		Large Tractor
Tire Type	16-650-8 22-11-8 25-12-9 24-9-11	16-650-8 23-1050-12 26-12-12	13" Rims 14" Rims	15" Rims 16" Rims	11-22-5	18-22-5	up to 28"	over 28"	terra tires 48-31-20 66-43-25
Suggested Tank Pressure	40 psi 2.7 bar	40 - 50psi 2.7 - 3.4bar	50 - 60psi 3.4 - 4.1bar	60 - 80psi 4.1 - 5.4bar	100psi 6.8bar	120psi 8.2bar	100psi 6.8bar	120psi 8.2bar	120 psi 8.2 bar

Limited Manufacturer Warranty

FOT makes every effort to ensure that this product meets high quality and durability standards. FOT warrants to the original retail consumer a 1-year limited warranty from the date the product was purchased at retail and each product is free from defects in materials. Warranty does not apply to defects due directly or indirectly to misuse, abuse, negligence or accidents, repairs or alterations, or a lack of maintenance. FOT shall in no event be liable for death, injuries to persons or property, or for incidental, special or consequential damages arising from the use of our products. To receive service under warranty, the original manufacturer part must be returned for examination by an authorized service center. Shipping and handling charges may apply. If a defect is found, FOT will either repair or replace the product at its discretion.

DO NOT RETURN TO STORE

For Customer Service:

Email: customerservice@focus-ontools.com or Call 1-800-348-5004