

GE5070

SAFETY DATA SHEET

1. Identification

Product identifier: GE5070

Other means of identification

Synonyms: SILICONE SEALANT

Recommended use and restriction on use

Recommended use: Silicone Elastomer

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information : Momentive Amer Seal.
260 HUDSON RIVER RD, 12188-1910 , USA
Contact person : commercial.services@momentive.com

Telephone : General information
+1-800-295-2392

Emergency telephone number
Supplier : CHEMTREC
1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin sensitizer Category 1
Toxic to reproduction Category 1B

Unknown toxicity - Health

Acute toxicity, oral	0 %
Acute toxicity, dermal	0 %
Acute toxicity, inhalation, vapor	0 %
Acute toxicity, inhalation, dust or mist	0 %

Label Elements

Hazard Symbol:

GE5070



Signal Word: Danger

Hazard Statement: H317; May cause an allergic skin reaction.
H360; May damage fertility or the unborn child.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: None.

Substance(s) formed under the conditions of use: Generates methanol during cure.

3. Composition/information on ingredients

GE5070

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
SILANE, DICHLORODIMETHYL-, REAKTION PRODUCTS WITH SILICA, Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	5 - <10%	# This substance has workplace exposure limit(s).
Distillates, petroleum, hydrotreated middle	64742-46-7	5 - <10%	# This substance has workplace exposure limit(s).
Hexamethyldisilazane	999-97-3	1 - <5%	# This substance has workplace exposure limit(s).
(1) TITANIUM DIOXIDE	13463-67-7	1 - <5%	# This substance has workplace exposure limit(s).
DIBUTYL TIN BIS ACETYLACETONATE	22673-19-4	0.1 - <0.3%	# This substance has workplace exposure limit(s).
(1) Silica	7631-86-9	0.1 - <1%	# This substance has workplace exposure limit(s).
(1) Aluminum oxide	1344-28-1	0.1 - <1%	# This substance has workplace exposure limit(s).

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

(1) The respirable particle(s) listed above are inextricably bound within the polymer matrix, and therefore does not present an inhalation hazard during normal use of this product. Tooling or machining of the cured product (sanding, cutting, milling) may release hazardous, respirable substances.

4. First-aid measures

Ingestion: If swallowed, do NOT induce vomiting. Give a glass of water.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

Skin Contact: To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. If skin irritation occurs: Get medical advice/attention.

GE5070

Eye contact: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: This product reacts with moisture in the acid contents of the stomach to form methanol.

5. Fire-fighting measures

General Fire Hazards: No data available.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).

Unsuitable extinguishing media: water jet

Specific hazards arising from the chemical: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No specific fire or explosion hazard.

Special protective equipment for fire-fighters: Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Avoid contact with skin and eyes. Keep out of reach of children. Keep container tightly closed. Adequate ventilation should be provided so that exposure limits are not exceeded. Product releases methanol during application and curing.

GE5070

Methods and material for containment and cleaning up:

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. Handling and storage

Precautions for safe handling:

Sensitivity to static discharge is not expected. Methanol is formed during processing. Use only in well-ventilated areas. Do not eat, drink or smoke when using the product. Wash thoroughly after handling. See Section 8 of the SDS for Personal Protective Equipment.

Conditions for safe storage, including any incompatibilities:

Keep container tightly closed and dry.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Distillates, petroleum, hydrotreated middle - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
Distillates, petroleum, hydrotreated middle - Mist.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Distillates, petroleum, hydrotreated middle	TWA	5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	3,500 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Distillates, petroleum, hydrotreated middle - Mist.	AN ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
(1) TITANIUM DIOXIDE - Total dust.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	10 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
(1) TITANIUM DIOXIDE - Particulate.	ST ESL	50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA PEL	10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01

GE5070

			2015)
(1) TITANIUM DIOXIDE - Respirable fraction.	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) TITANIUM DIOXIDE - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
DIBUTYL TIN BIS ACETYLACETONATE - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
	REL	0.1 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	0.1 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
DIBUTYL TIN BIS ACETYLACETONATE - Particulate.	AN ESL	0.1 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	1 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
DIBUTYL TIN BIS ACETYLACETONATE - as Sn	TWA PEL	0.1 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	STEL	0.2 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
(1) Silica	REL	6 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	6 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	6 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
(1) Silica - Particulate.	ST ESL	27 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	2 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
(1) Silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
(1) Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
(1) Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
(1) Aluminum oxide -	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)

GE5070

Respirable fraction.			(1989)
(1) Aluminum oxide - Total dust.	TWA	10 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
(1) Aluminum oxide - Respirable fraction.	TWA	5 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
(1) Aluminum oxide - Total dust.	TWA	10 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
(1) Aluminum oxide - Particulate.	AN ESL	5 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	50 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
(1) Aluminum oxide - Respirable fraction.	TWA PEL	5 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
(1) Aluminum oxide - Total dust.	TWA PEL	10 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) Aluminum oxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	5 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) Aluminum oxide - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)

This product contains one or more substances with an occupational exposure limit. However, the respirable particle(s) of this/these substance(s) are inextricably bound within the polymer matrix. Therefore, we do not expect an exposure to this/these substance(s) during normal use of this product. Tooling or machining of the cured product (sanding, cutting, milling) may release hazardous, respirable substances.

Appropriate Engineering Controls

Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

General information:

Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

Eye/face protection:

Safety glasses with side shields

Skin Protection

Hand Protection:

Cloth gloves.

Other:

Wear suitable protective clothing and eye/face protection.

GE5070

Respiratory Protection: If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	solid
Color:	White
Odor:	Ammonia.
Odor threshold:	No data available.
pH:	Not applicable
Melting point/freezing point:	Not applicable
Initial boiling point and boiling range:	Not applicable
Flash Point:	> 93.3 °C (estimated)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Heat of combustion:	No data available.
Vapor pressure:	Not applicable
Vapor density:	No data available.
Density:	No data available.
Relative density:	1.02
Solubility(ies)	
Solubility in water:	Insoluble
Solubility (other):	Slightly in Toluene

GE5070

Partition coefficient (n-octanol/water) Log Pow:	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
SADT:	No data available.
Viscosity, dynamic:	No data available.
Viscosity, kinematic:	No data available.
VOC:	27 g/l ;

10. Stability and reactivity

Reactivity:	No dangerous reaction if used as recommended.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerisation does not occur.
Conditions to avoid:	None known.
Incompatible Materials:	None known.
Hazardous Decomposition Products:	Carbon dioxide Ammonia. Silicon dioxide. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

GE5070

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Hexamethyldisilazane LD 50 (Rat): 870 mg/kg

(1) TITANIUM DIOXIDE LD 50 (Rat): > 10,000 mg/kg

(1) Silica LD 50 (Rat): > 15,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

(1) TITANIUM DIOXIDE LD 50 (Rabbit): > 10,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

(1) TITANIUM DIOXIDE LC50 (Rat): > 6.8 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

(1) Silica (Rabbit): No skin irritation

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE No eye irritation

Respiratory or Skin Sensitization

Product: No data available.

GE5070

Specified substance(s):

(1) TITANIUM DIOXIDE negative

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified **US. National Toxicology Program (NTP) Report on Carcinogens:**
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects:

This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive. Contains dibutyltin compound(s) - May impair fertility. May cause harm to unborn child.

GE5070

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE LC0 (Leuciscus idus, 48 h): > 1,000 mg/l

(1) Silica LC0 (Brachydanio rerio, 96 h): 5,000 mg/l

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

(1) Silica LC0 (Brachydanio rerio, 4 d): 5,000 mg/l

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE 0 %

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

GE5070

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

SILANE,	No data available.
DICHLORODIMETHYL-, REAKTION PRODUCTS WITH SILICA, Silane, dichlorodimethyl-, reaction products with silica	
Distillates, petroleum, hydrotreated middle	No data available.
Hexamethyldisilazane	No data available.
(1) TITANIUM DIOXIDE	No data available.
DIBUTYL TIN BIS ACETYLACETONATE	No data available.
(1) Silica	No data available.
(1) Aluminum oxide	No data available.

Other adverse effects: No data available.

13. Disposal considerations

General information: The generation of waste should be avoided or minimized wherever possible. See Section 8 for information on appropriate personal protective equipment. Do not discharge into drains, water courses or onto the ground.

Disposal instructions: Disposal should be made in accordance with federal, state and local regulations.

Contaminated Packaging: Dispose of as unused product.

14. Transport information

DOT
 Not regulated.

IMDG
 Not regulated.

IATA
 Not regulated.

Special precautions for user: This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

GE5070

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Reproductive toxicity
Respiratory or Skin Sensitization

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
SILANE, DICHLORODIMETHYL-, REAKTION PRODUCTS WITH SILICA, Silane, dichlorodimethyl-, reaction products with silica	10000 lbs
Distillates, petroleum, hydrotreated middle	10000 lbs
Hexamethyldisilazane	10000 lbs
(1) TITANIUM DIOXIDE	10000 lbs
DIBUTYL TIN BIS ACETYLACETONATE	10000 lbs
(1) Silica	10000 lbs
(1) Aluminum oxide	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

GE5070



WARNING

Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

METHYLPOLYSILOXANE
SILANE, DICHLORODIMETHYL-, REAKTION PRODUCTS WITH
SILICA, Silane, dichlorodimethyl-, reaction products with silica
Distillates, petroleum, hydrotreated middle
SILOXANES AND SILICONES, DI-ME
Hexamethyldisilazane
(1) TITANIUM DIOXIDE
DIBUTYL TIN BIS ACETYLACETONATE
(1) Aluminum oxide

US. Massachusetts RTK - Substance List

Chemical Identity

Distillates, petroleum, hydrotreated middle
10,10'-OXYBISPHENOXARSINE

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Distillates, petroleum, hydrotreated middle
(1) TITANIUM DIOXIDE

US. Rhode Island RTK

Chemical Identity

Distillates, petroleum, hydrotreated middle

GE5070

Inventory Status:

Australia AICS:	n (Negative listing)	Remarks: None.
Canada DSL Inventory List:	y (positive listing)	Remarks: None.
EU EINECS List:	y (positive listing)	Remarks: None.
Japan (ENCS) List:	n (Negative listing)	Remarks: None.
China Inventory of Existing Chemical Substances:	y (positive listing)	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	n (Negative listing)	Remarks: None.
Canada NDSL Inventory:	n (Negative listing)	Remarks: None.
Philippines PICCS:	n (Negative listing)	Remarks: None.
US TSCA Inventory:	y (positive listing)	Remarks: All components are listed or exempted on TSCA
New Zealand Inventory of Chemicals:	n (Negative listing)	Remarks: None.
Taiwan. Taiwan inventory (CSNN):	y (positive listing)	Remarks: None.

16. Other information, including date of preparation or last revision

HMIS Hazard ID

Health	*	2
Flammability		1
Physical Hazards		1
PERSONAL PROTECTION		

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 08/24/2018
Revision Date: No data available.
Version #: 2.1
Further Information: No data available.

GE5070

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safehandling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.