



The FS200 stepladders have a duty rating of 225 pounds with braces on the top step and top horizontal. Featuring a high performance HolsterTop with a paint and tool holder, these stepladders have slip-resistant, TRACTION-TRED® steps and external PINCH-PROOF™ spreaders. The EDGE® molded brace and foot pad combination provides enhanced bracing strength and increased protection against damage. Fiberglass rails are non-conductive for working near electricity.


Features

- Back-up plates to reinforce top connectors
- Designed for one person jobs
- Every rivet backed up by metal plate or washer to protect fiberglass
- External Spreaders
- Molded braces
- Slip-resistant foot pad
- Slip-resistant Traction-Tred steps

Dimensions

Feature	Size
Top Dimension	5-3/8 in x 13 in
Front Rails Dimension	3-1/8 in
Front Flange Dimension	1-1/8 in
Rear Rails Dimension	1-3/4 in
Rear Flange Dimension	1-3/16 in
Steps Dimension	3 in

Specifications

Feature	Size / Details
Size	6 ft
Reach Height	10 ft
Max. Standing Height	3 ft 10 in
Description of Top Features	Paint tray slot, can hook, Lock In accessory sockets, 2 tool holes, putty knife slot, drill hole, pint, quart and gallon paint cans, parts tray
Edge Bracing	Lightweight
Load Capacity	225 lbs
Type	Type II Duty Rating
Performance Rating	
Material	Fiberglass
Approx. Width	22 in
Approx. Spread	41-7/8 in
With Pail Shelf	No
Spreader Material	Steel
Certifications	ANSI A14.5 (2007); OSHA
Approx. Cu. Ft. Per Unit	4.5
Approx. Shipping Wt. Lbs.	16