



USE AND CARE SPECIFICATIONS

DESCRIPTION: Ipe Oil[®] Hardwood Deck Finish, by DeckWise[®], is an oil based product that protects and conditions hardwoods such as Ipe, Cumaru, Tigerwood, Massaranduba and Mahogany while also maintaining an all-natural appearance. It has been produced with professional results in mind, providing exceptional penetration, water repellency and U.V. protection.

SHAKE, STIR & MIX WELL • Questions/Comments: info@DeckWise.com

VEHICLE TYPE

Solvent based, blend of natural oils and synthetic alkyds.
Low VOC formula MHV contains VOC exempt solvent.

COLORS

Available in Natural

VISCOSITY

15-18 Seconds Zahn #2 at 77F

VOC CONTENT

MHV-5xx < 250 g/L (as supplied)

SOLIDS BY VOLUME

MHV-5xx 49%

SOLIDS BY WEIGHT

MHV-5xx 48%

WEIGHT PER GALLON

MHV-5xx 8.2 Pounds

COVERAGE

Rough Wood: 150 to 250 square feet per gallon
Smooth Wood: 200 to 300 square feet per gallon

DRY TIME

Allow 24 hours in good drying conditions

APPLY WITH

Brush, lint-free rag, roller, airless spray

PACKAGING

1 U.S. gallon / 3.785 Liters

SURFACE PREPARATION

For best results, always clean new, gray or dirty hardwood before applying Ipe Oil[®]. Use DeckWise[®] Deck & Wood Cleaner Part 1 and for hardwood with tannic acid bleeding or rust stains, use Deck & Wood Brightener Part 2. Allow hardwood to completely dry for at least 24 to 48 hours. New hardwood should be aged at least 6-8 weeks and cleaned before applying product.

SPECIAL INSTRUCTIONS

Before applying, this product should be mixed thoroughly. Ensure that all settled material on bottom of can is evenly incorporated, and intermix multiple containers for an even blend.

Apply Ipe Oil[®] when surface temperatures are between 45F and 90F. If surface is hot to the touch, it is too hot to apply product. Do not apply product if precipitation is expected within 24-48 hours.



Brush, Roller & Rag Application: For the best results, utilize a high quality 3/8" nap roller, pad applicator or stain brush. To minimize lapping, maintain a wet edge lengthwise and do not break in the middle of boards. One coat is sufficient for most applications. Always apply oil onto the boards parallel to the grain of the wood. **NOTE: Product not absorbed into the wood within 30-45 minutes must be thoroughly removed.**

Spray Application: When spraying, back brush or roll to prevent sags and runs. Cover surrounding areas to protect from over spray. For airless spray, use .015" to .019" tip size for best results. **NOTE: Product not absorbed into the wood within 30-45 minutes must be thoroughly removed.**

Wipe Off Excess: Depending on temperature and direct sunlight verses shade, soak time may need adjusted. It is essential to wipe excess oil off completely and attention paid to pooling after application. Continue to wipe excess oil until no surface sheen or leeching is noticeable. Wood surface must NOT look wet and will have a matte finish.

Rev:11.01.2017



The Ipe Clip® Fastener Company, LLC

Phone: 941-896-9851 • Email: info@DeckWise.com

Web: www.DeckWise.com



Ipe Oil®
Hardwood Deck Finish

USE AND CARE SPECIFICATIONS

DESCRIPTION: Ipe Oil® Hardwood Deck Finish, by DeckWise®, is an oil based product that protects and conditions hardwoods such as Ipe, Cumaru, Tigerwood, Massaranduba and Mahogany while also maintaining an all-natural appearance. It has been produced with professional results in mind, providing exceptional penetration, water repellency and U.V. protection.

SHAKE, STIR & MIX WELL • Questions/Comments: info@DeckWise.com

MAINTENANCE

Clean and brighten hardwoods at least once a year with DeckWise® Deck & Wood Cleaner Part 1 and DeckWise® Deck & Wood Brightener Part 2 or use the DeckWise Deck Maintenance Kit with all the products and tools needed in one handy package. Apply Ipe Oil® for Hardwood Decks every one to two years in most applications for desired natural hardwood color.

CLEANUP

Cleanup & Disposal: Wash rollers, brushes, spray equipment and steel wool with mineral spirits. Be sure to let air dry out of direct sunlight before disposal. Lay rags flat to dry out of sunlight or soak application utensils and any other materials in water immediately after use. Always keep the oil container closed and sealed when not in use.

WARNING! Rags, steel wool, brushes, rollers and waste soaked with Ipe Oil® may spontaneously combust if improperly piled and discarded. Immediately after each use, place all waste in a water filled metal container and seal. Dispose of empty containers and waste filled containers in accordance with local, state and federal regulations.

The suggestions and technical data for use contained herein are accurate to the best of our knowledge. It is offered in good faith that the statements of this publication does not constitute any warranty, either implied or expressed, as to the performance of this product. As use and conditions our products are outside our control, we can only guarantee these products to adhere to our criteria of quality. Our liability, if any, will certainly be limited to only replacing defective product. All technical information stated is at all times subject to change without prior notice.

Rev:11.01.2017