HANGING LANTERN
Assembly Instructions

CAUTION

- Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.
- Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

TOOLS REQUIRED

Ladder

Safety glasses

Electrical tape

Phillips screwdriver

Flat blade screwdriver

Pliers


Wire strippers


Fixture


lamp chimney

lamp holder rings


Mounting Unit


Mounting Screws

Wire Nuts

*PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE

HANGING LANTERN
Assembly Instructions

STEP 1

Use the mounting screws to attach the mounting unit to the junction box



STEP2

Make the electrical connection from the junction box to the fixture. Connect the ground wire to the mounting unit using the preinstalled green ground screw. Then, connect the positive, negative and ground wires with the supplied wire nuts. Secure with electrical tape

Connect Clear, Brown, Gold or Black Parallel Wire without tracer (round & smooth) or Black Fixture Wire to:

Black or Red Supply Wire or Insulated Wire (other than green) with copper conductor.

Connect Clear, Brown, Gold or Black *Parallel Wire with tracer (square & ridged) or White Fixture Wire to:

White Supply Wire or Insulated Wire (other than green) with silver conductor





STEP3

Place the canopy over the mounting unit and secure the fixture with the cap nuts.



STEP 4

Install Glasses to the fixture by lampholder ring

Install bulb(Not Included)

E26 Type A 60W