

WHEN TO CHANGE YOUR CARTRIDGE OR PARTICULATE FILTER

WHEN TO CHANGE YOUR CARTRIDGE

- Use a change schedule to know when to replace cartridges
- Establish a change schedule by using a service life calculator ([3M.com/ServiceLife](https://www.3m.com/ServiceLife)) or using common change schedules based on substance-specific standards as defined by OSHA
- However, if at any time you detect a smell, taste or irritation from the contaminants, leave the contaminated area immediately, replace the cartridges and perform a seal check before entering hazardous area again



WHEN TO CHANGE YOUR PARTICULATE FILTER

If you experience any of the 3 Ds while using your reusable respirator, go to a non-contaminated area and change the filters:

3 Ds

- Dirty
- Damaged
- Difficult to breathe through

NIOSH-APPROVED P95 filters for at least 95% filtration efficiency against solids and liquid aerosols, as well as oil-based particulates



NIOSH-APPROVED P100 filters for at least 99.97% filtration efficiency against solids and liquid aerosols, as well as oils



*Always replace your filter immediately if you encounter one of the 3 Ds (see above) before the recommended service life is over.

WARNING: Workplace/Occupational Applications: Use under a regulated government (e.g. OSHA) respiratory protection program, including requirements such as fit testing and training for certain hazardous exposures. For correct use, consult supervisor and User Instructions, or call 3M in USA at 1-800-243-4630. In Canada, call 1-800-267-4414.



Consumer Health and Safety Division
3M Center, Building 222-5N-12
St. Paul, MN 55144-1000

© 3M 2021. All rights reserved. 3M is a trademark 3M.