



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 10/27/10

DAP® Waterproof Roof Sealant

- For Repairing Minor Roof Leaks
- Can Be Used For Wet or Dry Applications
- Durable and Flexible
- Weatherproof Seal
- Exterior Use Only

Packaging: 10.1 fl. oz. (300 mL) cartridge
Color: Black
UPC Number: 7079818268

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on "Ask the Expert"
Order Information: 800-327-3339
Fax Number: 410-534-2650

Product Description:

DAP® Waterproof Roof Sealant is a high performance, asphalt-based sealant that will not run or bubble. It is ideal for repairing minor roof leaks and preventing the penetration of air and moisture. It offers excellent adhesion and resists the damaging effects of ultra-violet light, temperature extremes and weathering that cause hardening, cracking, and crumbling of oil-based sealants. DAP® Waterproof Roof Sealant forms a long-lasting, waterproof seal that resists cracking, crumbling, and sagging. Can be used in both dry and wet applications (emergency roof repairs).

Suggested Uses:

Ideal for sealing:

- Corrugated Roofing
- Asphalt surfaces
- Chimneys
- Roof/Pipe Flashing
- Copings
- Gable Joints
- Shingles/Gutters
- Spotting shingle tabs
- Repairing minor roof leaks

Adheres to:

- Wood
- Masonry
- Fiberglass
- Metal
- Asphalt

Surface Preparation & Application:

1. Remove loose, damaged concrete or blacktop from surface. Crack surface must be free of grease, oil and other foreign matter. Sweep or blow surface with compressed air to remove all mud, dirt, dust and other loose debris.
2. For wet surfaces, wipe off excess water.
3. Cut nozzle at a 45° angle to desired bead size.
4. Puncture inner foil seal.
5. Load cartridge into caulking gun.
6. Fill cracks and gaps with sealant pushing sealant ahead of nozzle.
7. Clean up excess uncured sealant with mineral spirits. Do not use mineral spirits to clean skin. Excess cured sealant must be cut or scraped away.
8. Paintable after one hour of application. However, it is recommended to use only high quality oil or asphalt-based paint. One coat may show a slight discoloration. Two coats will provide a clean film.

For Best Results:

- *Apply in temperatures above 40°F.*
- *Do not use below waterline.*
- *Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8" x 3/8", use backer rod material.*
- *Store away from extreme heat or cold.*

Physical & Chemical Characteristics:

Vehicle:	Asphalt
Tack Free:	1 hour
Full Cure:	2 – 4 weeks depending on temperature, humidity and depth of fill
Service Temperature Range (cured sealant):	-40°F to 180°F
Application Temperature Range:	40°F to 120°F
Coverage:	56 linear feet at a 3/16" bead
Odor:	Asphaltic
Consistency:	Gun grade
Volatile:	Mineral Spirits
Pigment:	Inert Fillers
Flash Point:	163°F
Specific Gravity:	1.6 ± 0.05
Solids:	87 ± 2% by weight
Weight per Gallon:	13.6 ± 0.2
Shelf Life:	12 months
MSDS No.:	00010004001

Clean Up:

Clean up excess uncured sealant with mineral spirits. Do not use mineral spirits to clean skin. Excess dried sealant must be cut or scraped away.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at dap.com or by calling 1-888-DAP-TIPS.

Satisfaction Guaranteed:

DAP will provide replacement product or refund sales price if product fails to perform when used as directed. Call 1-888-DAP-TIPS, with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

