



AVAILABLE NOW

BLACK NON-SAG and SELF-LEVELING SEALANTS FOR ASPHALT, CONCRETE and ROOFING.

Both products outperform and outlast silicone and polyurethane technologies providing exceptional durability and excellent adhesion to a wide variety of substrates.

- Freeze/thaw-resistant
- Interior and exterior use
- Low odor and no isocyanates
- Bonds to dry and wet surfaces
- Weather- and UV-resistant, non-shrink
- Designed to outlast polyurethane and silicone



Scan QR code to watch
the products in use.
CTScement.com
800-929-3030

FLIP FOR
MORE INFO



AVAILABLE NOW



BLACK NON-SAG SEALANT & ADHESIVE

Multisurface Multipurpose
Hybrid Silane Polyether

Use on horizontal, vertical and overhead applications, including cracks and joints, roofing, windows, doors, siding and trim.

- Superior adhesion and sag-resistance
- Paintable and waterproof in 40 minutes
- Conforms to: ASTM C920, Type S, Grade NS, Class 50, uses NT, T2, M, G, A, and O



BLACK SELF-LEVELING SEALANT

Pro-Performance Joint & Crack Filler
Hybrid Silane Polyether

Use for horizontal sealant applications, including control joints, expansion joints, crack filling, roofing, and sealing around pools and fountains.

- Superior cohesive and adhesive strength
- Tack-free in 60 minutes
- Conforms to: ASTM C920, Type S, Grade P, Class 25, uses T2, M, and O



Scan QR code to watch
the products in use.
CTScement.com
800-929-3030

