

# KILZ® KLEAR™ INTERIOR/EXTERIOR WATER-BASE CLEAR PRIMER/SEALER



- KILZ KLEAR high performance sealer is a fast dry multi-surface transparent primer
- Particularly effective for 'same color painting'
- Bonds and seals porous and chalky surfaces with little change to current color
- Tough, flexible and breathable film to offer years of service
- May also be used to seal highly porous surfaces with a transparent flat finish
- Suitable for sealing torn drywall facing paper, dried wallcovering adhesive, 'hot' joint compounds, concrete and stucco with surface pH up to 12.5



Soap & Water  
Clean-Up



300 - 400 sq.ft. / gal.!



30 Min - Dry Time to Touch!<sup>1</sup>  
1 Hr - Dry Time to Recoat!<sup>1</sup>



Protect from  
Freezing

## WHERE TO USE

KILZ KLEAR® high performance sealer is a fast dry multi-surface clear primer developed to seal porous surfaces inside and outside your home. Particularly effective for 'same color painting', KILZ KLEAR Primer will bond and seal porous and chalky surfaces with little change to current color. KILZ KLEAR Primer is a tough, flexible and breathable film to offer years of service. KILZ KLEAR Primer may also be used to seal highly porous surfaces with a transparent flat finish. Suitable for sealing torn drywall facing paper, dried wallcovering adhesive, 'hot' joint compounds, concrete and stucco. Use on interior and exterior surfaces including drywall, plaster, wood, galvanized, aluminum, architectural plastics, masonry and brick. Not recommended for floors.

## SURFACE PREPARATION (The following steps are recommended for product performance.)

- All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew, loose peeling paint, rust and all other foreign substances.
- If washing is necessary, use a non-soapy detergent or a TSP substitute, rinse well and allow to dry.
- Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous\*.
- Glossy Surfaces: Use only over properly prepared glossy surfaces, scuff-sand to de-gloss and wipe clean before application\*.
- Mold or Mildew Covered Surfaces: Wash the area with a mildew remover, rinse with water and allow to dry before priming.

**\*WARNING** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## APPLICATION

- Stir thoroughly before and occasionally during use.
- Use product when the surface and air temperatures are between 50° - 90°F (10° - 32°C).
- Coverage: 300-400 sq. ft. (18.6 - 27.9 m<sup>2</sup>) per gallon, depending on the surface texture, porosity and the application method.
- Dry Time @ 77°F (25°C) / 50% RH: Touch 30 - 60 minutes, Recoat 1 hour.
- Do not thin or apply at a greater spread rate or build up a visual glaze on the surface. Product is formulated for use at package consistency only.
- Brush – High quality Nylon/Polyester
- Roller – High quality 3/8 - 1/2" nap on smooth surfaces or 1/2 - 3/4" nap on semi-rough or porous surfaces.
- Airless spray – .017 - .021 tip / 60 mesh filter
- Prime the entire surface to ensure a uniform appearance of the topcoat.
- If rain or threatening weather is expected within 8 hours, delay applications until dry conditions exist.

- Never apply to frozen or frost covered substrates.
- Note: Do not apply product to wet or water saturated substrates or when the relative humidity is above 90%. Not for use below grade or under water.
- Do not flood coat.
- Must be top coated within 7 days of application or the surface may need to be re-cleaned.

## CLEAN-UP & DISPOSAL

- Clean equipment and paint splatters with warm, soapy water.
- Do not dispose of this product down a drain. Please consider donating any unused product. For recycling or disposal information contact your local household refuse collection service.
- If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal information contact your local household refuse collection service.



**WARNING**

Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**USE ONLY WITH ADEQUATE VENTILATION**

**WARNING IRRITANT. HARMFUL IF SWALLOWED. CONTAINS ETHYLENE GLYCOL.** Avoid contact with eyes. May cause eye, nose and throat irritation. Avoid breathing of dust, vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness, or if air monitoring demonstrates vapor/ mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH / MSHA TC-23C or equivalent) during and after application. Follow respirator manufacturer's direction for respirator use. Close container after each use. Wash thoroughly after handling and before smoking and eating. **FIRST AID:** If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention.

**KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY**

**LIFETIME LIMITED WARRANTY:** Masterchem Industries LLC warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for so long as you reside in your home. If this product is found to be defective upon inspection by its representative, Masterchem Industries LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey:** The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. For warranty service, call: 1-866-774-6371, or email: [techservice@masterchem.com](mailto:techservice@masterchem.com). Masterchem Industries LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

<sup>1</sup> Depending on the surface texture, porosity and application method

<sup>!!</sup> at 77°F, 50% RH. Longer dry time required in cooler temperatures and in higher humidity



©2019 Masterchem Industries LLC  
1-866-774-6371 • [www.kilz.com](http://www.kilz.com)  
L2201 • REV. 06/19  
MAX VOC: <100 g/L (<0.83 Pounds/Gallon)