

**GE284 3TG-TUBE(0.198LBS-0.090KG)
SILICONE SEALANT**

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Waterford Plant
260 Hudson River Rd
Waterford NY 12188

Revised: 09/10/2007

Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Sealant
Formula: Mixture

HMIS

Flammability: 1 Reactivity: 0 Health: 1

NFPA

Flammability: 1 Reactivity: 0 Health: 1

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! Harmful by inhalation, in contact with skin and if swallowed. May cause skin, eye, and stomach irritation. May cause central nervous system depression. May cause adverse reproductive effects. Adverse reproductive effects reported in animals.

Form: Solid Color: Translucent Odor: Ammonia

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed. May cause stomach discomfort. May cause central nervous system effects. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Not an anticipated route of exposure.

SKIN

Skin irritation is possible after contact with the uncured product. Uncured product contact will irritate lips, gums and tongue. May cause mild skin irritation. May be absorbed through skin and produce effects as listed under "Ingestion".

INHALATION

Causes mild respiratory tract irritation. Applies in uncured state. May also cause other effects as listed under "Ingestion".

EYES

Eye irritation on contact with the uncured product. May cause mild eye irritation.

MEDICAL CONDITIONS AGGRAVATED

Pre-existing skin or respiratory diseases.

**GE284 3TG-TUBE(0.198LBS-0.090KG)
SILICONE SEALANT**

SUBCHRONIC (TARGET ORGAN)

Skin; Central nervous system

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Inhalation; Dermal; Eyes; Oral.

3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
Hexamethyldisilazane	999-97-3	1 - 5 %
Methyl trimethoxysilane	1185-55-3	1 - 5 %
DISTILLATES, PETROLEUM, HYDROTREATED	64742-47-8	5 - 10 %
<u>B. NON-HAZARDOUS</u>		
Treated Filler	68611-44-9	10 - 30 %
Polydimethylsiloxane	63148-62-9	10 - 30 %
Methoxypolydimethylsiloxane	68037-58-1	60 - 90 %

4. FIRST AID MEASURES

INGESTION

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. Get medical attention if irritation persists.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get

**GE284 3TG-TUBE(0.198LBS-0.090KG)
SILICONE SEALANT**

medical attention if irritation persists.

NOTE TO PHYSICIAN

None known.

5. FIRE-FIGHTING MEASURES

FLASH POINT: > 9,393 °C; 16939 °F
METHOD: estimated
IGNITION TEMPERATURE: Unknown
FLAMMABLE LIMITS IN AIR - LOWER (%): Not applicable
FLAMMABLE LIMITS IN AIR - UPPER (%): Not applicable

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Product releases methanol during application and curing. Use mechanical ventilation to stay below TLV of 25 ppm ammonia. Keep container tightly closed. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation. Store away from heat, sources of ignition, and incompatibles. Keep away from children.

**GE284 3TG-TUBE(0.198LBS-0.090KG)
SILICONE SEALANT**

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

Eyewash stations; Showers

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Cloth gloves.

EYE AND FACE PROTECTION

Safety glasses

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

Component	CAS RN	Source	Value
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	Not applicable
VAPOR PRESSURE (20 C) (MM HG):	Not applicable
VAPOR DENSITY (AIR=1):	No data available
FREEZING POINT:	Not applicable
MELTING POINT:	Not applicable
PHYSICAL STATE:	Solid
ODOR:	Ammonia
COLOR:	Translucent
EVAPORATION RATE (BUTYL ACETATE=1):	No data available
SPECIFIC GRAVITY (WATER=1):	ca. 1.05
DENSITY:	ca. 1,050 g/cm ³
ACID / ALKALINITY (MEQ/G):	Not applicable
pH:	Not applicable
VOLATILE ORGANIC CONTENT (VOL):	2.2 %(m)
SOLUBILITY IN WATER (20 C):	Insoluble

**GE284 3TG-TUBE(0.198LBS-0.090KG)
SILICONE SEALANT**

SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT): PARTIAL IN TOLUENE
VOC EXCL. H2O & EXEMPTS (G/L): 27

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Will not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Methanol; Carbon dioxide (CO₂); Formaldehyde; Carbon monoxide; Ammonia; Silicon dioxide.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: Unknown

ACUTE DERMAL

Remarks: Unknown

ACUTE INHALATION

Remarks: Unknown

OTHER

Contains dibutyltin compound(s) - May impair fertility. May cause harm to unborn child.

SENSITIZATION

No data available

SKIN IRRITATION

No data available

EYE IRRITATION

No data available

MUTAGENICITY

Unknown

**GE284 3TG-TUBE(0.198LBS-0.090KG)
SILICONE SEALANT**

OTHER EFFECTS OF OVEREXPOSURE

This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

No data available

CHEMICAL FATE

No data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

15. REGULATORY INFORMATION

Inventories

Canada DSL Inventory	y (Positive listing)
Korea Existing Chemicals Inventory (KECI)	y (Positive listing)
China Inventory of Existing Chemical Substances	y (Positive listing)
Australia Inventory of Chemical Substances (AICS)	y (Positive listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (Positive listing)
EU list of existing chemical substances	y (Positive listing)
Canada NDSL Inventory	n (Negative listing)
Japan Inventory of Existing &	n (Negative listing)

**GE284 3TG-TUBE(0.198LBS-0.090KG)
SILICONE SEALANT**

New Chemical Substances
(ENCS)

TSCA list

e (Special case)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

SARA (311,312) HAZARD CLASS

Acute Health Hazard; Chronic Health Hazard

SARA (313) CHEMICALS

58-36-6, 10, 10'-oxybisphenoxarsine

Canadian Regulatory Information

WHMIS HAZARD CLASS

D2A VERY TOXIC MATERIALS, D2B TOXIC MATERIALS

Other

SCHDLE B/HTSUS:

3214.10.00.10 Mastic based on rubber

ECCN:

EAR99

CALIFORNIA PROPOSITION 65

WARNING! This product contains a chemical known in the State of California to cause cancer.
108-88-3, Toluene.

16. OTHER INFORMATION

OTHER

C = ceiling limit NEGL = negligible EST = estimated NF = none found NA = not applicable
UNKN = unknown NE = none established REC = recommended ND = none determined
V = recommended by vendor SKN = skin TS = trade secret R = recommended
MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million
ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2)., These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.