





• **Dimensions**

Overall bottom projection - 183/8" Overall top projection -12" Height - 6" Available widths: 21", 24", 30", 36" & 42"

Hood Body

Stainless Steel: 24 gauge, grade 430 stainless steel. Painted: 23 gauge cold rolled commercial grade (CRCQ) steel, auto welded, coated with a baked enamel finish.

Motor

2 speed, single coil, thermally protected, permanently lubricated. Rated 120 volts, 60 hz. Complete with 200°C lead wires.

• Lighting

Single 60 watt cook light capacity (bulb not included).

Ducting Options

Horizontal ducting: $3^{1/4}$ "x10" (duct adapter and damper included). Vertical ducting: $3^{1/4}$ "x10" (duct adapter and damper included). Vertical ducting: 7" round (duct adapter and damper not included). Ductless: removable front vent (charcoal filter not included).

• Fan Blade


One piece polymeric, electronically balanced blade. $65\!/\!8^{\prime\prime}$ diameter with 5 paddles.

<u>Electrical connection</u>

Hood top - 7/8" knockout hole for use with 1/2" cable clamp Hood back - 7/8" knockout hole for use with 1/2" cable clamp



AV SERIES



<u>Filters</u>

UL rated, class 2 filter. Grease Filter: RF35 - 87/8"x10³/8" (included). Charcoal Filter: RF34 (not included). Combo Grease/Charcoal: RF55 (not included).

Available Finishes

White, Biscuit, Almond, Black & Stainless Steel.

EXPANDED PERFORMANCE										
	Static Pressure (inches of w.g.)						Sones	Fan Speed	Power	
Air Flow - CFM	0	0.05	0.1	0.15	0.2	0.25	@ .1 SP	RPM	Watts	Apms
Vertical Ducting High	246	232	218	203	181	147	7.5	2973	87.0	2.1
Horizontal Ducting High	225	210	180	175	155	120	7.0	3024	87.0	2.1

