

Model:

# 24" Back Bar Cooler:

SBB-24-48G

Glass Swing Door Back Bar Cooler with LED Lighting



## SBB-24-48G

- **CABINET CONSTRUCTION**  
Standard, cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish. Stainless exterior options available. Standard interior construction utilizes stainless steel walls, floor and ceiling.
- **REFRIGERATION**  
Refrigeration system uses R290 refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.
- **ELECTRICAL**  
Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet.
- **TEMPERATURE**  
Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)


### MODEL FEATURES:

- Standard LED light inside of the cabinet
- Easily accessible condenser coil for cleaning, and easy service access
- Tempered glass to avoid injury by broken glasses

### Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Cabinet Dimensions (inches / mm)			Capacity	HP	Voltage	Amps	NEMA Config.
		L	D	H					
SBB-24-48G	2	48 7/8 1240	24 3/8 620	35 5/8 905	11.8 cu.ft. 335L	1/3+	115V/60Hz 220V/50Hz	2.88	5-15P 

● Plug type varies by country.

● Height does not include 3" casters.



Intertek



Intertek

CONFORMS TO NSF/ANSI STD. 7

SABA

Add: 3390 Enterprise Avenue, Hayward, CA 94545-3228

Tel: (510) 293-0189 Fax: (510) 293-0199 E-mail: info@sabacorpusa.com Website: www.sabacorpusa.com

## SBB-24-48G Plan View

