

BEHR® WATER-BASED WOOD EFFECTS

No.B4600 Aged Gray
No.B4602 Charred Black
No.B4604 Rustic Brown



- Creates a faux aged look on all types of wood.
- Less odor than oil-based products.
- Easy application.
- Easy water clean up.



Prep Before Use



1 Coat Application



Spread Rate:
200 Sq. Ft. / Qt.



Clean-Up:
Soap & Water

READY TO USE. PROTECT FROM FREEZING.

WHERE TO USE: Properly prepared Interior bare wood surfaces. Not recommended for floors.

SURFACE PREPARATION* (Proper surface preparation is required)

- Remove any existing finishes with sandpaper or liquid stripper.
- Wood Effects works best on bare wood.
- Prepare bare wood by sanding in the direction of the grain with sandpaper.
- Remove any dust with a clean, dry rag.

PRODUCT PREPARATION AND COLOR TESTING

- Wood Effects color will vary with different types of wood.
- To verify the final look, test Wood Effects in an inconspicuous area first.

STAIN APPLICATION

- Stir material thoroughly before and occasionally during use. Do not shake.
- For best results, use at temperatures between 60°F (16°C) and 90°F (32°C).
- Apply with a synthetic bristle brush or foam brush.
- Allow Wood Effects to sit on the wood for 30 minutes to 1 hour for the final effect. Wiping away is not required.
- For a lighter effect, apply product and wipe away immediately or lightly sand the finish with fine grit sandpaper once it is dry. To darken, a second coat can be applied after 1 hour.

CLEAR FINISH APPLICATION

- A topcoat is necessary for the best protection.
- Wait 1 hour for Wood Effects to dry before applying clear topcoat.
- For best results, use BEHR® Water-Based Fast Drying Polyurethane as a protective top coat. Test in an inconspicuous area first.

DISPOSAL

- For disposal of empty containers and unused product contact your household refuse collection service.

LIMITED WARRANTY

Visit behr.com/warranty or call 1-800-854-0133 Ext. 2 for more information

***WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

⚠ WARNING Cancer and Reproductive Harm –
www.P65Warnings.ca.gov

WARNING! IRRITANT CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CONTAIN: CRYSTALLINE SILICA AND TITANIUM DIOXIDE. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN-DO NOT TAKE INTERNALLY.

PLEASE SEE PRODUCT LABEL FOR SPECIFIC WARNINGS. WARNINGS MAY VARY BETWEEN PRODUCTS AND OR COLORS.



©2021 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. (C.O.V.) <120 g/L • REV. 9/21