



Section 1 - Product and Company Identification

Material Name	- Gardner Drive Seal 10
Chemical Category	- Mixture
Product Code	- 7585-GA
Product Description	- Asphalt emulsion driveway sealer..
Product Use	- Filler and sealant for asphalt pavements.
Synonyms	- Low VOC Water Based Asphalt Coating
Manufacturer	- Gardner-Gibson 4161 E. 7th Avenue Tampa, FL 33605 United States
Telephone	
Technical	- 813-248-2101
<u>Emergency</u>	- 800-424-9300

Section 2 - Hazards Identification

GHS HAZARDS AND PRECAUTIONS

Signal Word: **WARNING!**

- **Causes Skin Irritation (Category 2)**
- **Causes Eye Irritation (Category 2B)**

Prevention Wash hand and exposed skin thoroughly after handling. Remove shoes and clothing that have been contaminated with material.

Response **If on skin:** Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.



Additional Product Information: Contains Petroleum Based Products. For Exterior Use Only. Use only with adequate ventilation. Keep product closed and properly stored when not in use. Avoid contact with skin. Use protective gloves, safety glasses, and protective clothing when using this product. Do not use in drinking water or food systems. Do not reuse empty container. Make sure container is sealed and secured in an upright position during transportation. Do not eat or drink while using this product and wash hand thoroughly after use.

Physical Form	- Liquid
Color	- Black
Odor	- Mild Hydrocarbon.
Flash Point	- 460°F(238°C)
OSHA(HCS2012) / GHS	- Skin Irritation- Category 2 – (Causes Skin Irritation), Serious Eye Damage, Eye Irritation - Category 2B (Causes eye irritation)
Route Of Entry	- Skin, Eye

Carcinogenic Effects			
	CAS	IARC	NTP
Quartz (This product encapsulated)	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen
Asphalt (High Temp Fumes) This product applied cold at ambient temperatures.	8052-42-4	Group 2B-Possible Carcinogen	Under Consideration

Other Information

- This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding. During spraying or sanding the product, wear suitable respiratory equipment to protect against inhalation of mist and dust.

See Section 12 for Ecological Information.

Section 3 - Composition/Information on Ingredients

Hazardous Components						
Chemical Name	CAS	%(wt)	UN;EINECS	LD50/LC50	Classifications According to Regulation/Directive	Other
Asphalt	8052-42-4	10% TO 20%	NA1999, 232-490-9	Ingestion/Oral-Rat LD50 · >5000 mg/kg Inhalation-Rat LC50 · >94.4 mg/m ³		
Quartz	14808-60-7	10% TO 20%	238-878-4			
Kaolin	1332-58-7	1% TO 5%				
Latex Polymer	9003-55-8	1% TO 5%				
Bentonite	1302-78-9	1% TO 5%	215-108-5			
Limestone	1317-65-3	10% TO 20%	215-609-9	Ingestion/Oral-Rat LD50 · >15400 mg/kg Skin-Rabbit LD50 · >3 g/kg		
Non-Hazardous Components						
Chemical Name	CAS	%(wt)	UN;EINECS	LD50/LC50	EU R & S Phrases	Other
Water	7732-18-5	45% TO 55%	231-791-2	Ingestion/Oral-Rat LD50 · >90 mL/kg	NDA	NDA

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

See Section 11 for Toxicological Information.

Section 4 - First Aid Measures

- Inhalation** - Remove to fresh air. Call a physician or poison control center. If not breathing, give artificial respiration.
- Skin** - Wash the contaminated area of body with soap and fresh water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Eye** - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. If eye irritation persists: Get medical advice/attention.
- Ingestion** - Call a physician or poison control center immediately. Do not give anything by mouth to an unconscious person. Do NOT induce vomiting.

See Section 2 for Potential Health Effects.

Section 5 - Fire Fighting Measures

- | | |
|---|---|
| Extinguishing Media | - SMALL FIRES: Dry chemical, CO ₂ , water spray or regular foam. |
| Unsuitable Extinguishing Media | - No data available |
| Firefighting Procedures | - Keep unauthorized personnel away. Stay upwind. Fire fighters should wear complete protective clothing including self-contained breathing apparatus. |
| Unusual Fire and Explosion Hazards | - Some of these materials may burn, but none ignite readily. May release irritating or toxic gases, fumes, or vapors. |
| Hazardous Combustion Products | - Carbon monoxide, carbon dioxide, hydrocarbons. |
| Protection of Firefighters | - Wear positive pressure self-contained breathing apparatus (SCBA). |
| Flash Point | - 460°F(238°C) |

Section 6 - Accidental Release Measures

- | | |
|--------------------------------------|---|
| Personal Precautions | - Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate enclosed areas |
| Emergency Procedures | - Stop leak if you can do it without risk. Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up |
| Environmental Precautions | - Avoid run off to waterways and sewers. Do NOT wash away into sewer. |
| Containment/Clean-up Measures | - Use appropriate Personal Protective Equipment (PPE) Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in suitable container. |
| Prohibited Materials | - Avoid contact with strong oxidizing agents and acids. |

Section 7 - Handling and Storage

- | | |
|---|--|
| Handling | - Keep containers tightly closed when not in use. Use only with adequate ventilation. |
| Storage | - Keep only in the original container/package in a cool well-ventilated place. Keep away from fire. Keep container closed when not in use. |
| Special Packaging Materials | - No data available |
| Incompatible Materials or Ignition Sources | - Avoid contact with strong oxidizing agents and acids. |

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment Pictograms



- | | |
|--|---|
| Respiratory | - When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding. |
| Eye/Face | - Wear ANSI approved safety glasses with side shields or safety goggles. |
| Hands | - Wear chemical protective gloves made of Nitrile or Neoprene. |
| Skin/Body | - Wear clothing that covers the skin to prevent skin exposure. |
| General Industrial Hygiene Considerations | - Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke during work. Wash hands before eating. |
| Engineering Measures/Controls | - Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. |

Exposure Limits/Guidelines

	Result	ACGIH	NIOSH	OSHA	United States - California
Limestone (1317-65-3)	TWAs	Not established	10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	Not established
Kaolin (1332-58-7)	TWAs	2 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	2 mg/m ³ PEL (respirable dust, containing no asbestos fibers, < 1% crystalline silica)
Quartz (14808-60-7)	TWAs	0.025 mg/m ³ TWA (respirable fraction)	0.05 mg/m ³ TWA (respirable dust)	Not established	0.3 mg/m ³ PEL (total dust); 0.1 mg/m ³ PEL (respirable dust)
Asphalt (8052-42-4)	TWAs	0.5 mg/m ³ TWA (as benzene soluble aerosol, fume, inhalable fraction)	Not established	Not established	5 mg/m ³ PEL (fume)

Exposure Control Notations

ACGIH

- Kaolin (1332-58-7):Carcinogens:A4 - Not Classifiable as a Human Carcinogen
- Asphalt (8052-42-4):Carcinogens:A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free)
- Quartz (14808-60-7):Carcinogens:A2 - Suspected Human Carcinogen

Key to abbreviations

- PEL = Permissible Exposure Level determined by the Occupational Safety and Health Administration (OSHA)
- TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Physical Form:	Liquid	Appearance/Description:	Thick black semi-liquid.
Color:	Black	Odor:	Mild Hydrocarbon.
Odor Threshold:	No data available	Boiling Point:	212°F
Heat of Decomposition:	Not relevant	pH:	9 to 10
Specific Gravity/Relative Density:	1.2 Water=1	Density:	= 10.3 lbs/gal
Vapor Pressure:	17 @ 77 F(25 C)	Vapor Density:	= 1 Air=1
Evaporation Rate:	1 Water = 1	VOC (Wt.):	No data available
VOC (Vol.):	<10 g/L	Volatiles (Wt.):	No data available
Volatiles (Vol.):	No data available	Flash Point:	460 F
Flash Point Test Type:	Not relevant	UEL:	Not relevant
LEL:	Not relevant	Heat of Combustion (ΔHc):	Not relevant

Section 10 - Stability and Reactivity

- | | |
|---|---|
| Stability | - Stable under normal temperatures and pressures. |
| Hazardous Polymerization | - Hazardous polymerization not indicated. |
| Conditions to Avoid | - Avoid contact with strong oxidizing agents and acids. |
| Incompatible Materials | - Strong oxidizers and acids. |
| Hazardous Decomposition Products | - Carbon monoxide, carbon dioxide and hydrocarbons. |

Section 11 - Toxicological Information

Component Name	Concentration	CAS	Data
Asphalt	10% TO 20%	8052-42-4	Acute Toxicity: ; orl-rat LD50:>5000 mg/kg; ihl-rat LC50:>94.4 mg/m3; ihl-hmn TDLo:10 mg/m3/5.5Y-I Tumorigen/Carcinogen: ; skn-mus TDLo:905 gm/kg/2Y-I
Quartz	10% TO 20%	14808-60-7	Acute Toxicity: ; orl-rat TDLo:120 gm/kg
Kaolin	1% TO 5%	1332-58-7	Acute Toxicity: ; orl-rat TDLo:370 gm/kg/37D-I
Bentonite	1% TO 5%	1302-78-9	Acute Toxicity: ; orl-rat TDLo:700 gm/kg/7D-I
Limestone	10% TO 20%	1333-86-4	Acute Toxicity: ; orl-rat LD50:>15400 mg/kg

Other Component Information

- IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz. ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz. NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz. Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist. Airborne exposure is not expected with this product. The materials are encapsulated and would only be release if the dry material was sanded. Exposure could increase if the product is sprayed.

Other Information

- This product contains petroleum asphalt. Petroleum asphalt is not listed as a carcinogen by OSHA or NTP. The National Institute of Occupational Safety and Health (NIOSH), has concluded that at higher temperatures roofing asphalt fumes are a potential occupational carcinogen. If this product is heated or comes in contact with heated material, avoid breathing fumes. This product may contain small amounts of polycyclic aromatic hydrocarbons (PAH's) which are recognized carcinogens in humans and experimental animals. Mouse skin painting studies of roofing asphalt vapor concentrate have shown evidence of tumor formation associated with localized skin irritation in recent studies. Inhalation studies of high airborne concentrations of asphalt/bitumen fumes in rats and mice produced bronchitis, pneumonitis, and lung changes such as fibrosis and cell damage.

Section 12 - Ecological Information

- Ecological Fate** - No data available.
- Persistence/Degradability** - No data available.
- Bioaccumulation Potential** - No data available.
- Mobility in Soil** - No data available.

Section 13 - Disposal Considerations

- Product** - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transportation Information

DOT - United States - Department of Transportation
Shipping Name: Not Restricted

TDG - Canada - Transport of Dangerous Goods
Shipping Name: Not Restricted

IMO/IMDG -International Maritime Transport
Shipping Name: Not Restricted

Section 15 - Regulatory Information

- SARA Hazard Classifications** - Acute, Chronic
- Risk & Safety Phrases** - California PROP 65: Asphalt and Asphalt Fumes may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm. .

State Right To Know

Component	CAS	MA	MN	NJ
Water	7732-18-5	No	No	No
Asphalt	8052-42-4	Yes	Yes	Yes
Quartz	14808-60-7	Yes	Yes	Yes
Kaolin	1332-58-7	Yes	Yes	Yes
Latex Polymer	9003-55-9	No	No	No
Bentonite	1302-78-9	No	No	No
Limestone	1317-65-3	Yes	Yes	Yes

Inventory

Component	CAS	EU EINECS	TSCA
Water	7732-18-5	Yes	Yes
Asphalt	8052-42-4	Yes	Yes
Quartz	14808-60-7	Yes	Yes
Kaolin	1332-58-7	Yes	Yes
Bentonite	1302-78-9	Yes	Yes
Limestone	1317-65-3	Yes	Yes

U.S. - California - Proposition 65 - Carcinogens List

- | | | | |
|-------------|------------|------------|--|
| • Kaolin | 1332-58-7 | 5% TO 12% | Not Listed |
| • Limestone | 1317-65-3 | 10% TO 20% | Not Listed |
| • Asphalt | 8052-42-4 | 20% TO 30% | Not Listed |
| • Quartz | 14808-60-7 | 15% TO 25% | carcinogen, initial date 10/1/88 (airborne particles of respirable size) |
| • Bentonite | 1302-78-9 | 1% TO 5% | Not Listed |
| • Water | 7732-18-5 | 35% TO 45% | Not Listed |

Section 16 - Other Information

- Last Revision Date** - 3-10-2020
- Prepared By** - GG Inc.
- Disclaimer/Statement of Liability** - This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. Gardner-Gibson does not accept liability for any loss or damage that may occur from the use of this information.