Safety Data Sheet

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of issue: 16/09/2019

Revision date: 16/09/2019

019 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Article
Trade name	: Li-MnO2 Button Cell(Lithium Metal Battery)
Other means of identification	: CR1220
	40mAh
	Voltage : 3.0V
	Battery Weight: 0.78g
1.2. Recommended use and restrict	ions on use
Main use category	: Power supply.
Restrictions on use	: No information available.
1.3. Supplier	
Supplier	: CHANGZHOU JINTAN CHAOCHUANG BATTERY CO., LTD
Address	: Xiyang Indusrial Zone, Xuebu Town, Jintan City, Jiangsu Province, China.
Phone	: +86-755-27597836
E-mail	: marvelous@chaochuang.com
	. marvelous@chaochdang.com
1.4. Emergency telephone number	
+86-13510093096	
SECTION 2: Hazard(s) identificat	ion
2.1. Classification of the substance	
GHS-US classification	
GHS-US classification The batteries are not hazardous when used	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of
GHS-US classification	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss.
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss.
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents,which could cause casualty loss. may expose:
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 22A
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 22A
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 22A
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 22A
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 22A
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 22A
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 2A precautionary statements :
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 2A precautionary statements : : : : : : : : : : : : : : : : : : :
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 2A precautionary statements : : : : : : : : : : : : : : : : : : :
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 2A precautionary statements : : : : : : : : : : : : :
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: ⁷ 2A precautionary statements : : : : : Warning : : Causes skin irritation. : : : Wash hands, forearms and face thoroughly after handling.
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 22A precautionary statements : : : : : : : : : : : : : : : : : : :
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 22A precautionary statements : : : Warning : Causes skin irritation. Causes serious eye irritation. : Wash hands, forearms and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water/
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 2A precautionary statements : $\overbrace{v}{2A}$: $\overbrace{v}{2A}$
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 2A precautionary statements : : : : : : : : : : : : : : : : : : :
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 2A precautionary statements : $\overbrace{v}{2A}$: $\overbrace{v}{2A}$
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 72A precautionary statements : $\overbrace{v2}$: Warning : Causes skin irritation. Causes serious eye irritation. : Wash hands, forearms and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water/ IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see supplemental first aid instruction on this label) If skin irritation occurs: Get medical advice/attention.
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: * 2A precautionary statements * * * * * * * * * * * * * * * * * * *
GHS-US classification The batteries are not hazardous when used rupture, fire, heat, leakage of internal compo In the case of rupture, the following hazards Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2.2. GHS Label elements, including GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of onents, which could cause casualty loss. may expose: 72A precautionary statements : $\overbrace{v2}$: Warning : Causes skin irritation. Causes serious eye irritation. : Wash hands, forearms and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water/ IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see supplemental first aid instruction on this label) If skin irritation occurs: Get medical advice/attention.

This product should not present a health hazard when used under reasonable conditions. If contact with the internal components of the battery may be irritating to skin, eyes and mucous membranes. Fire will produce irritating, corrosive and/or toxic gases

_

Safety Data Sheet This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

Substances 3.1.

Not applicable 32 Mixtures

3.2. Wixtures			
Name	Product identifier	%	
Stainless Steel	(CAS-No.) 12597-68-1	66.666	
Manganese oxide (MnO2)	(CAS-No.) 1313-13-9	19.615	
Propylene carbonate	(CAS-No.) 108-32-7	3.205	
Polypropylene	(CAS-No.) 9003-07-0	2.821	
Polytetrafluoroethylene	(CAS-No.) 9002-84-0	1.731	
Graphite	(CAS-No.) 7782-42-5	1.731	
Ethylene glycol dimethyl ether	(CAS-No.) 110-71-4	1.538	
Lithium	(CAS-No.) 7439-93-2	1.41	
Perchloric acid, lithium salt	(CAS-No.) 7791-03-9	1.282	

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: No hazards which require special first aid measures.
	If you feel unwell, seek medical advice (show directions for use or safety data sheet if possible).
First-aid measures after inhalation	: There will be no dangerous during normal use. But breathe in a large number of batteries, or heat released from the gas, it will stimulate the respiratory tract and eyes. Remove to fresh air immediately. Get medical treatment immediately
First-aid measures after skin contact	: There will be no dangerous during normal use. But contacting battery electrolyte, may cause severe irritation or burns.
First-aid measures after eye contact	: There will be no dangerous during normal use. But contacting battery electrolyte can burn the eyes.
	Flush the eyes with plenty of clean water for at least 15 minutes immediately, without rubbing. Get immediate medical treatment. If appropriate procedures are not taken, this may cause eye injury.
First-aid measures after ingestion	: Ingestion of internal chemical materials may cause mouth, throat and intestinal irritation and damage.
	Rinse mouth Get medical attention Never give anything by mouth to an unconscious person
4.2. Most important symptoms and effect	s (acute and delayed)
Symptoms/effects	: No information available.
4.3. Immediate medical attention and spe	cial treatment, if necessary
Treat symptomatically.	

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing	ing media	
Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Unsuitable extinguishing media	: No information available.	

Safety Data Sheet This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

5.2. Specific hazards arising from the chemical			
Fire hazard :	Battery can be overheated by an external source or by internal shorting and develop metal hydroxide mist.		
	Toxic vapor may release in case of fire.		
	Containers may explode when heated.		
	Fire fighting water runoff and dilution water may be toxic and corrosive and may cause adverse environmental impacts.		
	Since vapour, generated from burning batteries may make eyes, nose and throat irritates, be sure to extinguish the fire on the windward side. Wear the respiratory protection equipment in some cases.		
	Exposure to the ingredients contained within the battery pack could be harmful under some circumstances.		
Toxic vapor may release in case of fire. :	Thermal decomposition can lead to release of irritating and toxic gases and vapors		
5.3. Special protective equipment and pred	autions for fire-fighters		
Protection during firefighting :	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.		
Other information :	Evacuate personnel to a safe area. Ensure adequate ventilation, especially in confined areas. Eliminate every possible source of ignition. Move containers from fire area if it can be done without personal risk. Cool tanks/drums with water spray/remove them into safety. Stay upwind/keep distance from source.		
SECTION 6: Accidental release measu	res		

6.1.	Personal precautions, protective equipment and emergency procedures		
6.1.1.	For non-emergency personnel		
Emergen	cy procedures :	No open flames, no sparks, and no smoking. Avoid contact with skin, eyes and clothing. Do not breathe dust/fume/gas/mist/vapors/spray.	
6.1.2.	For emergency responders		
Protective	equipment :	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
Emergen	cy procedures :	Stop leak if safe to do so. Evacuate personnel to a safe area. Ensure adequate ventilation, especially in confined areas.	
6.2.	Environmental precautions		
Avoid rele	ease to the environment.		
6.3.	Methods and material for containment	and cleaning up	
For conta	inment :	Collect spillage. Move containers from fire area if it can be done without personal risk. Contain large spillage with sand or earth.	
Methods	for cleaning up :	Take up liquid spill into absorbent material. Clean up any spills as soon as possible, using an absorbent material to collect it. Notify authorities if product enters sewers or public waters.	
Other info	ormation :	Dispose of materials or solid residues at an authorized site.	
6.4.	Reference to other sections		
For furthe	er information refer to section 13.		
SECTIO	ON 7: Handling and storage		
7.1.	Precautions for safe handling		
Precautio	ns for safe handling :	When packing the batteries, do not allow battery terminals to contact each other, or contact with other metals.	
		Be sure to pack batteries by providing partitions in the packaging box, or in a separate plastic bag so that the single batteries are not mixed together.	
		Use strong material for packaging boxes so that they will not be damaged by vibration, impact, dropping and stacking during their transportation.	
		Do not short-circuit, recharge, deform, throw into fire or disassemble.	
		Do not mix different type of batteries.	
		Do not solder directly onto batteries.	
		Insert the battery correctly in electrical equipment.	
Hygiene r	neasures :	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	

Safety Data Sheet

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

7.2.	Conditions for safe storage, including	any incompatibilities
Storage conditions		: Store in a cool and dry area, but prevent condensation on cell or battery terminals.
		High temperature may damage the performance of the battery.
		Protect from physical damage and short circuits.
		To avoid risk of fire or explosion, keep sparks and other sources of ignition away from the battery.
		Do not allow metal objects to simultaneously contact both positive and negative terminal of batteries.
		Do not stack battery directly on another battery.
		Do not store batteries on electrically conductive surfaces.
		Keep containers tightly closed in a dry, cool and well-ventilated place
		Keep locked up and out of reach of children
		Keep away from food, drink and animal feeding stuffs
		Store in accordance with local regulations

SECTION 8: Exposure controls/personal protection						
8.1. Control parameters						
Polypropylene (9003-07-0)						
Not applicable						
Manganese oxide (MnO2) (1313-13-9)						
Not applicable						
Lithium (7439-93-2)						
Not applicable						
Perchloric acid, lith	ium salt (7791-03-9)					
Not applicable						
Polytetrafluoroethy	lene (9002-84-0)					
Not applicable						
Graphite (7782-42-5	1					
ACGIH	GIH ACGIH TWA (mg/m ³) 2 mg/m ³ (all forms except graphite fibers-respi particulate matter)					
OSHA	OSHA PEL (TWA) (mg/m ³) 15 mg/m ³ (synthetic-total dust) 5 mg/m ³ (synthetic-respirable fraction)					
IDLH US IDLH (mg/m³) 1250 mg/m³						
NIOSH	NIOSH NIOSH REL (TWA) (mg/m³) 2.5 mg/m³ (natural-respirable dust)					
Propylene carbonate (108-32-7)						
Not applicable						
Ethylene glycol dimethyl ether (110-71-4)						
Not applicable						

8.2.	Appropriate engineering controls		
Appropria	ate engineering controls		Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Remove all sources of ignition.
Environm	ental exposure controls	:	Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Under normal condition of use and handling no special protection is required for sealed battery. In the event of battery case breakage, should be wear appropriate safety gloves

Eye protection:

Under normal condition of use and handling no special protection is required for sealed battery. Use appropriate safety glasses when there is the risk of splash

Safety Data Sheet

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

Skin and body protection:

Under normal condition of use and handling no special protection is required for sealed battery. It is recommended to wear appropriate protective clothing when the battery case is broken.

Respiratory protection:

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	chemical properties
Physical state	: Solid
Color	: Metallic color.
Odor	: Odorless.
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not flammable
Vapor pressure	: Not applicable
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: Not applicable
Explosion limits	: Not applicable
Explosive properties	: Not an explosive
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Avoid contact with incompatible materials

10.5. Incompatible materials

Oxidizing agent. Strong acid. Strong base.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information			
11.1. Information on toxicological effects			
Acute toxicity	: Not classified		

Safety Data Sheet

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

Manganese oxide (MnO2) (1313-13-9)		
LD50 oral rat	9000 mg/kg	
Propylene carbonate (108-32-7)		
LD50 oral rat	29000 mg/kg	
LD50 dermal rabbit	> 3000 mg/kg	
Ethylene glycol dimethyl ether (110-71-4		
LD50 oral rat	> 4000 mg/kg	
LD50 dermal rabbit	1000 - 2000 mg/kg	
LC50 inhalation rat (mg/l)	20 - 63 mg/l (Exposure time: 6 h)	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitisation	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Polypropylene (9003-07-0)		
IARC group	3 - Not classifiable	
Polytetrafluoroethylene (9002-84-0)		
IARC group	3 - Not classifiable	
Reproductive toxicity	: Not classified	
STOT-single exposure	: Not classified	
STOT-repeated exposure	: Not classified	
Aspiration hazard	: Not classified	
Symptoms/effects after skin contact	: Irritation.	
Symptoms/effects after eye contact	: Eye irritation.	

SECTION 12: Ecological informat	ion
12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Propylene carbonate (108-32-7)		
LC50 fish 1	> 1000 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])	
EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Manganese oxide (MnO2) (1313-13	9)	
BCF fish 1	(no bioaccumulation expected)	
Log Pow	< 0 (at 20 °C)	
Propylene carbonate (108-32-7)		
Log Pow	0.48 (at 25 °C)	

Safety Data Sheet This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal consideratior	IS
13.1. Disposal methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
SECTION 14: Transport information	
Department of Transportation (DOT)	
In accordance with DOT	
Not regulated	
Transportation of Dangerous Goods	
Not regulated	
Transport by sea	
Not regulated	
Air transport	
Not regulated	
SECTION 15: Regulatory information	1
15.1. US Federal regulations	
Polypropylene (9003-07-0)	
Listed on the United States TSCA (Toxic Subst	ances Control Act) inventory
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting

EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Manganese oxide (MnO2) (1313-13-9)	
Listed on the United States TSCA (Toxic Substan	ces Control Act) inventory
Lithium (7439-93-2)	
Listed on the United States TSCA (Toxic Substan	ces Control Act) inventory
Perchloric acid, lithium salt (7791-03-9)	
Listed on the United States TSCA (Toxic Substan	ces Control Act) inventory
Polytetrafluoroethylene (9002-84-0)	
Listed on the United States TSCA (Toxic Substan	ces Control Act) inventory
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Graphite (7782-42-5)	
Listed on the United States TSCA (Toxic Substan	ces Control Act) inventory
Propylene carbonate (108-32-7)	
Listed on the United States TSCA (Toxic Substan	ces Control Act) inventory

Safety Data Sheet

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

Ethylene glycol dimethyl ether (110-71-4)	
Listed on the United States TSCA (Toxic Substar	nces Control Act) inventory
EPA TSCA Regulatory Flag	S - S - indicates a substance that is identified in a final Significant New Use Rule.

15.2. International regulations	
CANADA	
Polypropylene (9003-07-0)	
Listed on the Canadian DSL (Domestic Substances List)	
Manganese oxide (MnO2) (1313-13-9)	
Listed on the Canadian DSL (Domestic Substances List)	
Lithium (7439-93-2)	
Listed on the Canadian DSL (Domestic Substances List)	
Perchloric acid, lithium salt (7791-03-9)	
Listed on the Canadian DSL (Domestic Substances List)	
Polytetrafluoroethylene (9002-84-0)	
Listed on the Canadian DSL (Domestic Substances List)	
Graphite (7782-42-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Propylene carbonate (108-32-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Ethylene glycol dimethyl ether (110-71-4)	
Ethylene glycol dimethyl ether (110-71-4) Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations	
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations	
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations No additional information available	ostances)
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations No additional information available Manganese oxide (MnO2) (1313-13-9)	ostances)
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations No additional information available Manganese oxide (MnO2) (1313-13-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub	
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations No additional information available Manganese oxide (MnO2) (1313-13-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Lithium (7439-93-2)	
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations No additional information available Manganese oxide (MnO2) (1313-13-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Lithium (7439-93-2) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub	ostances)
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations No additional information available Manganese oxide (MnO2) (1313-13-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Lithium (7439-93-2) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Perchloric acid, lithium salt (7791-03-9)	ostances)
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations No additional information available Manganese oxide (MnO2) (1313-13-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Lithium (7439-93-2) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Perchloric acid, lithium salt (7791-03-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Perchloric acid, lithium salt (7791-03-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub	ostances)
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations No additional information available Manganese oxide (MnO2) (1313-13-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Lithium (7439-93-2) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Perchloric acid, lithium salt (7791-03-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Graphite (7782-42-5)	ostances)
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations No additional information available Manganese oxide (MnO2) (1313-13-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Lithium (7439-93-2) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Perchloric acid, lithium salt (7791-03-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Graphite (7782-42-5) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub	ostances) ostances)
Listed on the Canadian DSL (Domestic Substances List) EU-Regulations No additional information available Manganese oxide (MnO2) (1313-13-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Lithium (7439-93-2) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Perchloric acid, lithium salt (7791-03-9) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Graphite (7782-42-5) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Sub Propylene carbonate (108-32-7)	ostances) ostances)

Polv	nrony	vlene i	(9003-0	17-0
	pi op			

Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)

Safety Data Sheet This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200
Manganese oxide (MnO2) (1313-13-9)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Japanese Pollutant Release and Transfer Register Law (PRTR Law) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)
Lithium (7439-93-2)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)
Perchloric acid, lithium salt (7791-03-9)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on the TCSI (Taiwan Chemical Substance Inventory)
Polytetrafluoroethylene (9002-84-0)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)
Graphite (7782-42-5)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)
Propylene carbonate (108-32-7)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)
Ethylene glycol dimethyl ether (110-71-4)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIOC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)

Safety Data Sheet

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

15.3. US State regulations

No additional information available

SECTION 16: Other information	
Issue date	: 16/09/2019
Revision date	: 16/09/2019
Data sources	: Loli. ECHA reference.

Key or legend to abbreviations and acronyms used in the safety data sheet

ADR	European Agreement Concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
ADN	European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterway
RID	Regulations Concerning the International Carriage of Dangerous Godds by Rail
PBT	Persistent, Bioaccumulative and Toxic
vPvB	Very Persistent and Very Bioaccumulative
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
LC50	Lethal Concentration 50
LD50	Lethal Dose 50
EC50	Effective Concentration 50
TWA	Time Weighted Average
STEL	Short Term Exposure Limit

ECHA: http://echa.europa.eu/

IFA GESTIS: http://gestis-en.itrust.de/nxt/gateway.dll?f=templates\$fn=default.htm\$vid=gestiseng:sdbeng

HSDB: http://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm

ICSC: http://www.ilo.org/dyn/icsc/showcard.home

eChemPortal: http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

NITE-CHRIP: http://www.nite.go.jp/en/chem/chrip/chrip_search/srhInput

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product