

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

1. Identification of the Substance / Preparation and of the Company / Undertaking

Product identifier

Product Name UG Uni-proof RV & Marine -50 °F Burst Antifreeze
Stock Numbers 132701 / 132705

Other means of identification

Synonyms Not available.

Recommended use of the chemical and restrictions on use

Recommended Use RV & Marine Antifreeze.

Uses advised against Not available.

Details of the supplier of the safety data sheet

Supplier Name South/Win, Ltd.
Supplier Address 112 Maxfield Rd.
Greensboro, NC 27405 US
Supplier Phone Number Phone: (800) 648-4393
Fax: (336) 398-5680
Emergency Phone: CHEMTREC: (800) 424-9300

2. Hazards Identification

GHS INFORMATION

Classification: Flammable Liquids, Category 3
Eye Irritation, Category 2A

Signal Word

Hazard Statement:

Flammable liquid and vapor.
Causes serious eye irritation

Warning



Appearance Red

Physical State Liquid

Odor Almost Odorless



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

Precautionary Statements

- Prevention:** Keep away from heat, sparks, open flames, and hot surfaces. – No smoking. Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical, ventilating, and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Wear protective gloves, protective clothing and eye protection.
- Response:** If on skin (or hair): Take off immediately all contaminated clothing.
Rinse skin with water/shower.
If in eyes; Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use dry chemical, CO₂, water spray or alcohol-resistant foam to extinguish.
- Storage:** Store in a well-ventilated place. Keep cool.
- Disposal:** Dispose of contents/container in accordance with applicable regional, national, and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: None.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200).

This material is considered hazardous by the Hazardous Products Regulations, 2015.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

3. Composition / Information on Ingredients

Ingredient(s)	Common name / Synonyms	CAS No.	% wt./wt.
Water	Not available.	7732-18-5	70 - 80
Ethanol	Not available.	64-17-5	10 - 20
1,2-Propanediol	Propylene glycol	57-55-6	3 - 5
Phosphoric acid, potassium salt (1:2)	Potassium phosphate, dibasic	7758-11-4	< 1

4. First-Aid Measures

- Inhalation:** If inhaled: Call a poison center or doctor if you feel unwell.
Acute and delayed symptoms and effects: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, and confusion, loss of appetite and/or loss of consciousness.
- Eye Contact:** If in eyes: Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Acute and delayed symptoms and effects: Causes serious eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Ethanol may cause painful sensitization to light, chemical conjunctivitis and corneal damage.
- Skin Contact:** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a poison center or doctor if you feel unwell.
Acute and delayed symptoms and effects: May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.
- Ingestion:** If swallowed: Call a poison center or doctor if you feel unwell. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
Acute and delayed symptoms and effects: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible)
- Note to Physician:** Symptoms may not appear immediately.



Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

5. Fire-fighting Measures

FLAMMABILITY AND EXPLOSION INFORMATION

Flammable liquid and vapor. Will be easily ignited by heat, sparks, or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors, or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Liquid is lighter than water.

If tank, railcar or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

Fire involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

Sensitivity to Mechanical Impact: This material is not sensitive to mechanical impact.
Sensitivity to Static Discharge: Take precautionary measures against static discharge. This material is sensitive to static discharge.

MEANS OF EXTINCTION

Suitable Extinguishing Media: Small Fire: Dry chemical, CO₂, water spray or alcohol-resistant foam.
Large Fire: Water spray, fog or alcohol-resistant foam. Move containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media: Do not use straight streams.

Products of Combustion: Oxides of carbon. Oxides of phosphorus. Potassium oxide.

Protection of Firefighters: Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

6. Accidental Release Measures

Emergency Procedures: As an immediate precautionary measure, isolate spill or leak area. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area). All equipment used when handling the product must be grounded.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

Personal Precautions:	Do not touch or walk through spilled material. Use personal protection recommended in Section 8.
Environmental Precautions:	Prevent entry into waterways, sewers, basements or confined areas.
Methods for Containment:	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors.
Methods for Clean-Up:	Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material.
Other Information:	See Section 13 for disposal considerations.

7. Handling and Storage

Handling:

Do not swallow. Avoid breathing mist, vapours, or spray. Avoid contact with eyes, skin, or clothing. Keep away from heat, sparks, open flames, and hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. See Section 8 for information on Personal Protective Equipment.

Storage:

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Do not store in unlabeled containers and use appropriate containment to avoid environmental contamination. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Exposure Guidelines Component

Water [CAS No. 7732-18-5]

ACGIH: No TLV established.

OSHA: No PEL established.

Ethanol [CAS No. 64-17-5]

ACGIH: 1000 ppm (TWA); A3 (2008)

OSHA: 1000 ppm (TWA), 1900 mg/m³ (TWA);

Propylene glycol [CAS No. 57-55-6]

ACGIH: No TLV established.

OSHA: No PEL established.

Potassium phosphate, dibasic [CAS No. 7758-11-4]

ACGIH: No TLV established.

OSHA: No PEL established.

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

PEL: Permissible Exposure Limit

TLV: Threshold Limit Value

TWA: Time-Weighted Average

Engineering Controls:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapour, gas, etc.) below recommended exposure limits. Use explosion-proof electrical, ventilating, and lighting equipment.

PERSONAL PROTECTIVE EQUIPMENT (PPE)



Eye/Face Protection:

Wear safety glasses with side shields or chemical goggles. Ensure that eyewash stations are close to the workstation location. Use equipment for eye protection that meets the standards referenced by CSA Standard CAN/CSA-Z94.3-92 and OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.

Hand Protection:

Wear protective gloves. Nitrile rubber gloves are recommended. Consult manufacturer specifications for further information.

Skin and Body Protection:

Wear protective clothing. Flame resistant clothing that meets the NFPA 2112 and CAN/CGSB 155.20 standards is recommended in areas where material is stored or handled.

Respiratory Protection:

If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA- Z94.4-11, with organic vapor cartridge, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air- purifying respirators.

General Hygiene Considerations:

Handle according to established industrial hygiene and safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

9. Physical and Chemical Properties

Appearance:	Clear, red liquid.
Colour:	Red.
Odour:	Almost odourless.
Odour Threshold:	Not available.
Physical State:	Liquid.
pH:	Not available.
Melting Point / Freezing Point:	Not available.
Initial Boiling Point:	85 °C (185 °F)
Boiling Range:	85 to 93.3 °C (185 to 200 °F)
Flash Point:	43 °C (109.4 °F) (TCC)
Evaporation Rate:	Not available.
Flammability (solid, gas):	Not applicable.
Lower Flammability Limit:	3.3 % (Ethanol)
Upper Flammability Limit:	19 % (Ethanol)
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density:	0.97 (Water = 1) at 21.1 °C (70 °F)
Solubilities:	Soluble in water.
Partition Coefficient: n-Octanol/Water:	Not available.
Auto-ignition Temperature:	363 °C (685.4 °F) (Ethanol)
Decomposition Temperature:	Not available.
Viscosity:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	Not available.
Density:	8.05 lb/gal
Coefficient of Water/Oil Distribution:	Not available.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

10. Stability and Reactivity

Reactivity:	Contact with incompatible materials. Sources of ignition. Exposure to heat.
Chemical Stability:	Stable under normal storage conditions.
Possibility of Hazardous Reactions:	None known.
Conditions to Avoid:	Contact with incompatible materials. Sources of ignition. Exposure to
Incompatible Materials:	Strong acids. Strong bases. Oxidizers.
Hazardous Decomposition Products:	Not available.

11. Toxicological Information

EFFECTS OF ACUTE EXPOSURE

Product Toxicity

Oral:	Not available.
Dermal:	Not available.
Inhalation:	Not available.

Component Toxicity

Component	CAS No.	LD50 oral	LD50 dermal	LC50
Water	7732-18-5	> 90 mL/kg (rat)	Not available.	Not available.
Ethanol	64-17-5	7060 mg/kg (rat)	20000 mg/kg (rabbit)	20000 ppm (rat); 10H
Propylene glycol	57-55-6	20000 mg/kg (rat)	20800 mg/kg (rabbit)	Not available.
Potassium phosphate, dibasic	7758-11-4	Not available.	Not available.	Not available.

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Blood. Central nervous system.

Symptoms (including delayed and immediate effects)

Inhalation: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, and confusion, loss of appetite and/or loss of consciousness.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

Eye: Causes serious eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Ethanol may cause painful sensitization to light, chemical conjunctivitis and corneal damage.

Skin: May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Ingestion: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Skin Sensitization: Not available.

Respiratory Sensitization: Not available.

Medical Conditions Aggravated By Exposure: Not available.

EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Blood. Cardiovascular system. Liver. Kidneys. Reproductive system. Central nervous system.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation. Prolonged exposure to Ethanol may cause liver, kidney, and heart damage.

Carcinogenicity: Product is not classified as a carcinogen. See Component Carcinogenicity table below for information on individual components. Animal studies with Ethanol have reported the development of tumours.

Component Carcinogenicity

Component	ACGIH	IARC	NTP	OSHA	Prop 65
Ethanol	A3	Not listed.	Not listed.	Not listed.	Not listed.

Mutagenicity: Laboratory experiments with Ethanol have resulted in mutagenic effects.

Reproductive Effects: Ethanol may cause reproductive effects.

Developmental Effects

Teratogenicity: Not available.

Embryotoxicity: Ethanol has been shown to produce fetotoxicity in the embryo or fetus of laboratory animals. Prenatal exposure to ethanol is associated with a distinct pattern of congenital malformations that have collectively been termed the "fetal alcohol syndrome".

Toxicologically Synergistic Materials: Not available.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

12. Ecological Information

Ecotoxicity:	Not available.
Persistence / Degradability:	Not available.
Bioaccumulation / Accumulation:	Not available.
Mobility in Environment:	Not available.
Other Adverse Effects:	Not available.

13. Disposal Considerations

Disposal Instructions: Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

14. Transport information

U.S. Department of Transportation (DOT)

Exempted under DOT CFR49 173.150(e). Product conforms to the water alcohol exemption.

This product is exempted under the "Limited Quantity Regulation" when packed in containers of one gallon or less.

Canada Transportation of Dangerous Goods (TDG)

Proper Shipping Name: UN1987, ALCOHOLS, N.O.S. (Ethanol), 3, PG III

Class: 3

UN Number: UN1987

Packing Group: III

Label Code:





Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

15. Regulatory information

Chemical Inventories US

(TSCA)

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

Federal Regulations

United States

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA Title III

No components are listed.

State Regulations

Massachusetts

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

Component	CAS No.	RTK List
Ethanol	64-17-5	Listed.

New Jersey

US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

Component	CAS No.	RTK List
Ethanol	64-17-5	SHHS
Propylene glycol	57-55-6	Listed.

Pennsylvania

US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Component	CAS No.	RTK List
Ethanol	64-17-5	Listed.
Propylene glycol	57-55-6	Listed.

California

California Prop 65: This product does not contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 7-Jun-2015

SDS Number: 9164

16. Other information

Prepared By: Randy Boitz

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet