



TRINITY GLASS
INTERNATIONAL

Direct Glazed Fiberglass Door
In-swing (IS) and Out-swing (OS)
TGI-M-11*

ENERGY PERFORMANCE RATINGS

Product Description** Default Frame*** PVC	U-Factor ¹ / Solar Heat Gain Coefficient (SHGC)			
	Individual Option Number			
	1/4 Lite ≤410†	1/2 Lite ≤900†	3/4 Lite ≤1100†	Full Lite >1100†
Optilite/Air/Lami (3mm/9mm) 1" IG	0.19 / 0.08 00160-00001	0.21 / 0.15 00192-00001	0.23 / 0.19 00224-00001	0.25 / 0.25 00256-00001

Air Leakage ≤0.3 cfm/ft²

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.

* Numbers below the performance ratings are referenced in the NFRC Certified Products Directory (e.g., ABC-X-1-00001-00001 or 123-X-1-00001-00001)

** #glazing layers / spacer type / low-e emissivity (surface) / gap fill / gap width (na=not applicable)

*** per NFRC 100

† square inches ¹ btu/hr*ft²*F

www.nfrc.org



ENERGY STAR® Certified in All 50 States

Certificado por ENERGY STAR en los 50 estados