© Arlo Technologies, Inc. Arlo, Arlo logo, and Every Angle Covered are trademarks of Arlo Technologies, Inc. Any other trademarks are for reference purposes.

Si ce produit est vendu au Canada, vous pouvez accéder à ce document en français canadien à *arlo.com/docs*.

(If this product is sold in Canada, you can access this document in Canadian French at *arlo.com/docs*.)

For regulatory compliance information including the EU Declaration of Conformity, visit *www.arlo.com/about/regulatory/*.


All-in-One Sensor Quick Start Guide

December 2024


201-50797-02

Arlo Technologies, Inc.
5770 Fleet St, Suite 200
Carlsbad, CA USA 92008


What's in the box




All-in-One Sensor




Magnet with Adhesive



Sensor Adhesive



Flat Wall Plate with Short Screw and Anchor



Corner Wall Plate with Long Screw and Anchor


Note: Your sensor might not need a wall plate, depending on how it will be used. The Arlo Secure App explains this during setup.

Battery Access and Onboarding


After you install your Keypad Sensor Hub, you can use the Arlo Secure App to add All-in-One Sensors.

To install your All-in-One Sensor:


1. Remove screw cover from Sensor using the flat side of the screwdriver.




2. Turn captive screw counterclockwise (~6 times). Screw will turn freely but won't come out.



3. Slide front cover down to reveal the battery and remove black tab located underneath battery.



4. Once tab is removed, ensure battery is still in place and the plus symbol is facing up.




Note: The sensor is for indoor use only. The Arlo Secure App shows you how to separate and reattach the screw cover and back cover from the housing.

Note: Keep the screw cover and back cover separate from your Sensor.

5. **Onboard your Sensor. Open the Arlo Secure App, tap the "+" icon to add device, and follow setup instructions for your All-in-One Sensor.**




6. **Reattach front and back cover, then slide until lines are aligned and you hear a click.**



7. **Using the screwdriver, turn the screw clockwise to tighten it securely.**



8. **Place bottom of screw cover in first, then snap top part in.**



Do not attach the sensor adhesive unless the app instructs you to do so. If you're using the sensor to detect water leaks, the adhesive isn't needed.

Need help?

We are here for you.

Visit *www.arlo.com/support* for quick answers and:

- How-to videos
- Troubleshooting tips
- Additional support resources