



96" TropoAir Liberator

Weight = 34.1 lbs. in box

Weight = 30.4 lbs. out of box

MODEL #9TB96



REQUIREMENTS

MECHANICAL:

Fan must be attached to a securely anchored electrical junction box that is rated for ceiling fans. Fan must also be mounted at least 10 feet above floor level.

ELECTRICAL:

Requires a grounded electrical supply line of 120 volts, 60Hz, 1 amp circuit.

FEATURES

MOTOR SPECS:

55W DC Motor

LOCATION USE:

This fan is rated cETLus and meets the standard for UL-507 and CAN/CSA-C22.2 No. 113.

WARRANTY:

Limited Lifetime Indoor & 10-Year Outdoor

OPTIONS

AVAILABLE FINISHES:

Brushed Nickel BN-1	Part #88501-88514
Oil Rubbed Bronze	Part #88503-88518
Pure White	Part #88502-88513

BLADES:

Match Fan Finish

CONTROL:

Six speeds and reversing function is controlled by the included Hand Held remote control.

LIGHTING:

Optional light kit available at additional cost. #610 Light is an 18-watt LED Array with 1400 Lumens and 3000 Kelvin.

DOWNROD:

The fan comes with a nom. $\frac{3}{4}$ " diameter x 9" long down-rod. Optional down-rods are available in 12", 24", 36", 48", 60" and 72" lengths. A down-rod coupler is available for installations requiring a down-rod longer than 72". Fan can be mounted on a sloped ceiling up to 35°.

PERFORMANCE

AIRFLOW/ENERGY EFFICIENCY INFO

Fan Speed	RPM	CFM/ Watt	WATT	CFM
High	70	281	55	15500
Med	51		15.7	
Low	33	1342	4.5	6043

Dimensions:		
Canopy Diameter	Sweep Diameter	
5 5/8"	96"	
Downrod Length	Blade Depth	All Depth
9"	17"	18"
12"	20"	21"
24"	32"	33"
36"	44"	45"
48"	56"	57"
72"	80"	81"