

MOISWELL

DEHUMIDIFIER

MODEL	Defender M70
POWER SOURCE	120V~60Hz
RATED POWER (95°F, 90% RH)	1050W
RATED CURRENT (95°F, 90% RH)	8.8A
MOISTURE REMOVAL CAPACITY(65°F,60% RH)	48 Pints/Day
MOISTURE REMOVAL (80°F,60% RH)	70 Pints/Day
MOISTURE REMOVAL (95°F,90% RH)	145 Pints/Day
INPUT POWER (65°F, 60% RH)	510W
INPUT CURRENT (65°F, 60% RH)	4.5A
IEF (65°F, 60% RH)	1.80 liters/kWh
MOTOR FLA	0.6A
MOTOR COMPRESSOR	RLA:8.2A LRA:30A
REFRIGERANT	R32/280g(9.88ozs)
MAXIMUM ALLOWABLE PRESSURE	6.5MPa
MAXIMUM ALLOWABLE DISCHARGE PRESSURE	4.0MPa
MAXIMUM ALLOWABLE SUCTION PRESSURE	1.7MPa
SERIAL NO.	240100001
DATE MANUFACTURED	01/2024

MADE IN CHINA



C

US

CONFORMS TO UL STD .60335-
1& 60335-2-40
CERTIFIED TO CSA STD.C22.2
NO.60335-1& 60335-2-40

