


Specialty standard grade receptacles

Product description

2-pole, 3-wire grounding
15A, 125V/AC
15A, 250V/AC



TR780




78



TR5797

Design features

- Tamper resistant receptacles provide compliance with 2014 NEC® Article 406.12 which states that all 15A and 20A, 125V/AC receptacles installed in dwelling units must be tamper resistant 
- Surface receptacles for use with surface mounted wiring to expand convenience receptacles on solid plaster, brick or concrete walls
- Floor box assembly includes heavy-duty single receptacle on recessed mounting strap, 18 cu. in. steel back box, solid brass cover, gasket and threaded brass closure cap with watertight neoprene rubber "O" ring
- High impact-resistant thermoplastic face and back body eliminates breakage
- Double-wipe ground contacts ensure long-term ground retention
- Tri-combo screws accept Slotted, Phillips, and Robertson-head tools for installation flexibility
- Side wire terminals accept up to #10 AWG solid wire
- Recessed receptacles feature a virtually unbreakable thermoplastic housing and tamper resistant shutters

Recessed receptacles



| Rating | | Description | Color | Catalog no. | |
|--------|------|---|-------|-------------|---|
| A | V/AC | | | | |
| 15 | 125 | Tamper resistant NEMA 5-15R single receptacle, with clock hanger, side wire | W | □ TR775W | • |
| 15 | 125 | Tamper resistant NEMA 5-15R duplex receptacle, push wire side wire | W | □ TR780W | |

cULus Listed to UL498, file no. E15058; NOM certified

Surface receptacle NEMA 5-15R



| Rating | | Description | Color suffix | Catalog no. | | |
|--------|------|--------------------------------------|--------------|-------------|---|---|
| A | V/AC | | | | | |
| 15 | 125 | NEMA 5-15R duplex surface receptacle | B, V | □ 78__ | • | • |

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Surface receptacle NEMA 6-15R



| Rating | | Description | Color | Catalog no. | |
|--------|------|--------------------------------------|-------|-------------|---|
| A | V/AC | | | | |
| 15 | 250 | NEMA 6-15R duplex surface receptacle | V | □ 74V | • |

Listed to UL498, file no. E15058; NOM certified

Floor box receptacles



| Rating | | Description | Color | Catalog no. |
|--------|------|--|-------|-------------|
| A | V/AC | | | |
| 15 | 125 | Tamper resistant NEMA 5-15R single receptacle brass floor box assembly, back & side wire | BR | □ TR5797 |

cULus Listed to UL498, file no. E15058

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: B (Black), BR (Brass), V (Ivory), W (White)



Dimensional information: B-68, B-69 **Specification information:** Please visit www.eaton.com/wiringdevices
Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page G-21

RoHS compliant - Page G-21

Tamper resistant