



The NXT1A Fiberglass single sided stepladder is now loaded with new advanced features. Multi functional HolsterTop® PRO keeps tools organized and safe on the ladder top. A magnetic strip and hardware bins keep parts and tools easily accessible and secure. The right handed drill hammer slot and pipe channel are conveniently located for ease of use. Comfortable slip resistant steps. The EDGE 360™ provides protection from every angle. The EDGE bracing system, oversized foot pad and rail shield, provide added rail protection. Great for electrical jobs. New great features and a robust 300 lbs. load capacity to maximize your productivity.

Features

- 4 rivets attach top to each front rail
- Back-up plates to reinforce top connectors
- Designed for one person jobs
- Every rivet backed up by metal plate or washer to protect fiberglass
- Full set of rear horizontals
- Internal Spreaders
- Molded braces
- Shoulder bolt and nut on top hinge
- Slip-resistant foot pad
- Slip-resistant Traction-Tred steps
- Slip-resistant Traction-Tred steps all knee braced

Dimensions

| Feature | Size |
|------------------------|------------------|
| Top Dimension | 5-3/4 in x 13 in |
| Front Rails Dimension | 3-1/8 in |
| Front Flange Dimension | 1-4/16 in |
| Rear Rails Dimension | 1-7/8 in |
| Rear Flange Dimension | 1-3/16 in |
| Steps Dimension | 3 in |

Specifications

| Feature | Size / Details |
|-----------------------------|---|
| Size | 6 ft |
| Reach Height | 10 ft |
| Max. Standing Height | 3 ft 10 in |
| Description of Top Features | Paint tray slot, can hook, Lock in accessory sockets, 2 tool holes, drill hole, p int, quart & gallon paint can, 2 parts trays, tape measure slot |
| Edge Bracing | Heavy |
| Load Capacity | 300 lbs |
| Type | Type IA Duty Rating |
| Performance Rating | ★★★★ |
| Material | Fiberglass |
| Approx. Width | 23-3/8 in |
| Approx. Spread | 41-1/4 in |
| With Pail Shelf | No |
| Spreader Material | Steel |
| Certifications | ANSI A14.5 (2007); OSHA |
| Approx. Cu. Ft. Per Unit | 5.3 |
| Approx. Shipping Wt. Lbs. | 22 |