

# DOMINATOR®

APRIL 2023

## PRODUCT OVERVIEW

Introducing **DOMINATOR® Mulch Anchor** – the innovative solution for worry-free landscaping. Are you tired of constantly reapplying mulch and gravel in your landscaping area due to washout and erosion? Look no further than Mulch Anchor. With its strong, water-based formula, Mulch Anchor acts as a mulch glue and gravel binder, perfect for keeping your landscaping materials in place. Not only does it reduce erosion, but it also makes it easier to blow leaves and debris off, leaving your mulch exactly where it belongs.

Worried about the safety of your pets or plants? Fear not! **DOMINATOR® Mulch Anchor** is non-toxic, water permeable, and safe for pet paws. Its long-lasting, fast-acting properties will set in just 6-24 hours (depending on weather conditions) and last 12-24 months before needing reapplication. Make your landscaping tasks less laborious and more efficient with Mulch Anchor. For the best results, apply on dry mulch or pea gravel. Say goodbye to washout and hello to worry-free landscaping with **DOMINATOR® Mulch Anchor**.

## FEATURES AND BENEFITS

- Non-toxic and pet friendly
- Ready to use formula for no waste
- Maximum hold on a variety of mulch types
- Fast acting formula – Completely set in 6-24 hours
- Long lasting control – up to 24 months before re-application

## PHYSICAL DATA

Product Type:	Water-based
Finish:	Clear
Components:	One; no mixing required
Curing Mechanism:	Air dry
Coverage:	Coverage rate ranges depending on type of surface and whether light or heavy coverage is required; see the Coverage Chart
Shelf Life:	Best used within 12 months of manufacture

Refer to the Safety Data Sheet for more technical detail.

**CONTACT INFORMATION:** Black Diamond Coatings, Inc. 6036 Nature Coast Blvd. Brooksville, FL 34602.  
[www.BDCbrands.com](http://www.BDCbrands.com) | 800-270-4050 | [info@BlackDiamondCoatings.com](mailto:info@BlackDiamondCoatings.com)  
 © 2023 Black Diamond Coatings, Inc.

## DOMINATOR® MULCH ANCHOR

FOR HOW-TO & VIDEO  
SCAN ME!



WWW.BDCBRANDS.COM

Use this product on the following surfaces:

Surface	DOMINATOR® Mulch Anchor
Pine Straw	✓
Cypress Mulch	✓
Rubber Mulch	✓
Pea Gravel	✓
Dirt/Sand (dust control)	✓

NOTE: Application instructions refer to application on mulch but this product may be used on any of the above surfaces.

## COVERAGE RATE CHART

25 Sq. Ft.	Light (to keep mulch in a landscaped area)	Heavy (slopes, significant rain, or leaf blowing)
Shredded Mulch Pine Straw Small Pea Gravel	1/3 Gal. for 1 coat (apply 2 coats)	3/4 Gal. for 1 coat (apply 2 coats)
Rubber Mulch Large Bark Larger Gravel	1/2 Gal. for 1 coat (apply 2-3 coats)	1 Gal. for 1 coat (apply 2-3 coats)

## APPLICATION PROCESS

### 1. PREPARE

**Protect surfaces not intended to be treated.** Ensure that walls, mulch borders and other surfaces are protected as needed.

**Ensure proper surface temperature.** Ensure ambient air temperature stays above 32° F until product is dry. If temperature falls below 32° F, performance of the product may be adversely affected. NOTE: Maximum product performance is achieved at 50° F or higher.

**A dry surface is best** for ensuring proper product adhesion. **Avoid applying the product when rain is forecasted within 24 hours to prevent product loss.**

**Use the proper equipment.** We recommend a pump style or battery-type sprayer to properly apply this product.

### 2. TEST

**Perform a small test area** (at least 2 sq. ft.) using the product to ensure suitability and the desired results prior to full application. Test for application coverage rate. Use the same preparation, equipment and conditions expected during the entire application. Due to the wide variety of substrates, preparation methods, application methods and environments, the customer should test the product in an inconspicuous spot for penetration and compatibility prior to full application.

### 3. APPLY

Do NOT Dilute or alter the product. Shake the DOMINATOR® Mulch Anchor container prior to use as some settling may have occurred.

**Apply the number of coats of Mulch Anchor as indicated in the Coverage Chart to your surface.** When spraying, use even, broad strokes to ensure uniform coverage. Apply liberally to the mulch areas. Under-application will not allow the product to perform properly.

Take necessary precaution not to apply to any surface not intended to be treated. Some settling may occur during application. If this happens, shake the container / sprayer enough to re-suspend the product and resume application.

**Allow sufficient dry times.** Mulch Anchor requires air to dry, so we recommend waiting at least 45 minutes to 1 hour between coats.

### 4. CLEANUP

Place any unused product back into original container to store for future use. Any mixture exposed to air will harden in the container. Clean equipment thoroughly until free of product residue. Product will stain clothing but can be removed from skin with a mild cleaner. If the product meets clothing, wash immediately and do not allow product to dry on clothing.

**Store and handle properly.** Store in a cool, dry place, but do not let the product freeze; and dispose of properly if it is allowed to freeze.

Please note: Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

### CUSTOMER CARE

We pride ourselves on being available to assist with product and job-related questions, including application instructions. Call 800-270-4050 or visit our website at [www.BlackDiamondCoatings.com](http://www.BlackDiamondCoatings.com) for additional product information.

### LIMITED WARRANTY

Black Diamond Coatings, Inc. (BDC) warrants this product to be free of defects when it is manufactured and shipped. All recommendations, information and technical data are based on the research of BDC and that of others and are believed to be accurate and reliable. However, the accuracy and completeness are not guaranteed because we cannot cover every scenario, including surfaces, conditions and application methods. Where permitted by law, BDC makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. User shall test the product on a small inconspicuous area to ensure desired results are achieved using the same conditions and equipment as expected during the entire application. User shall rely on his/her own knowledge and testing to determine the suitability of the product for a particular purpose and assume all risks and liability in connection thereto. Acceptance and use of this product absolves BDC from any other liability, from whatever source, including liability for special, indirect or consequential damages, and the liability of BDC shall not exceed the price of this product. A proof of purchase will be required for any claim of a defective product. Replacement of any defective product shall be the buyer's sole remedy under this warranty. This warranty may not be modified or extended by representatives of BDC or its distributors.