

Installation Tips

Your new floor is a free-floating floor system that requires no glues or fasteners to install. Make sure you are installing your floor over a sound, solid surface. Patch or fill any very large holes, or grind any protrusions from the substrate. Your modular floor is made with the latest technology in high-tech composite polymers. It is very strong, light weight, and can support a great deal of weight. The following are a few key tips that will make your installation process trouble free.

- Start your installation from either side of the inner door opening and work inward. Be sure to start on the side that has the longest and straightest wall.
- During your floor installation, keep nothing on top of the floor as your floor will self correct as you go.
- Do your entire trimming at the hottest part of the day and with nothing on top of the floor.
- Be sure to leave a minimum of 1/2" space between the floor edge and wall (or anything such as cabinets, door rails, steps, etc). Your floor edge should never be up against anything.
- When bringing everything back into your newly surfaced area, do so at the hottest part of the day, when the floor is fully expanded to its maximum.
- Never try to glue down or fasten your floor, it is designed to expand and contract.
- Save your trim pieces, they may be able to be used in other areas of your garage install.
- Day to day cleaning is performed by sweeping and mopping with water and a degreaser. Solvent-based solutions can be used to clean stubborn areas without harming the flooring. To aid in separating the floor for removal, slide a broom handle under the floor at a joint and slide it along the joint to separate the locks.