## **Specifications**



## Nottely Touchless Single-Handle Pull-Down Kitchen Faucet FEATURES · Requires 1 or 3-Hole Sink with 8" On-Center MODEL SKU # FINISH Flexible Supply Lines with 3/8" Compression Fittings 305514647 HD67495-1001 Chrome · Max Flow Rate: 1.8 gpm (6.8 L/min) at 60 psi Max Countertop Thickness: 2 5/32" HD67495-1008D2 305188336 **Stainless Steel** Spout Reach: 7 1/2" 305514641 HD67495-1027D Bronze Spout Height: 14 19/32" · Ceramic Valve for Lifetime Drip-Free Operation • With Zinc Lever Handle · With Hands-Free ON/OFF Technology With TurboSpray FastMount Installation CODE COMPLIANCE · IAPMO Certified: ASME A112.18.1/CSA B125.1 · Compliant to NSF/ANSI 61 Section 9 · Compliant to NSF/ANSI 372 · Calgreen Certified · Meets AB 1953 Lead Standard · ADA Compliant GREEN 9 5/8" [244.6mm] 6 10 19/32 [269.3mm] 7 1/2" [190.6mm] WARRANTY · Limited Lifetime Warranty 14 19/32" 14 19/32" [370.9mm] [370.9mm] 7 21/32" [194.7mm] С Max: 2 5/32" [54.7mm] 9/16-24UNEF-2B INSTALLATION DIMENSIONS

Glacier Bay reserves the right to make changes in specifications and materials and to change and discontinue models, both without notice or obligation. Dimensions are for reference only.