



**DYNAGRIP®**  
THE GRIP THAT OUTPERFORMS™

# Technical Data Bulletin

## FOAMBOARD

### Construction Adhesive

DAP® DYNAGRIP® FOAMBOARD construction adhesive is a premium grade adhesive specifically formulated for insulation foam paneling installation. This VOC compliant adhesive provides excellent adhesion to foam panels and a variety of construction materials. DYNAGRIP® FOAMBOARD is an instant grab adhesive that provides a strong permanent bond and will not etch or burn through foam panels.



**STRONG  
PERMANENT  
BOND**



**INSTANT  
GRAB**



**NO ETCH  
OR BURN  
THROUGH**

#### Recommended For:

- Polystyrene Foam
- Foam Insulation Panel Installation

#### Adheres To:

- Concrete
- Dimensional Lumber
- Drywall
- Foam Insulation Panels
- Furring Strips
- Masonry
- OSB
- Plywood
- Polystyrene Foam
- Wood

#### Not Recommended For:

- Bonding two non-porous materials
- Constant water exposure
- Mirror installation
- Applications other foamboard panel installation

DAP Products, Inc.  
2400 Boston Street, Suite 200  
Baltimore, MD 21224  
Phone: 410-675-2100  
REV: 11/01/2016

SKU #	SIZE
7079827519	10.3oz



**CAUTION!**  
Read back panel carefully for cautions.  
**(PRECAUCION!** Lea cuidadosamente  
el panel posterior sobre otras precauciones.  
10.3 FL. OZ. (305 mL)



**DYNAGRIP**  
THE GRIP THAT OUTPERFORMS™

## FOAMBOARD

### Product Features

- Easy Water Clean Up
- Easy To Gun
- Low Odor
- VOC Compliant

### Directions

**FOR BEST RESULTS:** Apply in temperatures above 40°F. Keep adhesive above 40°F for easier gunning. One surface must be porous. Store away from extreme heat or cold.

**INSTRUCTIONS:** 1. Surfaces must be clean, structurally sound, and free of debris. 2. Pre-cut and fit materials before applying adhesive. 3. Trim nozzle to desired bead size. ¼" recommended for most applications. 4. Puncture inner foil seal. 5. Load cartridge into applicator gun. 6. Apply a continuous bead to edges of furring strips or backer material. 7. Within 10 minutes, position and press panels firmly into place. 8. Apply mechanical fasteners and brace as needed. 9. Allow to dry for 24 hours.

**CLEAN UP:** Uncured adhesive: wash away with warm water and soap. Cured adhesive: must be cut or scraped away.

**USAGE INFORMATION:** For usage information or warranty information, please contact DAP Technical Customer Service at 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on "Ask the Expert".

Contains: Ethylene glycol and urea.

May be harmful if swallowed or in contact with skin. May cause eye, skin, nose, throat and respiratory tract irritation. Avoid breathing vapors. Use only with adequate ventilation. Ensure fresh air entry. Avoid contact with eyes, skin and clothing. Wear rubber gloves and eye protection with side shields.

**WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**FIRST AID:** SKIN CONTACT: Wash skin thoroughly with soap and water. EYE CONTACT: Immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: **DO NOT INDUCE VOMITING.** Get medical attention immediately if complications arise from exposure. For emergencies, call poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit [dap.com](http://dap.com).

**KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.**

### TYPICAL PHYSICAL PROPERTIES

- Type: Synthetic Latex
- Application Temperature: 40°F to 100°F
- Service Temperature: 0°F to 140°F
- Bead Color: Off White
- Solids: 68%
- Shelf Life: 18 months
- Skin Time: 20 minutes
- Cure Time: 7 days
- Coverage:
  - 10.3oz: ¼" bead yields 32 linear ft., 3/8" bead yields 14 linear ft.
- Specifications:
  - ASTM C557 Meets or Exceeds.
- Calif. ARB VOC <0.8% Wt/Wt
- VOC Content: VOC less Water, less Exempt Solvent: <32 g/L