

QO240CP

Mini circuit breaker, QO, 40A, 2 pole, 120/240 VAC, 10 kA, plug in mount, consumer pack



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	40 A
Voltage Rating	120/240 V AC 120 V AC 48 V DC
Mounting Type	Plug-in
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs
Type of packing	Consumer packaging

Complementary

Interrupt Rating	10 kA 120/240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz 5 kA 48 V DC
Number of Panel Spaces	2
Wire Size	AWG 8...AWG 2 copper or aluminium
Tightening torque	44.25 lbf.in (5 N.m) 0.02...0.04 in ² (10...25 mm ²) AWG 8...AWG 2)
Maximum Height	3.12 in (79.25 mm)
Maximum Depth	2.91 in (73.91 mm)
Maximum Width	1.5 in (38.10 mm)

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	01341 - QO 2 POLE BULK BRKRS15-60A
Discount Schedule	CPQ
GTIN	00047569838040
Nbr. of units in pkg.	5
Package weight(Lbs)	0.55 lb(US) (0.25 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.50 in (3.81 cm)
Package 1 width	3.20 in (8.128 cm)
Package 1 Length	3.10 in (7.874 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	2.95 lb(US) (1.338 kg)
Package 2 Height	3.10 in (7.874 cm)

Package 2 width	3.20 in (8.128 cm)
Package 2 Length	7.80 in (19.812 cm)
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Weight	30.25 lb(US) (13.721 kg)
Package 3 Height	8.20 in (20.828 cm)
Package 3 width	7.90 in (20.066 cm)
Package 3 Length	17.30 in (43.942 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product