

• TRUSTED QUALITY SINCE 1921 •
RUST-OLEUM®
SPECIALTY

RUST-OLEUM® MARBLE SPRAY PAINT

DESCRIPTION AND USES

Rust-Oleum® Marble spray paint creates a raised webbing-like texture that mimics the look of a marble finish. Perfect for use on vases, lamps, tabletops, and other home accents. Use directly on a surface, or over a base coat of any color for a custom look. For use on interior surfaces.

PRODUCTS

SKU	DESCRIPTION (10.25 Oz. Aerosol)
372484	Marble Black
372487	Marble White

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT.

SURFACE PREPARATION

Remove loose paint and rust with wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRIMING

Use of a Rust-Oleum primer provides superior adhesion and hiding and is especially recommended for bare wood and metal.

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

PAINTING

Shake can vigorously for one minute after mixing ball begins to rattle. Shake often during use. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Hold can upright 12-14" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying.

DRY AND RECOAT TIMES

Based on 70°F (21°C) – 50% relative humidity. Allow more time at cooler temperatures. May recoat at anytime. Dries to the touch in 20 minutes and to handle in 1 hour. Fully dry in 24 hours.

CLEAN UP

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet paint with Xylol or mineral spirits. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick pin or other object into the stem.

	TECHNICAL DATA	SPC-118
• TRUSTED QUALITY SINCE 1921 • RUST-OLEUM® SPECIALTY	RUST-OLEUM® MARBLE SPRAY PAINT	

PHYSICAL PROPERTIES

		MARBLE SPRAY PAINT
Resin Type		Vinyl Acetate
Pigment Type		Varies with Color
Solvents		Acetone
MIR		0.28 Max
Fill Weight		10.25 oz.
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	5 minutes
	Handle	10 minutes
	Recoat	Anytime
	Full Cure	15 minutes
Shelf Life		2 years
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.