

INSTALLATION INSTRUCTION

Installation Grade Levels, Methods and Environment

This product can be installed on, above or below grade levels; either floated or glued; indoors use only.

CAUTION!

TRAFFICMASTER PRODUCT DOES NOT CONTAIN ASBESTOS. EXISTING INSTALLED RESILIENT FLOORING AND ASPHALTIC ADHESIVE MAY CONTAIN ASBESTOS OR CRYSTALLINE SILICA.

See "Recommended Work Practices for Removal of Resilient Floor Coverings" at www.rfci.com

CAUTION!

CALIFORNIA RESIDENTS: This product can create wood dust and emits formaldehyde, both are known to the State of California to cause cancer.

WOOD DUST: Sawing, sanding and machining wood products can produce wood dust. It causes respiratory, skin and eye irritation. Avoid prolonged exposure to wood dust. If high dust levels are encountered use an appropriate NIOSH-designated dust mask.

Owner/Installer Responsibility

Owner/installer should inspect the flooring for defects prior to installation and during installation.

During installation, do not install planks which appear to be defective.

After installation, inspect the floor from a standing position. Minor scratches can generally be repaired with the use of putty, stain or filler. It is an industry standard practice of flooring installation.

Job Site Condition

Manufacturer will decline responsibility for situations associated with improper installation or poor site conditions.

Pouring of basement concrete floors, drywall and plasterwork, plumbing, etc. must be completed well in advance of the floor delivery.

Job site should be in a normal living condition, i.e., room temperature of 60°F-80°F and relative humidity (RH) level of 35%-60%.

Concrete Subfloor Requirements

It must be cured. It must be clean. It must be flat and level (3/16 inch for every 10 feet).

Minimum moisture barrier is 6 mil (0.006 inch) virgin polyethylene sheet.

It must have moisture content of:

- Less than 5% as per Tramex Concrete Moisture Encounter or;
- Less than 3 lbs. per 1000 square feet per 24 hours per Calcium Chloride test (ASTM F-1869) or;

- Less than 2.5% per Calcium Carbide (CM) test (ASTM D-4944-04 modified).

Wood Subfloor

It must be clean. It must be flat and level (3/16 inch for every 10 feet).

It must have moisture content of less than 14%.

It must be structurally sound.

Underlayment

Sound reducing underlayment is required. Either attached or separate.

Existing Floor Coverings

Acceptable floor coverings include: linoleum, vinyl carpet tile, terrazzo, ceramic tile and other "moisture sealing floors."

Unacceptable floor coverings include: carpet, needle punch felt, edge glued linoleum and other "moisture absorbing flooring."

Radiant Heated Floor

This product can be installed over radiant heated floor. Special install precautions apply.

The finished floor surface temperature must not exceed 85°F throughout the service life of the floor.

Wet Areas

This product can be installed in bathrooms, kitchens, mud rooms, foyers, powder rooms and laundry rooms.

Do not install in saunas, swimming pool areas and other similar extreme wet areas.

Fill all expansion gaps with water repellent sealant. Seal joints between panels.

Acclimation

This product does not require acclimation provided there are no extreme temperature and humidity differences between retailer, transportation and final installation site.

Expansion Gaps

Allow expansion gap of 5/16 inch to 3/8 inch around perimeter of the floor and vertical structures.

Floor spanning greater than 40 feet, length or width, require expansion T-molding.

Wall openings, with or without door, require expansion T-molding.

Tools

You need the following tools to install this product: tapping block, pull bar, spacers, tape measure, hammer, circular saw, saw blade with carbide tip for finish cuts, work gloves.

Helpful Considerations

Work in well lit area.

Install flooring perpendicular to the direction of the floor joists. If possible, install the boards parallel to the direction of the light entering the room.

Install the underlayment in the same direction that the laminate flooring is to be installed. Tape all seams.

Stagger end joints but avoid stair-stepping appearance by varying stagger distances between adjacent rows. Minimum stagger distance is 6 inches.

Boards cut from the opposite end of the row may be used for the next row starter boards.

Click Lock Technique

Position the second panel in the groove of the first panel at a 20° or 30° angle.

Move the panel gently up and down while exerting pressure toward the first panel.

The panel will lock into place. See diagrams below.

Maintenance and Care

Please Note: Damages resulting from improper care and maintenance of the floor are not covered by warranty.

- 1. Sweep or dust mop regularly. If vacuuming, use vacuum head with a brush or felt, not a head equipped with a beater.

- 2. Do not leave any amount of liquids (water, juice, soft drinks, spills, etc.) on the floor. Clean any wet spots immediately.

- 3. Avoid excessive exposure to water from tracking during periods of inclement weather.

- 4. Never use a wet mop or douse floor with water or liquid cleaners. Liquid can seep between the cracks and cause moisture damage.

- 5. Never use a steam cleaner.

- 6. Do not use any cleaning agents containing wax, oil or polish. Left over residue will form a dull film. For tough spots, use damp cloth or apply a little alcohol or nail polish remover on the clean cloth, rub till spot is removed.

- 7. Do not use steel wool or scouring powder which will scratch the floor.

- 8. Minimize abrasive and dirt by placing mats on both sides of exterior doors. Area rugs in high-traffic areas are also a good idea.

- 9. Place protective pads beneath furniture legs and other heavy objects. Keep furniture casters clean.

- 10. Keep pets' nails trimmed.

- 11. Remove shoes with cleats, spikes or exceptionally pointy heels before walking on the floor.

- 12. Take great care when moving furniture and heavy objects. Lay down a protective sheet or plywood.

- 13. Do not obstruct in any way the expansion joint around the perimeter of your floor.

Warranty

This product comes with manufacturer's limited residential or commercial warranty, depending on which model was purchased. Warranty applies to original purchaser of the flooring. Please contact Customer Service Representative by calling our toll free number below for a written copy of the warranty which provides detailed terms of coverage and limitations.

Technical Support

For installation information and technical questions not covered in this installation guide, please contact Technical Support Representative by calling the toll free number.

Toll Free Number: 877-630-1800

INSTRUCCIONES DE INSTALACIÓN

Niveles, métodos y entornos de instalación

Este producto puede instalarse al nivel, por encima del nivel o por debajo del nivel del suelo, ya sea de forma flotante o con pegamento; sólo para uso en interiores.

¡PRECAUCIÓN!

EL PRODUCTO TRAFFICMASTER NO CONTIENE ASBESTO. LOS PISOS FLEXIBLES Y EL ADHESIVO ASFÁLTICO PREVIAMENTE INSTALADOS PUEDEN CONTENER ASBESTO O SÍLICE CRISTALINA.

Consultar las "Prácticas recomendadas para la extracción de los revestimientos para pisos flexibles" (Recommended Work Practices for Removal of Resilient Floor Coverings) en www.rfci.com

¡PRECAUCIÓN!

RESIDENTES DE CALIFORNIA: Este producto puede producir aserrín y emitir formaldehído, los cuales el Estado de California reconoce como causantes de cáncer.

ASERRÍN: Serruchar, lijar o trabajar la madera, puede producir aserrín. El aserrín puede causar irritación en la piel, ojos y vías respiratorias. Evita la exposición prolongada al aserrín. Si hay demasiado polvo usa una mascarilla antipolvo apropiada, certificada por el Instituto Nacional para la Seguridad y Salud Ocupacional (NIOSH, en inglés).

Responsabilidades del propietario/installador

El propietario/installador deberá inspeccionar el piso para detectar defectos antes de la instalación y durante la misma.

Durante la instalación, no coloques tablas que tengan aspecto defectuoso.

Luego de la instalación, ponte de pie e inspecciona el piso desde esa posición. Por lo general, los rayones menores pueden repararse con masilla, tinte o relleno. Esta es una práctica estándar de la industria de la instalación de pisos.

Condiciones del lugar de trabajo

El fabricante rechaza la responsabilidad por situaciones relacionadas con la instalación inadecuada o malas condiciones del lugar de trabajo.

Los pisos de concreto en sótanos los trabajos con drywall, yeso, plomería, etc., deben estar terminados mucho antes de que el piso sea entregado.

El lugar de trabajo deberá encontrarse en una condición normal de habitabilidad, es decir, con una temperatura ambiente de entre 60°F y 80°F, y un nivel de humedad relativa (RH) de entre 35% y 60%.

Requisitos del contrapiso de concreto

Debe estar curado. Debe estar limpio. Debe estar nivelado y plano (46 cm por cada 3 m).

La barrera mínima de humedad es una lámina de polietileno virgen de 6 milésimas de pulgada (0.15 mm).

Debe tener un contenido de humedad de:

- Menos de 5% conforme a la medición realizada con Tramex Concrete Moisture Encounter o

- Menos de 1.36 kg cada 93 m2 durante 24 horas conforme al resultado de la prueba con Cloruro de calcio (ASTM F-1869) o

- Menos de 2.5% conforme al resultado arrojado por la prueba con Carburo de calcio (CM) (ASTM D-4944-04 modificada).

Contrapiso de madera

Debe estar limpio. Debe estar nivelado y plano (46 cm por cada 3 m).

Debe tener un contenido de humedad menor al 14%.

Debe ser estable estructuralmente.

Contrapiso

Se requiere un contrapiso con aislamiento acústico. Ya sea colocado en forma complementaria o por separado.

Recubrimientos de pisos existentes

Los recubrimientos de pisos aceptables incluyen: linóleo, recubrimientos de alfombra de vinilo, terrazo, losa de cerámica y otros "pisos que sellan la humedad".

Los recubrimientos de pisos inaceptables incluyen: alfombra, fieltro punzonado, linóleo pegado en los bordes y otros "pisos que absorben la humedad".

Pisos de calefacción radiante

Este producto puede instalarse sobre pisos de calefacción radiante. Deben tomarse precauciones especiales.

La temperatura de la superficie del piso terminado no debe exceder los 85°F a lo largo de la vida útil del piso.

Áreas húmedas

Este producto puede instalarse en baños, cocinas, salas de fangoterapia, salas de estar, tocadores y cuartos de lavado.

No lo instales en saunas, áreas de piscinas y otras zonas similares extremadamente húmedas.

Rellena todas las separaciones de expansión con sellador impermeable. Sella las juntas entre paneles.

Aclimatación

Este producto no necesita aclimatación ya que no existen diferencias extremas de temperatura y humedad entre la tienda minorista, el transporte y el lugar de instalación final.

Separaciones de expansión

Deja separaciones de expansión de entre 0.79 cm y 0.95 cm alrededor del perímetro del piso y las estructuras verticales.

Una separación de más de 12 metros de largo o ancho necesita molduras de expansión en forma de T. Las aberturas en la pared, con o sin puerta, requieren molduras de expansión en forma de T.

Herramientas

Necesitarás las siguientes herramientas para instalar este producto: taco para martillar, barra de tracción, espaciadores, cinta métrica, martillo, sierra circular, sierra con punta de carburo para cortes de acabado, guantes de trabajo.

Consejos útiles

Trabaja en un área bien iluminada.

Instala el material de piso de forma perpendicular a la dirección de las vigas del piso. Si fuese posible, instala las tablas de forma paralela a la dirección en que la luz entra a la habitación.

Instala el contrapiso en la misma dirección en que se colocará el piso laminado. Cubre todas las uniones con cinta.

Escalona las juntas de los extremos pero varía las distancias entre las filas adyacentes para evitar que parezcan peldanos de escalera. La distancia mínima de escalonamiento es de 15.24 cm.

Las tablas cortadas desde el extremo opuesto de la fila pueden usarse para iniciar la siguiente fila de tablas.

Técnica Click Lock

Coloca el segundo panel en la ranura del primer panel en un ángulo de 20° o 30°.

Mueve el panel suavemente hacia arriba y hacia abajo ejerciendo presión contra el primer panel. El panel se fijará en su lugar. Ver los diagramas a continuación.

Cuidado y mantenimiento

Ten en cuenta: Los daños que resulten del cuidado y mantenimiento inadecuado del piso no están cubiertos por la garantía.

1. Barre o pasa el trapo rítmicamente. Al aspirar, usa el cabezal de la aspiradora con un cepillo o fieltro, no un cabezal con ruedas.

2. No dejes restos de líquidos (agua, jugo, bebidas gaseosas, derrames, etc.) sobre el piso. Limpia cualquier mancha de inmediato.

3. Evita exponer el