



Material Safety Data Sheet (MSDS)

According to ISO 11014-2009

Report No.: DGC180409025KEA02

Date: Dec. 17, 2020

Page 1 of 10

Product Name: Lead-acid battery (2V/4V/6V/12V)

MSDS

According to ISO 11014-2009

Applicant:

Foshan City Shunde Ocean Electric Co.,Ltd

Address:

No.8,Longsheng 11 RD Longyan,Leliu Town,
Shunde,Foshan City,Guangdong,China.

Product Name:

Lead-acid battery (2V/4V/6V/12V)

Issue date:

Dec. 17, 2020

Edited by:

NTEK Testing Technology Co., Ltd.

Written by:

Kelly

Checked by:



Approved by:

Caby

This document cannot be reproduced except in full, without prior written approval of NTEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

NTEK Testing Technology Co., Ltd.

Address: Building 3, Meisaidaxin Park, Keji 8th Road, Songshan Lake High-Tech Industrial Development Zone,
Dongguan, Guangdong, China

Tel: (+86-769) 23301666

Fax: (+86-769) 23301600

Email: service@ntek.org.cn

<http://www.dgntek.org.cn>



Material Safety Data Sheet (MSDS)

According to ISO 11014-2009

Report No.: DGC180409025KEA02

Date: Dec. 17, 2020

Page 2 of 10

Product Name: Lead-acid battery (2V/4V/6V/12V)

Section 1 - Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Lead-acid battery (2V/4V/6V/12V)

Model: 0.5-2000ah

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Emergency power supply

Uses advised against: No information available.

1.3 Details of the supplier of the safety data sheet

Supplier: Foshan City Shunde Ocean Electric Co., Ltd

Address: No.8, Longsheng 11 RD Longyan, Leliu Town, Shunde, Foshan City, Guangdong, China.

E-mail: 474657369@qq.com

Telephone: 13652912395

Fax: 0757-25339998

1.4 Emergency telephone number: /

Section 2 - Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation GHS

Skin Corr. 1A : H314

Oral Acute Tox. 4 * : H302

Inhalation Acute Tox. 4 * : H332

Repr. 1 : H360

STOT RE 2 : H373

Aquatic Acute 1 : H400

Aquatic Chronic 1 : H410

2.2 Label elements

Labelling according to Regulation GHS

The product is classified and labelled according to the GHS regulation.

This document cannot be reproduced except in full, without prior written approval of NTEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

NTEK Testing Technology Co., Ltd.

Address: Building 3, Meisaidaxin Park, Keji 8th Road, Songshan Lake High-Tech Industrial Development Zone,
Dongguan, Guangdong, China

Tel: (+86-769) 23301666

Fax: (+86-769) 23301600

Email: service@ntek.org.cn

<http://www.dgntek.org.cn>



Material Safety Data Sheet (MSDS)

According to ISO 11014-2009

Report No.: DGC180409025KEA02

Date: Dec. 17, 2020

Page 3 of 10

Product Name: Lead-acid battery (2V/4V/6V/12V)

Hazard pictogram(s):



GHS05



GHS07



GHS08



GHS09

Signal word: Danger

Hazard statement(s):

- H314 Causes severe skin burns and eye damage.
H302 Harmful if swallowed.
H332 Harmful if inhaled.
H360 May damage fertility or the unborn child .
H373 May cause damage to organs through prolonged or repeated exposure
exposure cause the hazard.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements:

- P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash ... thoroughly after handling.
P270 Do no eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required.
P310 Immediately call a POISON CENTER or doctor/physician.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

This document cannot be reproduced except in full, without prior written approval of NTEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

NTEK Testing Technology Co., Ltd.

Address: Building 3, Meisaidaxin Park, Keji 8th Road, Songshan Lake High-Tech Industrial Development Zone,
Dongguan, Guangdong, China

Tel: (+86-769) 23301666

Fax: (+86-769) 23301600

Email: service@ntek.org.cn

<http://www.dgntek.org.cn>



Material Safety Data Sheet (MSDS)

According to ISO 11014-2009

Report No.: DGC180409025KEA02

Date: Dec. 17, 2020

Page 4 of 10

Product Name: Lead-acid battery (2V/4V/6V/12V)

P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see ... on this label).
P322	Specific measures (see ... on this label).
P330	Rinse mouth.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of contents/container to ...

2.3 Other hazards:

No hazards occur during the normal operation of a Lead Acid Battery as it is described in the instructions for use that are provided with the Battery. Lead Acid Batteries have three significant characteristics:

1. They contain an electrolyte which contains diluted sulphuric acid. Sulphuric acid may cause severe chemical burns.
2. During the charging process or during operation, they might develop hydrogen gas and oxygen, which under certain circumstances may result in an explosive mixture.

This document cannot be reproduced except in full, without prior written approval of NTEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

NTEK Testing Technology Co., Ltd.

Address: Building 3, Meisaidaxin Park, Keji 8th Road, Songshan Lake High-Tech Industrial Development Zone,
Dongguan, Guangdong, China

Tel: (+86-769) 23301666

Fax: (+86-769) 23301600

Email: service@ntek.org.cn

<http://www.dgntek.org.cn>



Material Safety Data Sheet (MSDS)

According to ISO 11014-2009

Report No.: DGC180409025KEA02

Date: Dec. 17, 2020

Page 5 of 10

Product Name: Lead-acid battery (2V/4V/6V/12V)

3. They can contain a considerable amount of energy, which may be a source of high electrical current and a severe electrical shock in the event of a short circuit.

The Batteries have to be marked with the symbols listed under section 15.

Environment hazard: Batteries no matter in the atmosphere or buried in deep underground, the heavy metals will overflow with the exudate, may cause the pollution of groundwater bodies, soil, serious harm to human health.

Burning explosion harm: Inflammable and explosive.

Section 3 – Composition/Information on Ingredient

3.1 Chemical characterization: Mixtures

Description:

Product: consisting of the following components.

Chemical Name	CAS No.	EC No.	Concentration
lead	7439-92-1	231-100-4	80%
Sulphuric acid	7664-93-9	231-639-5	10%
Silicon Dioxide	7631-86-9	231-545-4	2%
Potassium Oxide	12136-45-7	235-227-6	1%
ABS shell	9003-56-9	/	7%

Section 4 - First Aid Measures

Skin: If electrolyte leakage occurs and makes contact with skin, immediately remove contaminated clothing, scrub with a dry cloth first, then wash with plenty of water, wash with 3%-5% NaHCO₃ solution finally. Get medical aid.

Eyes: Immediately flush eyes with plenty of water. Occasionally lifting the upper and lower eyelids. Get medical aid.

Inhalation: Immediately move to fresh air, maintain the airway smooth. Difficulty in breathing, give oxygen. If breathing stops, artificial respiration should begin immediately. Get medical aid.

Ingestion: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

This document cannot be reproduced except in full, without prior written approval of NTEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

NTEK Testing Technology Co., Ltd.

Address: Building 3, Meisaidaxin Park, Keji 8th Road, Songshan Lake High-Tech Industrial Development Zone,
Dongguan, Guangdong, China

Tel: (+86-769) 23301666

Fax: (+86-769) 23301600

Email: service@ntek.org.cn

http://www.dgntek.org.cn



Material Safety Data Sheet (MSDS)

According to ISO 11014-2009

Report No.: DGC180409025KEA02

Date: Dec. 17, 2020

Page 6 of 10

Product Name: Lead-acid battery (2V/4V/6V/12V)

Section 5 – Fire and Explosion Hazard Data

Fire disaster/Explosion risk: Generally, security, no fire and no explosion. While, severe impact and high fever may cause explode.

Extinguishing agent: Carbon dioxide, dry chemical or foam extinguishers.

Fire extinguishing methods: 1. Fire personnel are required to wear self-contained breathing apparatus to avoid breathing irritant fumes. Wear protective clothing and equipment to prevent body contact with electrolyte solution. 2. Rapid evacuation of emergency personnel to leave the fire, quickly cut off the fire source. 3. To mist cooling the tanks or containers exposed to fire. 4. If the spill has not ignited, water spray mist to spread the steam and to protect personnel attempting to stop the leak. 5. Large area of the large fire, use water spray control of unmanned aircraft operated or automatic swinging fire hose.

Fire-fight notes : 1. Move containers as far as possible from the fire scene to department. 2. In imposing the upper hand to avoid the risk of steam and toxic decomposition products. 3. Tank safety valve has been sounded, or discoloration due to fire and immediately evacuated.

Section 6 - Accidental Release Measures

The information is of relevance only if the battery is broken and the ingredients are released.

Clean-up methods: 1. Isolate leakage pollution area, access restricted. 2. Recommend emergency personnel to wear self positive pressure respirator and acid-base proofing overalls. 3. Do not contact with the leakage directly, if the chemical substances leaked outside of battery, try neutralizing exposed battery parts with soda ash or sodium bicarbonate until fizzing stops, and using sand or bonding agent to absorb split acid. 4. Collect residue in a suitable container and place the broken battery in a heavy-duty plastic bag or other non-metallic container.

Note: 1. Leakage region ventilation. 2. Fight or remove all ignition sources. 3. To prevent leakage of material into the sewer or confined space. 4. Notify the government health and safety and environmental protection-related units.

This document cannot be reproduced except in full, without prior written approval of NTEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

NTEK Testing Technology Co., Ltd.

Address: Building 3, Meisaidaxin Park, Keji 8th Road, Songshan Lake High-Tech Industrial Development Zone,
Dongguan, Guangdong, China

Tel: (+86-769) 23301666

Fax: (+86-769) 23301600

Email: service@ntek.org.cn

<http://www.dgntek.org.cn>



Material Safety Data Sheet (MSDS)

According to ISO 11014-2009

Report No.: DGC180409025KEA02

Date: Dec. 17, 2020

Page 7 of 10

Product Name: Lead-acid battery (2V/4V/6V/12V)

Section 7 - Handling and Storage

Handling Precautions: 1. With closed operation, provide a good natural ventilation. The operator must go through specialized training, strict compliance with operating rules. 2. Keep away from heat, ignition sources and no smoking. Use non-sparking ventilation explosion-proof type equipment. 3. Do not crush, short (+) and (-) battery terminals with conductive (i.e. metal) goods. 4. Do not directly heat or solder. Do not throw into fire or the place where may be submerged by water. 5. Do not be installed in sealed equipment. 6. Make sure than the connection between batteries is correct. 7. Do not use the battery in places where are full of dust (it should be regular checked when used in dusty environment). 8. Use tools which are with insulating bush when handling. 9. Do not clean the battery with diluent, gasoline, kerosene or composite liquid. 10. Slow handling when disassembly. 11. Do not cover the battery with materials which can produce static electricity. 12. Battery do not be thrown away, put in as much as possible separated from other garbage. 13. Pay special attention to be not smash foot.

Storage Precautions: 1. Stored in a cool, dry, well-ventilated place, keep batteries in non-conductive (i.e. plastic) trays. Storage areas should be clearly marked "no obstacles." 2. Away from combustibles areas. Away from heat, ignition sources. Avoid overheating and supercooling. Avoid contacting with metal containers directly, adopt acid proofing and flame resistant materials. 3. Near the storage areas have adequate fire extinguishers and spill clean-up equipment. 4. Avoid storing large quantities of indoor, as much as possible stored in the isolation of the fire building. 5. Small parts, avoid contact with children, to avoid being swallowed children.

Section 8 - Exposure Controls, Personal Protection

Engineering controls: Store batteries with adequate ventilation. Room ventilation is also required for batteries utilized for standby power generation. Never recharge batteries in an unventilated, enclosed space.

Personal Protective Equipment:

During installation, normal conditions of use or in the event of battery breakage, no exposure to lead and lead containing battery paste. Exposure to sulphuric acid and acid mist might occur during charge.

Respiratory protection: NIOSH approved acid mist/organic vapor respirator, if OSHA PEL is exceeded.

Eye protection: Chemical goggles, safety glasses with side shields and or a full-face shield.

Hand protection: Rubber, PVC or neoprene gloves

This document cannot be reproduced except in full, without prior written approval of NTEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

NTEK Testing Technology Co., Ltd.

Address: Building 3, Meisaidaxin Park, Keji 8th Road, Songshan Lake High-Tech Industrial Development Zone,
Dongguan, Guangdong, China

Tel: (+86-769) 23301666

Fax: (+86-769) 23301600

Email: service@ntek.org.cn

<http://www.dgntek.org.cn>



Material Safety Data Sheet (MSDS)

According to ISO 11014-2009

Report No.: DGC180409025KEA02

Date: Dec. 17, 2020

Page 8 of 10

Product Name: Lead-acid battery (2V/4V/6V/12V)

Body protection: Acid resistant apron or clothes

Other protection: In the workplace non-smoking or eating. Use standard lead-acid battery practices. Do not wear metallic jewelry when working with batteries. Use non-conductive tools only. Discharge static electricity prior to working on a battery. Maintain fire extinguisher and emergency communication device in the work area. After work, take a bath. Separate storage of contaminated clothing, washed standby. Pay attention to personal hygiene.

Hygiene measures: Follow correct safety rules, do not reuse the container that repair or without trade processed. Refer to the MSDS measures, even an empty container handling.

Section 9 - Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Solid
Colour:	Gray
Odour:	Odourless

Other information:

9.2 Additional information: No data available.

Section 10 - Stability and Reactivity

Stability: Stable under normal use, hazardous reactions occurring under specific conditions, such as overheating and overcharging.

Avoid material: Conductive materials, water, seawater, strong oxidizers, strong acids, strong alkaline materials, organic solvents

Avoid contact with conditions: When a battery cell is exposed to an external short-circuit, crushes, modification, high temperature above 100 °C, it will be the cause of heat generation and ignition. Direct sunlight and high humidity.

This document cannot be reproduced except in full, without prior written approval of NTEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

NTEK Testing Technology Co., Ltd.

Address: Building 3, Meisaidaxin Park, Keji 8th Road, Songshan Lake High-Tech Industrial Development Zone,
Dongguan, Guangdong, China

Tel: (+86-769) 23301666

Fax: (+86-769) 23301600

Email: service@ntek.org.cn

<http://www.dgntek.org.cn>



Material Safety Data Sheet (MSDS)

According to ISO 11014-2009

Report No.: DGC180409025KEA02

Date: Dec. 17, 2020

Page 9 of 10

Product Name: Lead-acid battery (2V/4V/6V/12V)

Hazardous decomposition products: Once batteries are breakage, split sulphuric acid should be careful which is corrosive, nonflammable liquid (thermal decomposition at 338°C) and destroys organic materials such as cardboard, wood, textiles and reacts with metals, producing hydrogen. Acid or harmful gas is emitted during fire.

Section 11 - Toxicological Information

Carcinogenicity: The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid mists containing sulfuric acid" as a category 1 carcinogen (inhalation), a substance that is carcinogenic to humans. This classification does not apply to the liquid forms of sulfuric acid contained within the battery. Misuse of the product, such as overcharging, may result in the generation of sulfuric acid mist at high levels.

Section 12 - Ecological Information

This information is of relevance if the battery is broken and the ingredients are released to environment. In order to avoid damage to the sewage system, the acid has to be neutralized by means of time or sodium carbonate before disposal. Ecological damage is possible by change of pH. The electrolyte solution reacts with water and organic substances, causing damage to flora and fauna. The electrolyte may also contain soluble components of lead that can be toxic to aquatic environments. Leaking metals will easily penetrate the soil, polluting groundwater, and then into the fish life, crops, the destruction of the human living environment, an indirect threat to human health. More importantly, the contaminated soil will be permanently lose its use value.

The waste batteries contain heavy metals can not be biodegradable and can accumulate in vivo.

Section 13 - Disposal Considerations

The nature of waste: Hazardous waste

Waste disposal methods: Dispose of batteries according to government regulations. Recommend sent to a special recycling bins of used batteries.

Notes waste: Do not waste batteries and garbage mixed together, to be dealt with separately.

This document cannot be reproduced except in full, without prior written approval of NTEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

NTEK Testing Technology Co., Ltd.

Address: Building 3, Meisaidaxin Park, Keji 8th Road, Songshan Lake High-Tech Industrial Development Zone,
Dongguan, Guangdong, China

Tel: (+86-769) 23301666

Fax: (+86-769) 23301600

Email: service@ntek.org.cn

<http://www.dgntek.org.cn>



Material Safety Data Sheet (MSDS)

According to ISO 11014-2009

Report No.: DGC180409025KEA02

Date: Dec. 17, 2020

Page 10 of 10

Product Name: Lead-acid battery (2V/4V/6V/12V)

Section 14 - Transport Information

In the case of transportation, confirm no leakage and no overspill from a container. Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo piles and wet by rain. The container must be handled carefully. Do not give shocks that result in a mark of hitting on a cell. In accordance with the above considerations when loading the batteries.

Section 15 - Regulatory Information

In accordance with EU Battery Directive and the respective national legislation, Lead Acid batteries have to be marked by a crossed out dust bin with the chemical symbol for lead shown below, together with the ISO return/recycling symbol.

Section 16 - Additional Information

References: N/A

The data in this Material Safety Data Sheet relates only to the specific material designated herein and will be used only for education, scientific research, enterprise product development and internal quality control or other purposes.



End of document

This document cannot be reproduced except in full, without prior written approval of NTEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

NTEK Testing Technology Co., Ltd.

Address: Building 3, Meisaidaxin Park, Keji 8th Road, Songshan Lake High-Tech Industrial Development Zone,
Dongguan, Guangdong, China

Tel: (+86-769) 23301666

Fax: (+86-769) 23301600

Email: service@ntek.org.cn

<http://www.dgntek.org.cn>