



Premium Interior/Exterior Latex High-Gloss GL71XX

DESCRIPTION

GLIDDEN™ interior/exterior high-gloss paint is perfect for trim, doors, cabinets and furniture because of its long lasting durable finish.



SPECIFICATION DATA

Color:

White & custom colors
Tint appropriate base with Dramatone™ Colorants

Finish: High-Gloss

Sheen - 90 units minimum @ 85°
Gloss - 65 units minimum @ 60°

Clean-up Solvent:

Soap & water

Density:

9.98 lbs/gal (1.20 kg/L)

VOC:

50 g/L (0.42 lbs/gal) maximum

Solids:

Volume - 36% +/- 1%
Weight - 48% +/- 1%

Practical Coverage:

Apply at 300-400 sq ft/gal (7-10 m²/L).
Actual coverage may vary depending on substrate and application method.

Recommended Film Thickness:

4.0 - 5.3 mils wet
1.4 - 1.9 mils dry

Flash Point:

None

Dry Time: 77°F (25°C) & 50% RH

To touch - 1 - 2 hours
To recoat - 4 hours

Shelf Life:

1 year minimum - unopened

FEATURES

- Durable gloss finish
- Weather resistant against blistering, peeling and flaking
- Fade and chalk resistant
- Provides a mildew resistant coating
- Easy application
- Quick drying and recoat
- Low odor and VOC

COMPOSITION

- 100% Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.



SURFACE PREPARATION

PREPARING PAINTED SURFACES FOR A PROFESSIONAL FINISH

Spackle holes or cracks • Lightly sand glossy areas.

Make sure all areas are clean, sound and free of flaking paint or any substances such as oil, grease, dirt...anything that will get between your surface and your paint. Prepare *Previously Painted Surfaces* with a GLIDDEN primer.

IT'S TIME TO PRIME - PREPARING UNPAINTED SURFACES

WALLBOARD - Joint compound must dry for two days before you apply a GLIDDEN primer.

INTERIOR WOOD - Set nails and fill holes with latex spackle. Sand lightly to a smooth surface, dust clean, then prime with a GLIDDEN primer.

EXTERIOR WOOD - Sand lightly to a smooth surface, dust clean, then prime with an exterior primer.

CONCRETE, PLASTER AND MASONRY - Cure for 30 days before painting. "Slick poured" or pre-cast concrete needs chemical

cleaning or a light sandblasting. Thoroughly rinse with water and allow to fully dry. Remove loose aggregate and prime with an appropriate masonry primer. For concrete block, fill with a latex block filler.

STEEL, GALVANIZED METAL AND ALUMINUM - Clean off oils, then prime with an appropriate metal primer.

WEATHERED ALUMINUM AND VINYL SIDING - Remove dirt and chalk. Prime with this product. If chalk remains after cleaning, prime with an exterior primer. When repainting vinyl siding, never use a color darker than the original color. Using a color darker than the original siding color will result in warping of the vinyl siding.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DIRECTIONS FOR USE

QUALITY TOOLS FOR A QUALITY JOB

Use a quality 1/4" – 3/8" nap roller, nylon or polyester brush, paint pad, or airless sprayer.

LET'S GET PAINTING

Mix thoroughly • Apply at package consistency • Thin only when using an airless sprayer if necessary using 1/2 pint water per gallon • Make sure the air, paint and the surface you are painting are above 50° F • Do not paint if rain, snow, heavy dew or lower temperatures are expected within 48 hours of painting • Apply generously, no overspreading • Certain colors may require more than one coat for complete hide • Ventilate & provide warmth for normal drying.

1. Stir with a lifting motion for uniform color.
2. Dampen roller slightly with water.
3. Brush/Edge a 3"- 4" border on wall around all edges.
4. In small sections, spread paint in a W pattern, then fill in with long, even strokes in the same direction.
5. Paint woodwork last with even strokes; paint away from the wet edge.

LET'S CLEAN UP

Clean hands and tools with warm, soapy water • Clean spills right away with a damp cloth • After 30 days or paint has fully cured, areas may be washed with a non-abrasive, mild detergent.

PRECAUTIONS

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL AND DIETHYLENE GLYCOL. ETHYLENE GLYCOL CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. DIETHYLENE GLYCOL MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS AND LIVER, KIDNEY DAMAGE. USE ONLY WITH ADEQUATE VENTILATION! KEEP OUT OF THE REACH OF CHILDREN. For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** For additional safety information, refer to the Material Safety Data Sheet for this product. If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.**

DS396-1205

SHIPPING

FREIGHT CLASSIFICATION:
Paint, Freezable

PACKAGING:
4 quart (0.9168 L)

FLASH POINT:
None



Akzo Nobel Paints LLC, Strongsville, Ohio 44136



1-800-GLIDDEN • www.glidden.com

LIMITATION OF LIABILITY To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.