

# BUILDMAN 6' DRYWALL BAKER™



<b>ASSEMBLED DIMENSIONS (W X D X H)</b>	<b>75.75 X 31 X 76 IN. (192.4 X 78.7 X 193 CM)</b>
<b>PACKAGE DIMENSIONS (W X D X H)</b>	<b>76.75 X 34.5 X 7 IN. (195 X 80.7 X 17.8 CM)</b>
<b>WEIGHT</b>	<b>180 LB (81.6 KG)</b>
<b>LOAD CAPACITY</b>	<b>1,500 LB (680 KG). COMBINED WEIGHT OF USER + MATERIALS</b>
<b>WORKING HEIGHTS</b>	<b>FROM 29 TO 71.5 IN. (73.7 TO 181.6 CM). 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS</b>
<b>REACH</b>	<b>12 FT (3.7 M). STACKABLE UP TO 2 UNITS HIGH FOR 18 FT (5.5 M) REACH</b>
<b>FINISH</b>	<b>POWDER COATED</b>
<b>PLATFORM</b>	<b>PLATFORM WITH TRAP DOOR. 19/32 IN. (15 MM) PLYWOOD, SLIP-RESISTANT</b>
<b>STRUCTURE</b>	<b>1.75 IN. (4.5 CM) SQUARE TUBE. 16 GAUGE STEEL</b>
<b>OPTIONS</b>	<b>GUARDRAILS SYSTEM (I-BMSGRJP) SET OF 4 OUTRIGGERS WITH CASTERS (I-BMSO4) SET OF 4 BASE PLATES (I-IBBF4) SET OF 4 LEVELING JACKS (I-IBSJP12H4) SCAFFLOCK SAFETY BRAKES (I-ISL) 39" HIGH EXTENSION (I-BMSSEX)</b>
<b>CASTERS</b>	<b>6 IN. (15 CM) DOUBLE LOCKING HEAVY DUTY</b>
<b>COMPATIBLE WITH</b>	<b>BILJAX, BUFFALO, WERNER, UST AND METALTECH BAKER*</b>
<b>STANDARDS</b>	<b>ANSI, CSA AND OSHA</b>
<b>MODEL</b>	<b>I-BMSS</b>
<b>UPC</b>	<b>778300100057</b>

\* All trademarks and registered trademarks listed above are the property of their respective owners.