

**Product** HOME-FLEX Underground<sup>®</sup> Anodeless Meter Riser, 3/4" - 2" IPS

**Project Information**

Job Name: _____	Date Submitted: _____
Location: _____	Submitted by: _____
Engineer: _____	Approved by: _____
Contractor: _____	Manufacturer's Rep: _____

**Installation**

Must be installed in accordance with the HOME-FLEX Underground<sup>®</sup> Installation Practices and Guidelines and in accordance with local codes.

**Application Information**

For use in Natural Gas and Liquefied Petroleum (Propane) Gas applications with Polyethylene (PE) gas pipelines.

**Technical Data**

*Materials*

Male Pipe Thread      Steel Gas Carrier (ASTM A53/API 5L)  
 Powder Coating      PPG-PCT70265  
 Plain End              Polyethylene Pipe (ASTM D513 )

*Pressure Ratings*

Max Operating Pressure      80 PSIG

*Temperature Ratings*

Operating Temperature Range      0°F - 140°F

**Codes**

Uniform Plumbing Code (UPC)  
 International Fuel Gas Code (IFGC)

**Standards**

ASTM F1973, D2513, A53/API 5L  
 ANSI B1.20.1

**Listings**

IAPMO Listed

**Dimensional Information**

	Size (IPS)	Part Number	Dimensions (in)			Weight (lbs)
			L	W	H	
	3/4" SDR 11	18-440-007	29	1.2	31	5
	1" SDR 11	18-440-010	29	1.6	31	6
	1-1/4" SDR 11	18-440-012	29	2.0	31	9
	1-1/2" SDR 11	18-440-015	29	2.2	31	14
	2" SDR 11	18-440-020	29	2.6	31	28

