



# Silicone Max™

## PREMIUM ALL PURPOSE 100% SILICONE

Provides **maximum** silicone performance to seal out air and water in window, door and siding applications. Provides **maximum flexibility and adhesion** to withstand contraction and expansion caused by temperature and weather fluctuations.

### MAXIMUM FLEXIBILITY

- +/- 50% joint movement. Meets ASTM C920, Class 50
- Withstands extreme joint movement without cracking or losing adhesion

### MAXIMUM PERFORMANCE

- All purpose, all surface versatility
- Water resistant in 30 minutes
- 100% waterproof & weatherproof
- Shrink & crack proof
- Low odor
- Lifetime guarantee
- Clear formula will NOT yellow
- White & Clear, 10.1 FL. OZ.



**Window, Door & Siding**



# Silicone Max™

## MAXIMUM SILICONE PERFORMANCE



Meets ASTM C920, Class 50 +/- 50% Dynamic Joint Movement	✓	Class 25, +/- 25%	✓
Widest Temperature Application Range: 40°F – 120°F	✓	40°F – 100°F	40°F – 100°F
Non-Yellowing Clear Formula	✓		
30 Minute Water Resistance	✓	✓	✓
Lifetime Guarantee	✓	✓	✓

### Ideal for Sealing:

- Windows
- Doors
- Siding
- Trim
- Flashing

### Maximum Adhesion to:

- Vinyl
- Aluminum
- Painted Surfaces
- Most Metals
- Wood
- Drywall/Plaster

#### SKU Specifications

Description	Size	Color	Product Code	GTIN 14	Case Pack	Case Weight (lbs.)	Case Dimensions (LxWxH)	Case Volume (cu. ft.)	Cases per Pallet
Silicone Max™ Premium All Purpose 100% Silicone	10.1 fl. oz.	White	0 70798 08790 3	100 70798 08790 0	12	11.96	8" x 6" x 12"	0.33	108
Silicone Max™ Premium All Purpose 100% Silicone	10.1 fl. oz.	Clear	0 70798 08791 0	100 70798 08791 7	12	9.74	8" x 6" x 12"	0.33	108