

Rule Quick Reference Guide

FLOAT SWITCH SPECIFICATIONS

| Model Number | Model Name | Volts (DC) | Max Amps | Wire Gauge | Size (height x length x width), inches (mm) |
|--------------|------------------------------------------------------|------------|----------------------------------|------------|---------------------------------------------|
| 35A | Rule- A-Matic | 12-24 | 14A (12v), 7A (24v) | 16 AWG | 2-1/4" x 5" x 1-3/4" (57 x 127 x 58mm) |
| 35FA | Rule- A-Matic with inline fuse holder | 12-24 | 14A (12v), 7A (24v) | | |
| 37A | Super Switch | 12-24-32 | 20A (12v), 10A (24V), 6.5A (32v) | 14 AWG | 2-1/4" x 5" x 2" (57 x 127 x 51mm) |
| 37FA | Super Switch with inline fuse holder | 12-24-32 | 20A (12v), 10A (24V), 6.5A (32v) | | |
| 40A | Rule-A-Matic Plus with shield | 12-24-32 | 20A (12v), 10A (24V), 6.5A (32v) | 14 AWG | 3" x 5-3/8" x 2-1/2" (76 x 137 x 64mm) |
| 40FA | Rule-A-Matic Plus with shield and inline fuse holder | 12-24-32 | 20A (12v), 10A (24V), 6.5A (32v) | | |
| 39 | ECO-Switch 12 Volt | 12 | 20A | 14 AWG | 1-7/8" x 6" x 2-3/4" (48 x 152 x 70mm) |
| 39-24 | ECO-Switch 24Volt | 24 | 10A | | |

RULE-MATE AUTOMATED BILGE PUMPS

| Capacity GPH (LPH) | Model No. | Volts | Fuse Size | Amps @12 v | Amps @13.6 v | Replacment Strainer | Height In. (mm) | Width In. (mm) | Hose Diameter In. (mm) | Panel Switches |
|--------------------|------------|------------|-----------|------------|--------------|---------------------|-----------------|----------------|------------------------|----------------|
| 500 (1893) | RM500A | 12DC | 3 | 2 | 2.2 | Model 1000864-26 | 4.5 (114) | 6 (152) | 3/4 (19.0) | 41, 43, 45 |
| | RM500A-24 | 24DC | 1.5 | 1.0 @ 24v | 1.3 @ 27.2v | | | | | 42, 44, 45 |
| 750 (2839) | RM750A | 12DC | 5 | 2.8 | 3.1 | Model 1000864-26 | 4.5 (114) | 6 (152) | 3/4 (19.0) | 41, 43, 45 |
| | RM750A-24 | 24DC | 3 | 1.4 @ 24v | 2.0 @ 27.2v | | | | | 42, 44, 45 |
| 900 (3407) | LP900S | 12DC | 7.5 | 4 | 5 | Model 1230R | 2.4 (60) | 2.4 (60) | Multiple | 41, 43, 45 |
| 1100 (4164) | RM1100A | 12DC | 5 | 3.4 | 4 | Model 1000864-26 | 4.5 (114) | 6 (152) | 1-1/8 (29) | 41, 43, 45 |
| | RM1100A-24 | 24DC | 3 | 1.4 @ 24v | 2.0 @ 27.2v | | | | | 42, 44, 45 |
| 1500 (5678) | RM1500A | 12DC | 10 | 4.8 | 7 | Model 286 | 6 (152) | 7.25 (185) | 1-1/8 (29) | 41, 43, 45 |
| 2000 (7571) | RM2000A | 12DC | 15 | 8.4 | 12 | | | | | 42, 44, 45 |
| | | RM2000A-24 | 24DC | 7.5 | 4.0 @ 24v | 6.0 @ 27.2v | | | | |

ELECTRONIC SENSING SERIES BILGE PUMPS

| Capacity GPH (LPH) | Model No. | Volts | Fuse Size | Amps @12 v | Amps @13.6 v | Replacment Strainer | Height In. (mm) | Width In. (mm) | Hose Diameter In. (mm) | Panel Switches |
|--------------------|-------------------|---------|-----------|------------|--------------|---------------------|-----------------|----------------|------------------------|----------------|
| 500 (1893) | 25SA-6 (6' wires) | 12DC | 4 | 1.6 | 1.8 | Model 1231R | 4.1 (104) | 2.9 (73) | 3/4 (19.0) | 41, 43, 45 |
| | 25SA | 12DC | 4 | 1.6 | 1.8 | | | | | 41, 43, 45 |
| | 25SA-24 | 24DC | 3 | 1.0 @ 24v | 1.2 @ 27.2v | | | | | 42, 44, 45 |
| 800 (3028) | 20SA | 12DC | 7.5 | 3.4 | 4.3 | Model 1232R | 4.7 (119) | 2.9 (73) | 1 (25) and 1-1/8 (29) | 41, 43, 45 |
| 1100 (4164) | 27SA | 12DC | 7.5 | 3.7 | 4.7 | | | | | 42, 44, 45 |
| | | 27SA-24 | 24DC | 4 | 1.9 @ 24V | 2.2 @ 24V | | | | |
| 2000 (7571) | 53S | 12DC | 15 | 8.4 | 12 | Model 278 | 7.75 (196.8) | 4.75 (121) | 1-1/8 (29) | 41, 43, 45 |
| 3700 (14010) | 55S | 12DC | 25 | 15.5 | 20 | Model 279 | 8.25 (209.5) | 4.9 (124) | 1-1/2 (38) | 41, 43, 45 |
| 4000 (15140) | 56S | 12DC | 25 | 15.5 | 20 | Model 279 | 9.25 (235) | 4.9 (124) | 2 (51.0) | 41, 43, 45 |

PANEL SWITCHES

| Part Number | Description | Volts (DC) | Max Amps (DC) | Size (width x height), Inches (mm) |
|-------------|------------------------------------|------------|-------------------------------|------------------------------------|
| 41 | 3 Way Panel Switch - Lighted | 12 | 20 | 3-1/4 x 2 (83 x 51mm) |
| 42 | 3 Way Panel Switch - Lighted | 24-32 | 10 (24V), 6.5 (32V) | 3-1/4 x 2 (83 x 51mm) |
| 45 | 3 Way Panel switch | 12-24-32 | 20 (12v), 10 (24v), 6.5 (32v) | 2-1/4 x 2 (57 x 51mm) |
| 43 | 3 Way Rocker Panel Switch- Lighted | 12 | 20 | 2-7/8 x 2-3/8 (73 x 60mm) |
| 44 | 3 Way Rocker Panel Switch- Lighted | 24 | 10 | 2-7/8 x 2-3/8 (73 x 60mm) |
| 49 | 2 Way Panel Switch | 12-24-32 | 20 (12v), 10 (24v), 6.5 (32v) | 2-1/4 x 2 (57 x 51mm) |



Warranty: All products of the company are sold and all services of the company are offered subject to the company's warranty and terms and conditions of sale, copies of which will be furnished upon request. The information provided herein is for guidance only, it does not constitute a guarantee of the performance or specification of any individual product or component.

marine.xylem.com

| | | | | | |
|------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| USA Xylem Inc. 100 Cummings Center Suite 535N Beverly MA, 01915 Tel: (978) 281-0440 Fax: (978) 283-2619 | UK Xylem Inc. Bingley Road, Hoddesdon Hertfordshire EN11 0BU Tel: +44 (0) 1992 450145 Fax: +44 (0) 1992 467132 | GERMANY Xylem Inc. Oststrasse 28 22844 Norderstedt Tel: +49-40-53 53 73-0 Fax: +49-40-53 53 73-11 | PHILIPPINES Xylem Inc. 12 Ring Road, LISP II Brgy. Lamesa, Calamba City 4027 Tel: 63 (49) 5434341 Fax: 63 (49) 5456817 | CHINA Xylem Inc. 18 Longyang Road Luhe (Nanjing) Jiangsu 211500 Tel: 86 (025) 57195000 | ITALY Xylem Inc. Via Tommaseo, 6 20059 Vimercate, Milano Tel: +39 039 685 2323 Fax: +39 039 666 307 |
|------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|

© 2016 Xylem Inc. All rights reserved. Rule is a registered trademark of Xylem Inc. or one of its subsidiaries. 950-0006 12/16

