

Use and Care

Before first use, run cold water for 5 minutes in filtered position.

During filter flush, it is normal to see cloudy water and hear the sound of water pushing air out of the filter cartridge. Flushing removes any loose materials, which is normal.

Prior to each use, run cold water for 5 seconds in filtered position to activate filter.

Never run hot water through the filter.

Do not use the water above 100°F/38°C as this may damage the filter. Use cold water only.


Change your filter every three months for best performance.

To change the filter or if you need sink space, remove the device from your faucet using the white Quick Release buttons. After each new filter cartridge is installed, run cold water for 5 minutes to flush it.

Clean the exterior of the faucet mount housing with a damp sponge or soft cloth.

A mild dishwashing liquid may also be used. Using anything else to clean your faucet mount could result in damage to the unit.

For more information, please visit PUR.com/support



Turn down the lever for filtered water.

Two Year Warranty

Kaz (Warrantor), warrants your PUR Faucet Mount Water Filter Unit (FM-2000B, FM-3333B, FM-4000B) for two (2) years from the date of purchase (except for the filter cartridge which is warranted for 30 days) against all defects in materials and workmanship, when used in compliance with the owner's manual.

If the product proves to be defective within two years from the date of purchase, call 1-800-787-5463. The warrantor assumes no responsibility for incidental or consequential damages; for damages arising out of misuse of the product or use of any unauthorized attachment; or for damages resulting from the use of the product with a defective water faucet. Some states do not allow the exclusion or limitation of incidental or consequential damages; so the above limitation or exclusion may not apply to you.

This warranty gives you specific legal rights, and you may have other legal rights which vary from state to state. System complies with applicable state and local regulations.

Should service be required or you have any questions regarding how to use your PUR product, please contact PUR Consumer Relations: PUR.com/support, 1-800-PUR-LINE, ConsumerRelations@kaz.com



You can fully recycle all of your PUR products and packaging free of charge through our partnership with TerraCycle®. Join the PUR Brigade® to recycle your old products and help us create a cleaner future. Please visit PUR.com/recycle to learn more.

Troubleshooting

Adapters don't fit / won't stay attached / keep falling off Installation issues	<ul style="list-style-type: none"> Check to make sure old aerator washer was removed and only the new adapter washer is being used.
Water leaks around the faucet adapter and faucet	<ul style="list-style-type: none"> Check to see that the washer was placed on top of the faucet adapter when installed. Make sure the adapter is hand-tightened securely to the faucet. Make sure the unit is securely attached to the faucet adapter.
Slow water flow, after 3 months of use, in the filtered position	<ul style="list-style-type: none"> When filter is near end of life, water will run slower in the filtered position. Replace your filter to ensure contaminant removal is at the certified levels."
Water leaks out around the filter cover	<ul style="list-style-type: none"> Try tightening faucet mount top cover all the way until tight. If that doesn't solve the problem, remove the filter cartridge and reinstall the filter cartridge again.
Difficulty removing the old filter cartridge to replace the filter	<ul style="list-style-type: none"> Remove the filter system unit from the faucet by squeezing the Quick Release buttons. Remove the cover. Slowly turn or twist the filter cartridge. This will help loosen the filter.

Technical Specifications:

FILTER CAPACITY:	100 gallons (378 liters)/up to 3 months
RATED SERVICE FLOW:	0.52 gallons/minute (2.0 liters/minute) at 60 psig
MAXIMUM TEMPERATURE:	100°F (38°C)
MINIMUM TEMPERATURE:	34°F (1°C)
MAXIMUM WORKING PRESSURE:	100 psig (690 kPa)
MINIMUM WORKING PRESSURE:	20 psig (138 kPa)

For system to perform as shown in the Performance Data Sheet, it is necessary to replace the filter when it exceeds filter capacity (100 gallons).

Testing was performed under standard laboratory conditions, actual performance may vary. The contaminants or other substances removed or reduced by this water filter are not necessarily in all users' water. Do not use with water that is microbiologically unsafe, or of unknown quality, without adequate disinfection before or after the system. Systems that are certified for cyst reduction may be used on disinfected water that may contain filterable cysts. Individuals requiring water of certain microbiological purity should consult their physician. Replacement filters may be purchased at most retail outlets or at PUR.com.



FM-2000B, FM-3333B, FM-3333BNM, FM-3400B, FM-3500B, FM-3700B, FM-4000B, FM-4100B, FM-9000B, FM-9100B, FM-9400B, FM-9600B
Systems Tested and Certified by NSF International against NSF/ANSI Standards 42, 53 and 401 for the reduction of the claims specified on the Performance Data Sheet.



FM-2000B, FM-3333B, FM-3333BNM, FM-3400B, FM-3500B, FM-3700B, FM-4000B, FM-4100B, FM-9000B, FM-9100B, FM-9400B, FM-9600B
Systems Tested and Certified by WQA against NSF/ANSI Standards 42, 53 and 401 for the reduction of the claims specified on the Performance Data Sheet.