



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 3/15/2017

## DAP® EXTREME STRETCH Premium Crackproof Elastomeric Sealant

### Professional Urethane Acrylic Sealant

- Stretches Over 600%
- Crackproof
- Superior multi-material adhesion strength
- Paintable in 2 hours (*Cool or humid conditions or type of paint used may require longer dry time.*)
- Excellent Paintability
- Easy Water Clean-up
- Low Odor
- Meets ASTM C920 Type S, Grade NS, Class 25
- Lifetime Guarantee
- Interior/Exterior

**Packaging:** 10.1 fl. oz. (300 mL) cartridge  
**Color:** White  
**UPC Number:** 7079818715

### Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224  
Usage Information: Call 1-888-DAP-TIPS or visit [dap.com](http://dap.com) & click on "Ask the Expert"  
Order Information: 800-327-3339  
Also, visit the DAP website at [www.dap.com](http://www.dap.com)

### Product Description:

**DAP® EXTREME STRETCH** is a premium urethanized sealant ideal for sealing a wide variety of interior & exterior surfaces. **EXTREME STRETCH** stretches over 600% and provides superior adhesion for a long lasting crackproof seal. Its unique formula is easy to apply & tool, low in odor & cleans up easily with water. Perfect for most sealing projects including windows, doors, trim, molding, siding, gutters, flashing, sinks, and countertops.

### *Ideal for Sealing:*

- *Windows*
- *Doors*
- *Baseboards*
- *Crown Molding*

- *Siding*
- *Eaves*
- *Vents*
- *Soffits*
- *Countertops*
- *Sinks*

*Adheres to:*

- *Wood*
- *Fiber Cement*
- *Tile*
- *Metal*
- *Plexiglass*
- *Fiberglass*
- *Stucco/Brick*
- *Vinyl*
- *Drywall*
- *Glass*
- *Aluminum*
- *Asphalt*
- *PVC Trimboard*
- *Mortar/Stone/Cinder Block*
- *Concrete*
- *EIFS*
- *Most Plastics*

**Performance Characteristics:**

- Exceeds the requirements of ASTM C920 standard specification for Elastomeric joint sealants, Type S, Grade NS, Class 25.
- Exceeds ASTM Spec C834 Standard Specification for Latex Sealants
- Offers excellent weatherability to resist UV light and temperature extremes without cracking, bubbling or becoming brittle.
- Provides a durable, long-lasting seal.
- Cured caulk is mildew resistant.
- Water clean-up.

**Surface Preparation & Application:**

1. Surface must be clean, dry and free of all old caulk, dirt, dust and grease.
2. Cut nozzle at a 45° angle to desired bead size.
3. Load into caulk gun.
4. Fill gap with sealant, pushing sealant ahead of nozzle.
5. For professional results, smooth bead of sealant with a finishing tool.
6. Clean up excess uncured sealant with a damp cloth before it skins over (15 minutes). Cured sealant must be cut or scraped away.
7. Allow sealant to dry 2 hours before painting with latex paints. Cool or humid conditions or type of paint used may require longer dry time.
8. Reseal cartridge for storage and reuse.

**For Best Results:**

- Apply in temperatures above 40°F.
- Do not apply if rain or freezing temperatures are forecasted before full cure can occur. Cold weather and high humidity will slow down cure time.
- Do not use below waterline or for marine or automobile applications, or filling surface defects.
- Joint size should not exceed 3” wide by 1/2” deep. If joint depth or width exceeds 1/2”, use foam backer rod.

- Store sealant away from extreme heat or cold.
- Substrates made of methylmethacrylate, polycarbonate, polypropylene, polyethylene and polytetrafluoroethylene do not allow for best adhesion and compatibility with sealant. Try test area before using.

**Typical Physical & Chemical Characteristics:**

Vehicle:	Acrylic Emulsion
Solids:	74% by weight
Filler:	Calcium carbonate
Volatile:	Water
Flash Point:	None
Density	10.9 lbs. / gal.
Application Temperature:	40°F to 100°F
Service Temperature:	-30°F to 180° F
Tooling Time:	15 minutes
Tack Free Time:	30 minutes
Through Dry:	24 hours (@ 3/16" bead)
Freeze/Thaw Stability:	Passes 5 cycles of 16 hours at -18°C and 8 hours at 23°C
Dynamic Joint Movement:	± 25%
Consistency:	Smooth
Odor:	Very mild
Paintable:	Yes
Applications:	Interior/Exterior
Shelf Life:	1-year minimum
Coverage:	55 linear feet at 3/16" diameter bead
ASTM SPEC:	ASTM C920, Type S, Grade NS Class 25
SDS No:	00040003001

**Clean Up:**

Clean up excess uncured sealant with a damp cloth or sponge before it skins over. Wash hands and tools with warm water and soap. Cured sealant must be cut or scraped away. Store in a cool, dry place away from extreme heat or cold.

**Safety:**

See product label or Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit [dap.com](http://dap.com).

**Lifetime Guarantee:**

DAP warrants this product for sealant purposes during the lifetime of your home when applied within one year of purchase and as directed. If product fails to perform when used as directed, return container and sales receipt to DAP Products Inc., TCS, 2400 Boston St., Baltimore, MD 21224 for replacement product or sales price refund. DAP will not be liable for incidental or consequential damages.