

## PRODUCT SAFETY DATA SHEET

### Manufacturer

Name of Company : Panasonic Corporation Energy Company  
 Address : 1-1, Matsushita-cho, Moriguchi, Osaka 570-8511 Japan  
 Department : Energy Solution Business Unit, Planning Group  
 Contact Person : Shuji Asano  
 Telephone number : +81-6-6994-4409  
 Facsimile number : +81-6-6991-6140  
 For emergency : Tel. (Working hours) +81-6-6994-4409  
 : Tel. (Holiday) +81-6-6991-1141



Document number : PMH-PSDS-110113

Issued : Jan, 13<sup>th</sup>, 2011

Name of product : Nickel-Metal Hydride Storage Battery  
 The models described as HHR-380AB28, HHR-20SCRY01  
 HHR-200AB24, HHR-30SCPYP20, HHR-20SCPYP14, HHR-150AAF9

### Substance Identification

Substance : Nickel-Metal Hydride Storage Battery  
 CAS No. : Not Specified.

### Composition

Common Chemical name	CAS number	Concentration/ Percentage Range
Nickel Hydroxide	12054-48-7	15-25%
Cobalt Hydroxide	21041-93-0	1-5%
Hydrogen absorbing alloy	7440-02-0(Ni) 7440-48-4(Co) 7439-96-5(Mn) 7429-90-5(Al)	20-35%
Nickel	7440-02-0	3-10%
Iron	7439-89-6	10-25%
Potassium Hydroxide	1310-58-3	0-15%
Sodium Hydroxide	1310-73-2	
Lithium Hydroxide	1310-65-2	

**Hazardous and Toxicity Class:**

Class name	: Not applicable
Hazard	: In case of battery shortage, there is possibility of heat up of battery and/or leakage.
Toxicity	: In case of burning of plastic parts there is possibility of gas generation, which has toxic for eyes, nose and throat.

---

**First Aid Measures**

In case of electrolyte leakage from the battery, necessary actions to be taken are described as follows.

- Eye contact : Flush the eyes with plenty of clean water such as tap water for more than 15 minutes without rubbing and immediately take a medical treatment.  
If appropriate procedures are not taken, it may cause a loss of sight.
- Skin contact : Wash the contact skin area off immediately with plenty of clean water such as tap water using soap, otherwise it might cause sore on the skin.
- Inhalation : Move the exposed person to fresh air area immediately.  
And take a medical treatment immediately.
- 

**Fire Fighting Measures**

1. Suitable fire extinguishing media are dry sand and chemical powder fire extinguisher.
  2. When in firefighting, the air respiratory protection should be used because acrid or harmful gas might be generated when fire is extinguished.
  3. Remove combustibles at once from a firefighting area.
  4. Remove the batteries to safe area at once from firefighting place.
- 

**Measures for electrolyte leakage (Accidental release measures)**

(When the electrolysis liquid leaks from the product)

1. Wiping it off with the dry towel.
  2. The fire should not be brought close to it.
  3. The protection glasses and rubber gloves are put on if necessary.
-

## Handling and Storage

- 1) The terminals of the battery pack should be protected in the packing form to be able to prevent them from external short circuit.
- 2) They are packed by the material with enough strength to prevent them from destroyed by vibrates, impact, fall and accumulation, etc. while transporting them.
- 3) Keep batteries out of water and wet when in storage and transported.
- 4) Keep batteries out of fire and avoid the high temperature atmosphere when in storage and transported.

An example of the high temperature : The high temperature storage like in the car exposed to blazing sun should be avoided.

## Exposure control (in case of electrolyte leakage from the battery)

Acceptable concentration	: Not specified in Japanese industrial hygienic association and ACGIH
Facilities	: Ventilation should be noted such as equipped with the limited spot area exhaust device used for the battery storage place.
Protective clothing	: The protection glasses, the mask for disaster prevention, and the protection gloves are used.

## Physical and Chemical Properties

Externals	: The nickel hydrogen storage battery is stored in the plastic resin case or tube. The voltage value depends on the number of built-in batteries used in battery pack.
-----------	--

## Stability and Reactivity

The external short, the crushing transformation, and the high temperature exposure of 100°C or more cause abnormal heat generation and the fire.

## Toxicological information

When the electrolyte leaks from the product

Acute toxicity : LD50 2g/Kg oral rat

(Based on material safety data sheet of liquid potassium hydro oxide)

Stimulation : The cornea inflammation is caused when the electrolyte gets in eye.

The long time exposure to the electrolyte stimulates mucous membranes of the bronchial tube and eye.

**Exposure control** (in case of electrolyte leakage from the battery)

Acceptable concentration : Not specified in Japanese industrial hygienic association and ACGIH

Facilities : Ventilation should be noted such as equipped with the limited spot area exhaust device used for the battery storage place.

Protective clothing : The protection glasses, the mask for disaster prevention, and the protection gloves are used.

**Physical and Chemical Properties**

Externals : The nickel hydrogen storage battery is stored in the plastic resin case or tube. The voltage value depends on the number of built-in batteries used in battery pack.

**Stability and Reactivity**

The external short, the crushing transformation, and the high temperature exposure of 100°C or more cause abnormal heat generation and the fire.

**Toxicological information**

When the electrolyte leaks from the product

Acute toxicity : LD50 2g/Kg oral rat

(Based on material safety data sheet of liquid potassium hydroxide)

Stimulation : The cornea inflammation is caused when the electrolyte gets in eye.

The long time exposure to the electrolyte stimulates mucous membranes of the bronchial tube and eye.

**Ecological Information**

Heavy metal quantity for cell

Hg < 0.5ppm Measurement Analysis: Atomic Absorption Spectrometer

Cd < 5.0ppm Measurement Analysis: Atomic Absorption Spectrometer

Pb < 40ppm Measurement Analysis: Atomic Absorption Spectrometer

**Disposal Considerations**

When the battery is worn out, dispose of it under the ordinances of each local government or the related laws and regulations.

## Disposal Considerations

When the battery is worn out, dispose of it under the ordinances of each local government or the related laws and regulations.

---

## Transport Information

1. During the transportation of a large amount of batteries by ship, trailer or railway, do not leave them in the places of high temperatures and do not allow them to be exposed to dew condensation.
  2. Avoid transportation with the possibility of the collapse of cargo piles and the packing damage.
  3. Protect the terminals of batteries and prevent them from short circuit so as not to cause dangerous heat generation.
- 

## Regulatory Information

- IATA Dangerous Goods Regulations 52<sup>th</sup> Edition Effective 1 January - 31 December 2011
  - ICAO Technical Instructions for the safe transport of dangerous goods by air
  - The product is handled as Non-Dangerous Goods by based on IATA(A123) for air shipment and IMDG(SP963) for sea shipment.
- 

## Others

### References

- Ni-Cd, Ni-MH Panasonic Catalogue and technical handbook.
  - MSDS of Nickel hydroxide and potassium hydroxide and sodium hydroxide from supplier.
  - Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations Volume 1. 16<sup>th</sup> revised edition.
  - IATA Dangerous Goods Regulations 52<sup>th</sup> Edition Effective 1 January -- 31 December 2011
  - Technical Instructions for the Safe Transport of Dangerous Goods by Air (Approved and published by decision of the Council of ICAO) 2003-2004 Edition
-